

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



REPLAST 2C PLASTICS ADHESIVE 210 SEC - 50 ML (comp. A)

Version	Revision Date:	SDS Number:	Date of last issue: 19.01.2017
2.6	29.03.2017	347104-00008	Date of first issue: 04.11.2015

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name	:	REPLAST 2C PLASTICS ADHESIVE 210 SEC - 50 ML (comp. A)
Product code	:	0893500043

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub- stance/Mixture	:	Adhesives
-----------------------------------	---	-----------

1.3 Details of the supplier of the safety data sheet

Company	:	Adolf Wuerth GmbH & Co. KG Reinhold-Würth-Str. 12-17 74653 Künzelsau
Telephone	:	+49 794015 0
Telefax	:	+49 794015 10 00
E-mail address of person responsible for the SDS	:	prodsafe@wuerth.com

1.4 Emergency telephone number

Giftnotrufzentrale Berlin +49 30 30686 790. Gesellschaft (07:00 – 18:00 Uhr) +49 794015 2552

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Acute toxicity, Category 4	H332: Harmful if inhaled.
Skin sensitisation, Category 1	H317: May cause an allergic skin reaction.
Specific target organ toxicity - single ex- posure, Category 3	H335: May cause respiratory irritation.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



REPLAST 2C PLASTICS ADHESIVE 210 SEC - 50 ML (comp. A)

Version	Revision Date:	SDS Number:	Date of last issue:
2.6	29.03.2017	347104-00008	19.01.2017
			Date of first issue: 04.11.2015

Hazard pictograms :



Signal word : Warning

Hazard statements :
H317 May cause an allergic skin reaction.
H332 Harmful if inhaled.
H335 May cause respiratory irritation.

Precautionary statements :
Prevention:
P271 Use only outdoors or in a well-ventilated area.
P272 Contaminated work clothing should not be allowed out of the workplace.
P280 Wear protective gloves.
Response:
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.
P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.
P362 + P364 Take off contaminated clothing and wash it before reuse.

Hazardous components which must be listed on the label:

Hexamethylene diisocyanate, oligomers
Hexamethylene diisocyanate

Additional Labelling

EUH204 Contains isocyanates. May produce an allergic reaction.

2.3 Other hazards

None known.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
Hexamethylene diisocyanate, oligomers	28182-81-2 500-060-2	Acute Tox. 4; H332 Skin Sens. 1; H317 STOT SE 3; H335	>= 70 - < 90
Hexamethylene diisocyanate	822-06-0 212-485-8 615-011-00-1	Acute Tox. 4; H302 Acute Tox. 1; H330 Skin Corr. 1C; H314	>= 0,1 - < 0,5

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



REPLAST 2C PLASTICS ADHESIVE 210 SEC - 50 ML (comp. A)

Version 2.6	Revision Date: 29.03.2017	SDS Number: 347104-00008	Date of last issue: 19.01.2017 Date of first issue: 04.11.2015
----------------	------------------------------	-----------------------------	---

		Eye Dam. 1; H318 Resp. Sens. 1; H334 Skin Sens. 1; H317 STOT SE 3; H335	
--	--	--	--

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

- | | |
|----------------------------|---|
| General advice | : In the case of accident or if you feel unwell, seek medical advice immediately.
When symptoms persist or in all cases of doubt seek medical advice. |
| Protection of first-aiders | : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists. |
| If inhaled | : If inhaled, remove to fresh air.
If not breathing, give artificial respiration.
If breathing is difficult, give oxygen.
Get medical attention if symptoms occur. |
| In case of skin contact | : In case of contact, immediately flush skin with soap and plenty of water.
Remove contaminated clothing and shoes.
Get medical attention.
Wash clothing before reuse.
Thoroughly clean shoes before reuse. |
| In case of eye contact | : Flush eyes with water as a precaution.
Get medical attention if irritation develops and persists. |
| If swallowed | : If swallowed, DO NOT induce vomiting.
Get medical attention if symptoms occur.
Rinse mouth thoroughly with water. |

4.2 Most important symptoms and effects, both acute and delayed

- | | |
|-------|--|
| Risks | : May cause an allergic skin reaction.
Harmful if inhaled.
May cause respiratory irritation. |
|-------|--|

4.3 Indication of any immediate medical attention and special treatment needed

- | | |
|-----------|---|
| Treatment | : Treat symptomatically and supportively. |
|-----------|---|

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



REPLAST 2C PLASTICS ADHESIVE 210 SEC - 50 ML (comp. A)

Version	Revision Date:	SDS Number:	Date of last issue: 19.01.2017
2.6	29.03.2017	347104-00008	Date of first issue: 04.11.2015

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Water spray
Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical

Unsuitable extinguishing media : None known.

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Exposure to combustion products may be a hazard to health.

Hazardous combustion products : Carbon oxides
Nitrogen oxides (NO_x)
Metal oxides
Silicon oxides

5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.
Use personal protective equipment.

Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Use water spray to cool unopened containers.
Remove undamaged containers from fire area if it is safe to do so.
Evacuate area.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.
Follow safe handling advice and personal protective equipment recommendations.

6.2 Environmental precautions

Environmental precautions : Discharge into the environment must be avoided.
Prevent further leakage or spillage if safe to do so.
Prevent spreading over a wide area (e.g. by containment or oil barriers).
Retain and dispose of contaminated wash water.
Local authorities should be advised if significant spillages cannot be contained.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



REPLAST 2C PLASTICS ADHESIVE 210 SEC - 50 ML (comp. A)

Version	Revision Date:	SDS Number:	Date of last issue: 19.01.2017
2.6	29.03.2017	347104-00008	Date of first issue: 04.11.2015

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material.
For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped, store recovered material in appropriate container. Clean up remaining materials from spill with suitable absorbent.
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation : Use with local exhaust ventilation.

Advice on safe handling : Do not get on skin or clothing.
Do not breathe vapours or spray mist.
Do not swallow.
Avoid contact with eyes.
Handle in accordance with good industrial hygiene and safety practice.
Keep container tightly closed.
Take care to prevent spills, waste and minimize release to the environment.

Hygiene measures : Ensure that eye flushing systems and safety showers are located close to the working place. When using do not eat, drink or smoke. Wash contaminated clothing before re-use.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Keep in properly labelled containers. Store locked up. Keep tightly closed. Keep in a cool, well-ventilated place. Store in accordance with the particular national regulations.

Advice on common storage : Do not store with the following product types:
Strong oxidizing agents

Storage class (TRGS 510) : 10, Combustible liquids

7.3 Specific end use(s)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



REPLAST 2C PLASTICS ADHESIVE 210 SEC - 50 ML (comp. A)

Version 2.6 Revision Date: 29.03.2017 SDS Number: 347104-00008 Date of last issue: 19.01.2017
Date of first issue: 04.11.2015

Specific use(s) : No data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Aluminum hydroxide	21645-51-2	AGW (Inhalable fraction)	10 mg/m ³	DE TRGS 900
Peak-limit: excursion factor (category)	2;(II)			
Further information	General dust value. For this substance no specific occupational exposure limit value is established, since the AGS does not yet have information regarding unspecific action on the respiratory organs in excess of the normal values., Commission for dangerous substances, Senate commission for the review of compounds at the work place dangerous for the health (MAK-commission).			
		AGW (Alveolate fraction)	1,25 mg/m ³	DE TRGS 900
Peak-limit: excursion factor (category)	2;(II)			
Further information	General dust value. For this substance no specific occupational exposure limit value is established, since the AGS does not yet have information regarding unspecific action on the respiratory organs in excess of the normal values., Commission for dangerous substances, Senate commission for the review of compounds at the work place dangerous for the health (MAK-commission).			
Dimethyl siloxane reaction with silica	67762-90-7	AGW (Inhalable fraction)	4 mg/m ³ (Silica)	DE TRGS 900
Further information	Senate commission for the review of compounds at the work place dangerous for the health (MAK-commission)., Colloidal amorphous silica, including pyrogenic silica and in wet processes manufactured silica (precipitated silica, sili-cagel)., When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			
Hexamethylene diisocyanate	822-06-0	AGW	0,005 ppm 0,035 mg/m ³	TRGS 430
Peak-limit: excursion factor (category)	1;=2=(I)			
Further information	The exposure limit is established for monomers. For regulatory details on oligomers and polymers see TRGS 430 'Isocyanate', airway sensitizing substance, Senate commission for the review of compounds at the work place dangerous for the health (MAK-commission).			
		AGW (Vapour and aerosols)	0,005 ppm 0,035 mg/m ³	DE TRGS 900
Peak-limit: excursion factor (category)	1;=2=(I)			

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



REPLAST 2C PLASTICS ADHESIVE 210 SEC - 50 ML (comp. A)

Version 2.6 Revision Date: 29.03.2017 SDS Number: 347104-00008 Date of last issue: 19.01.2017
Date of first issue: 04.11.2015

Further information	Senate commission for the review of compounds at the work place dangerous for the health (MAK-commission)., Sum of vapor and aerosols., The exposure limit is established for monomers. For regulatory details on oligomers and polymers see TRGS 430 'Isocyanate'., Substance sensitizing through the respiratory system
---------------------	---

Biological occupational exposure limits

Substance name	CAS-No.	Control parameters	Sampling time	Basis
Hexamethylene diisocyanate	822-06-0	hexamethylendiamine: 15 µg/g creatinine (Urine)	Immediately after exposure or after working hours	TRGS 903

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
Hexamethylene diisocyanate, oligomers	Workers	Inhalation	Long-term local effects	0,5 mg/m ³
	Workers	Inhalation	Acute local effects	1 mg/m ³
Metal Oxide	Workers	Inhalation	Long-term local effects	3,59 mg/m ³
	Consumers	Ingestion	Long-term systemic effects	2,37 mg/kg bw/day
Zeolites	Workers	Inhalation	Long-term systemic effects	3 mg/m ³
	Workers	Skin contact	Long-term systemic effects	2,5 mg/kg bw/day
	Consumers	Inhalation	Long-term local effects	0,003 mg/m ³
	Consumers	Skin contact	Long-term systemic effects	1,25 mg/kg bw/day
	Consumers	Ingestion		1,25 mg/kg bw/day
Hexamethylene diisocyanate	Workers	Inhalation	Long-term systemic effects	0,035 mg/m ³
	Workers	Inhalation	Acute systemic effects	0,07 mg/m ³
	Workers	Inhalation	Long-term local effects	0,035 mg/m ³
	Workers	Inhalation	Acute local effects	0,07 mg/m ³

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
Hexamethylene diisocyanate, oligomers	Fresh water	0,127 mg/l
	Marine water	0,0127 mg/l
	Intermittent use/release	1,27 mg/l
	Sewage treatment plant	38,3 mg/l
	Fresh water sediment	266700 mg/kg
	Marine sediment	26670 mg/kg
	Soil	53182 mg/kg

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



REPLAST 2C PLASTICS ADHESIVE 210 SEC - 50 ML (comp. A)

Version 2.6 Revision Date: 29.03.2017 SDS Number: 347104-00008 Date of last issue: 19.01.2017
Date of first issue: 04.11.2015

Metal Oxide	Fresh water	74,9 µg/l
	Sewage treatment plant	20 mg/l
Zeolites	Fresh water	3,2 mg/l
	Marine water	0,32 mg/l
	Sewage treatment plant	95 mg/l
	Soil	600 mg/kg
Hexamethylene diisocyanate	Fresh water	0,0774 mg/l
	Marine water	0,00774 mg/l
	Intermittent use/release	0,774 mg/l
	Sewage treatment plant	8,42 mg/l
	Fresh water sediment	0,01334 mg/kg
	Marine sediment	0,001344 mg/kg
	Soil	0,0026 mg/kg

8.2 Exposure controls

Engineering measures

Minimize workplace exposure concentrations.
Use with local exhaust ventilation.

Personal protective equipment

Eye protection : Wear the following personal protective equipment:
Safety glasses

Hand protection

Material : PVA
Break through time : 240 - 480 min
Glove thickness : 0,25 - 0,38 mm
Directive : DIN EN 374

Material : Neoprene
Break through time : 240 - 480 min
Glove thickness : 0,25 - 0,38 mm
Directive : DIN EN 374

Material : Natural Rubber
Break through time : 240 - 480 min
Glove thickness : 0,25 - 0,38 mm
Directive : DIN EN 374

Remarks : Choose gloves to protect hands against chemicals depending on the concentration and quantity of the hazardous substance and specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.

Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.
Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



REPLAST 2C PLASTICS ADHESIVE 210 SEC - 50 ML (comp. A)

Version	Revision Date:	SDS Number:	Date of last issue: 19.01.2017
2.6	29.03.2017	347104-00008	Date of first issue: 04.11.2015

Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Filter type : Combined particulates and organic vapour type (A-P)

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance	: liquid
Colour	: white
Odour	: No data available
Odour Threshold	: No data available
pH	: No data available
Melting point/freezing point	: No data available
Initial boiling point and boiling range	: No data available
Flash point	: > 200 °C Other information: No data available
Evaporation rate	: No data available
Flammability (solid, gas)	: Not applicable
Upper explosion limit / Upper flammability limit	: No data available
Lower explosion limit / Lower flammability limit	: No data available
Vapour pressure	: No data available
Relative vapour density	: No data available
Density	: 1,3 g/cm ³ (20 °C)
Solubility(ies) Water solubility	: No data available
Partition coefficient: n-octanol/water	: Not applicable
Auto-ignition temperature	: No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



REPLAST 2C PLASTICS ADHESIVE 210 SEC - 50 ML (comp. A)

Version	Revision Date:	SDS Number:	Date of last issue: 19.01.2017
2.6	29.03.2017	347104-00008	Date of first issue: 04.11.2015

Decomposition temperature : No data available

Viscosity

Viscosity, dynamic : 13.000 cP (23 °C)

Viscosity, kinematic : No data available

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

9.2 Other information

Particle size : Not applicable

SECTION 10: Stability and reactivity

10.1 Reactivity

Not classified as a reactivity hazard.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions : Can react with strong oxidizing agents.

10.4 Conditions to avoid

Conditions to avoid : None known.

10.5 Incompatible materials

Materials to avoid : Oxidizing agents

10.6 Hazardous decomposition products

No hazardous decomposition products are known.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Information on likely routes of exposure : Inhalation
Skin contact
Ingestion
Eye contact

Acute toxicity

Harmful if inhaled.

Product:

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



REPLAST 2C PLASTICS ADHESIVE 210 SEC - 50 ML (comp. A)

Version	Revision Date:	SDS Number:	Date of last issue: 19.01.2017
2.6	29.03.2017	347104-00008	Date of first issue: 04.11.2015

Acute inhalation toxicity : Acute toxicity estimate: 1,32 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: Calculation method

Components:

Hexamethylene diisocyanate, oligomers:

Acute oral toxicity : LD50 (Rat, female): > 2.500 mg/kg
Method: OECD Test Guideline 423
Assessment: The substance or mixture has no acute oral toxicity

Acute inhalation toxicity : Acute toxicity estimate: 1,5 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: Expert judgement

Acute dermal toxicity : LD50 (Rat): > 2.000 mg/kg
Method: OECD Test Guideline 402
Assessment: The substance or mixture has no acute dermal toxicity

Hexamethylene diisocyanate:

Acute oral toxicity : LD50 (Rat): 959 mg/kg

Acute inhalation toxicity : LC50 (Rat): 124 mg/m³
Exposure time: 4 h
Test atmosphere: vapour
Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 (Rat): > 7.000 mg/kg
Method: OECD Test Guideline 402

Skin corrosion/irritation

Not classified based on available information.

Components:

Hexamethylene diisocyanate, oligomers:

Species: Rabbit
Method: OECD Test Guideline 404
Result: No skin irritation

Hexamethylene diisocyanate:

Species: Rabbit
Method: OECD Test Guideline 404
Result: Corrosive after 1 to 4 hours of exposure

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



REPLAST 2C PLASTICS ADHESIVE 210 SEC - 50 ML (comp. A)

Version	Revision Date:	SDS Number:	Date of last issue: 19.01.2017
2.6	29.03.2017	347104-00008	Date of first issue: 04.11.2015

Serious eye damage/eye irritation

Not classified based on available information.

Components:

Hexamethylene diisocyanate, oligomers:

Species: Rabbit

Method: OECD Test Guideline 405

Result: No eye irritation

Hexamethylene diisocyanate:

Species: Rabbit

Method: OECD Test Guideline 405

Result: Irreversible effects on the eye

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

Not classified based on available information.

Components:

Hexamethylene diisocyanate, oligomers:

Test Type: Local lymph node assay (LLNA)

Exposure routes: Skin contact

Species: Mouse

Method: OECD Test Guideline 429

Result: positive

Assessment: Probability or evidence of skin sensitisation in humans

Exposure routes: Inhalation

Species: Guinea pig

Result: negative

Hexamethylene diisocyanate:

Test Type: Maximisation Test

Exposure routes: Skin contact

Species: Guinea pig

Result: positive

Assessment: Probability or evidence of skin sensitisation in humans

Exposure routes: inhalation (vapour)

Species: Guinea pig

Result: positive

Assessment: Probability of respiratory sensitisation in humans based on animal testing

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



REPLAST 2C PLASTICS ADHESIVE 210 SEC - 50 ML (comp. A)

Version	Revision Date:	SDS Number:	Date of last issue: 19.01.2017
2.6	29.03.2017	347104-00008	Date of first issue: 04.11.2015

Germ cell mutagenicity

Not classified based on available information.

Components:

Hexamethylene diisocyanate, oligomers:

Genotoxicity in vitro	: Test Type: In vitro mammalian cell gene mutation test Method: OECD Test Guideline 476 Result: negative
	: Test Type: Bacterial reverse mutation assay (AMES) Method: OECD Test Guideline 471 Result: negative
	: Test Type: Chromosome aberration test in vitro Method: OECD Test Guideline 473 Result: negative
Genotoxicity in vivo	: Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay) Species: Mouse Application Route: Ingestion Result: negative

Hexamethylene diisocyanate:

Genotoxicity in vitro	: Test Type: Bacterial reverse mutation assay (AMES) Result: negative
Genotoxicity in vivo	: Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay) Species: Mouse Application Route: inhalation (vapour) Result: negative

Carcinogenicity

Not classified based on available information.

Components:

Hexamethylene diisocyanate:

Species: Rat
Application Route: inhalation (vapour)
Exposure time: 2 Years
Method: OECD Test Guideline 453
Result: negative

Reproductive toxicity

Not classified based on available information.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



REPLAST 2C PLASTICS ADHESIVE 210 SEC - 50 ML (comp. A)

Version	Revision Date:	SDS Number:	Date of last issue: 19.01.2017
2.6	29.03.2017	347104-00008	Date of first issue: 04.11.2015

Components:

Hexamethylene diisocyanate:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: inhalation (vapour)
Method: OECD Test Guideline 422
Result: negative

Effects on foetal development : Test Type: Embryo-foetal development
Species: Rat
Application Route: inhalation (vapour)
Method: OECD Test Guideline 414
Result: negative

STOT - single exposure

May cause respiratory irritation.

Components:

Hexamethylene diisocyanate, oligomers:

Assessment: May cause respiratory irritation.

Hexamethylene diisocyanate:

Assessment: May cause respiratory irritation.

STOT - repeated exposure

Not classified based on available information.

Components:

Hexamethylene diisocyanate:

Exposure routes: inhalation (vapour)
Assessment: No significant health effects observed in animals at concentrations of 1 mg/l/6h/d or less.

Repeated dose toxicity

Components:

Hexamethylene diisocyanate:

Species: Rat
NOAEL: 0,000034 mg/l
Application Route: inhalation (vapour)
Exposure time: 2 yr

Aspiration toxicity

Not classified based on available information.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



REPLAST 2C PLASTICS ADHESIVE 210 SEC - 50 ML (comp. A)

Version	Revision Date:	SDS Number:	Date of last issue: 19.01.2017
2.6	29.03.2017	347104-00008	Date of first issue: 04.11.2015

SECTION 12: Ecological information

12.1 Toxicity

Components:

Hexamethylene diisocyanate, oligomers:

Toxicity to fish	:	LC50 (Danio rerio (zebra fish)): > 100 mg/l Exposure time: 96 h Method: Directive 67/548/EEC, Annex V, C.1.
Toxicity to daphnia and other aquatic invertebrates	:	EL50 (Daphnia magna (Water flea)): 127 mg/l Exposure time: 48 h Method: Directive 67/548/EEC, Annex V, C.2.
Toxicity to algae	:	EC10 (Desmodesmus subspicatus (green algae)): 370 mg/l Exposure time: 72 h ErC50 (Desmodesmus subspicatus (green algae)): > 1.000 mg/l Exposure time: 72 h
Toxicity to microorganisms	:	EC10 : 880 mg/l Exposure time: 3 h Method: OECD Test Guideline 209

Hexamethylene diisocyanate:

Toxicity to fish	:	LC0 (Danio rerio (zebra fish)): 82,8 mg/l Exposure time: 96 h Method: Directive 67/548/EEC, Annex V, C.1.
Toxicity to daphnia and other aquatic invertebrates	:	EC0 (Daphnia magna (Water flea)): 89,1 mg/l Exposure time: 48 h Method: Directive 67/548/EEC, Annex V, C.2.
Toxicity to algae	:	EC50 (Desmodesmus subspicatus (green algae)): > 77,4 mg/l Exposure time: 72 h Method: Directive 67/548/EEC, Annex V, C.3. NOEC (Desmodesmus subspicatus (green algae)): 11,7 mg/l Exposure time: 72 h Method: Directive 67/548/EEC, Annex V, C.3.
Toxicity to microorganisms	:	EC50 : 842 mg/l Exposure time: 3 h

12.2 Persistence and degradability

Components:

Hexamethylene diisocyanate, oligomers:

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



REPLAST 2C PLASTICS ADHESIVE 210 SEC - 50 ML (comp. A)

Version	Revision Date:	SDS Number:	Date of last issue: 19.01.2017
2.6	29.03.2017	347104-00008	Date of first issue: 04.11.2015

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 1 %
Exposure time: 28 d
Method: Regulation (EC) No. 440/2008, Annex, C.4-E

Hexamethylene diisocyanate:

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 42 %
Exposure time: 28 d
Method: Regulation (EC) No. 440/2008, Annex, C.4-D

12.3 Bioaccumulative potential

Components:

Hexamethylene diisocyanate, oligomers:

Partition coefficient: n- : log Pow: > 4
octanol/water Remarks: Calculation

Hexamethylene diisocyanate:

Partition coefficient: n- : log Pow: 0,02
octanol/water Remarks: Based on data from similar materials

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Not relevant

12.6 Other adverse effects

No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Dispose of in accordance with local regulations.
According to the European Waste Catalogue, Waste Codes
are not product specific, but application specific.
Waste codes should be assigned by the user, preferably in
discussion with the waste disposal authorities.

Contaminated packaging : Empty containers should be taken to an approved waste han-
dling site for recycling or disposal.
If not otherwise specified: Dispose of as unused product.

Waste Code : The following Waste Codes are only suggestions:

used product
080409, waste adhesives and sealants containing organic
solvents or other dangerous substances

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



REPLAST 2C PLASTICS ADHESIVE 210 SEC - 50 ML (comp. A)

Version	Revision Date:	SDS Number:	Date of last issue: 19.01.2017
2.6	29.03.2017	347104-00008	Date of first issue: 04.11.2015

unused product
080409, waste adhesives and sealants containing organic solvents or other dangerous substances

uncleaned packagings
150110, packaging containing residues of or contaminated by dangerous substances

SECTION 14: Transport information

14.1 UN number

ADN	:	Not regulated as a dangerous good
ADR	:	Not regulated as a dangerous good
RID	:	Not regulated as a dangerous good
IMDG	:	Not regulated as a dangerous good
IATA	:	UN 3334

14.2 UN proper shipping name

ADN	:	Not regulated as a dangerous good
ADR	:	Not regulated as a dangerous good
RID	:	Not regulated as a dangerous good
IMDG	:	Not regulated as a dangerous good
IATA	:	Aviation regulated liquid, n.o.s. (Hexamethylene diisocyanate, oligomers)

14.3 Transport hazard class(es)

ADN	:	Not regulated as a dangerous good
ADR	:	Not regulated as a dangerous good
RID	:	Not regulated as a dangerous good
IMDG	:	Not regulated as a dangerous good
IATA	:	9

14.4 Packing group

ADN	:	Not regulated as a dangerous good
ADR	:	Not regulated as a dangerous good
RID	:	Not regulated as a dangerous good
IMDG	:	Not regulated as a dangerous good
IATA (Cargo)	:	
Packing instruction (cargo aircraft)	:	964

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



REPLAST 2C PLASTICS ADHESIVE 210 SEC - 50 ML (comp. A)

Version 2.6	Revision Date: 29.03.2017	SDS Number: 347104-00008	Date of last issue: 19.01.2017 Date of first issue: 04.11.2015
----------------	------------------------------	-----------------------------	---

Packing instruction (LQ) : Y964
Packing group : III
Labels : Miscellaneous

IATA (Passenger)

Packing instruction (passenger aircraft) : 964
Packing instruction (LQ) : Y964
Packing group : III
Labels : Miscellaneous

14.5 Environmental hazards

ADN : Not regulated as a dangerous good
ADR : Not regulated as a dangerous good
RID : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good

14.6 Special precautions for user

Not applicable

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Remarks : Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII) : Not applicable

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : Not applicable

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

Regulation (EC) No 850/2004 on persistent organic pollutants : Not applicable

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals : Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.
Not applicable

Water contaminating class (Germany) : WGK 1 slightly water endangering
Classification according VwVwS, Annex 4.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



REPLAST 2C PLASTICS ADHESIVE 210 SEC - 50 ML (comp. A)

Version	Revision Date:	SDS Number:	Date of last issue: 19.01.2017
2.6	29.03.2017	347104-00008	Date of first issue: 04.11.2015

Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)
Volatile organic compounds (VOC) content: 0 %, 0 g/l
Remarks: VOC content excluding water

Other regulations:
TRGS 430 (German regulatory requirements)

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

15.2 Chemical safety assessment

A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

Full text of H-Statements

H302	: Harmful if swallowed.
H314	: Causes severe skin burns and eye damage.
H317	: May cause an allergic skin reaction.
H318	: Causes serious eye damage.
H330	: Fatal if inhaled.
H332	: Harmful if inhaled.
H334	: May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	: May cause respiratory irritation.

Full text of other abbreviations

Acute Tox.	: Acute toxicity
Eye Dam.	: Serious eye damage
Resp. Sens.	: Respiratory sensitisation
Skin Corr.	: Skin corrosion
Skin Sens.	: Skin sensitisation
STOT SE	: Specific target organ toxicity - single exposure
DE TRGS 900	: Germany. TRGS 900 - Occupational exposure limit values.
TRGS 430	: Germany. TRGS 430 - Isocyanates
TRGS 903	: TRGS 903 - Biological limit values
DE TRGS 900 / AGW	: Time Weighted Average
TRGS 430 / AGW	: Occupational Exposure Limit

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System;

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



REPLAST 2C PLASTICS ADHESIVE 210 SEC - 50 ML (comp. A)

Version	Revision Date:	SDS Number:	Date of last issue: 19.01.2017
2.6	29.03.2017	347104-00008	Date of first issue: 04.11.2015

GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Sources of key data used to compile the Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Classification of the mixture:

Acute Tox. 4	H332
Skin Sens. 1	H317
STOT SE 3	H335

Classification procedure:

Calculation method
Calculation method
Calculation method

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

DE / EN