

RKD-FLEX SEALANT



Sealant for sealing cable and pipe openings in areas contacting the ground.

Ready for processing

Fast processing.

Permanently elastic

Can be processed further afterward.

Pasty consistency

Does not run.

Good adhesion on dry and moist surfaces

Color	Content in mL	Art. No.	P. Qty.
Gray	310	0892 350 310	6

Instructions:

Before processing the RKD-FLEX, the cartridge should be heated up to 30 °C (place it in warm water). After cleaning the opening of dust, sand etc., a PU foam (e.g. PURLOGIC® TOP) securing block is created at a depth of 10 cm. The RKD-FLEX can then be introduced to the opening. The minimum layer thickness here should be 8 cm. In the case of cable openings, the cable should be shaken once after sealing. Then fill the resulting empty spaces with sealant. The cables should be de-energized. Using a spreader, press on and smooth out the

sealant to form approx. 1 cm-wide edging around the cable. Finally, seal the edging with the fixing cement.

Field of application:

Sealant for sealing cable and pipe openings in areas contacting the ground. Hollow spaces can also be sealed against pressing water with RKD-FLEX. Suitable application surfaces: Concrete, brick, mortar, plaster and other mineral building materials, ceramic, PVC, polyethylene and polypropylene.

Notes:

The ratio of the sealant to the diameter ratio of the opening should not drop below 1.5:1. The maximum diameter of the opening should not exceed 300 mm. Approx. 1.6 kg is consumed per hollow space. Application surfaces can be dry, moist or wet, but they must be free of grease, tar and oil.

Technical data:

Base	Polyolefin
Processing temperature	+5 °C to +35 °C
Consistency	Pasty
Density	1.60 g/cm ³
Application surface temperature	+5 °C to +30 °C
Shelf life at +5 °C to +25 °C	24 months
Heat resistance	+50 °C

This information is only a recommendation based on our experience. Preliminary testing required.

Additional articles:

PURLOGIC® Top
Art. No. 0892 142, 0892 142 1

Fixing Cement
Art. No. 0890 350, 0890 351

Cartridge Gun
Art. No. 0891...

Safety Glove
Art. No. 0899...