

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



SMP ADHESIVE SEALANT GREY - 290 ML

Version	Revision Date:	SDS Number:	Date of last issue: 07.12.2016
1.4	10.03.2017	564828-00005	Date of first issue: 17.03.2016

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : SMP ADHESIVE SEALANT GREY - 290 ML

Product code : 0893237101

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub- : Sealant
stance/Mixture

1.3 Details of the supplier of the safety data sheet

Company : Adolf Wuerth GmbH & Co. KG
Reinhold-Würth-Str. 12-17
74653 Künzelsau

Telephone : +49 794015 0

Telefax : +49 794015 10 00

E-mail address of person : prodsafe@wuerth.com
responsible for the SDS

1.4 Emergency telephone number

Giftnotrufzentrale Berlin +49 30 30686 790. Gesellschaft (07:00 – 18:00 Uhr) +49 794015 2552

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Skin sensitisation, Category 1 H317: May cause an allergic skin reaction.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : Warning

Hazard statements : H317 May cause an allergic skin reaction.

Precautionary statements : **Prevention:**

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



SMP ADHESIVE SEALANT GREY - 290 ML

Version 1.4 Revision Date: 10.03.2017 SDS Number: 564828-00005 Date of last issue: 07.12.2016
Date of first issue: 17.03.2016

P272 Contaminated work clothing should not be allowed out of the workplace.

P280 Wear protective gloves.

Response:

P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.

P362 + P364 Take off contaminated clothing and wash it before reuse.

Hazardous components which must be listed on the label:

3-(2-aminoethylamino) propyltrimethoxysilane

Dioctyltin bis(acetylacetonate)

N-[3-(dimethoxymethylsilyl)propyl]ethylenediamine

Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate

2.3 Other hazards

None known.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
trimethoxyvinylsilane	2768-02-7 220-449-8 01-2119513215-52	Flam. Liq. 3; H226 Acute Tox. 4; H332	$\geq 1 - < 10$
3-(2-aminoethylamino) propyltrimethoxysilane	1760-24-3 217-164-6 01-2119970215-39	Acute Tox. 4; H332 Eye Dam. 1; H318 Skin Sens. 1; H317	$\geq 0,1 - < 1$
Dioctyltin bis(acetylacetonate)	54068-28-9 483-270-6 01-0000020199-67	Skin Sens. 1B; H317 Repr. 2; H361d STOT RE 1; H372	$\geq 0,1 - < 1$
N-[3-(dimethoxymethylsilyl)propyl]ethylenediamine	3069-29-2 221-336-6 01-2119963926-21	Acute Tox. 4; H302 Skin Irrit. 2; H315 Eye Dam. 1; H318 Skin Sens. 1A; H317	$\geq 0,1 - < 1$
Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	Not Assigned 01-2119491304-40	Skin Sens. 1A; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410	$\geq 0,025 - < 0,1$

For explanation of abbreviations see section 16.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



SMP ADHESIVE SEALANT GREY - 290 ML

Version	Revision Date:	SDS Number:	Date of last issue: 07.12.2016
1.4	10.03.2017	564828-00005	Date of first issue: 17.03.2016

SECTION 4: First aid measures

4.1 Description of first aid measures

- | | | |
|----------------------------|---|---|
| General advice | : | In the case of accident or if you feel unwell, seek medical advice immediately.
When symptoms persist or in all cases of doubt seek medical advice. |
| Protection of first-aiders | : | First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists. |
| If inhaled | : | If inhaled, remove to fresh air.
Get medical attention. |
| In case of skin contact | : | In case of contact, immediately flush skin with soap and plenty of water.
Remove contaminated clothing and shoes.
Get medical attention.
Wash clothing before reuse.
Thoroughly clean shoes before reuse. |
| In case of eye contact | : | Flush eyes with water as a precaution.
Get medical attention if irritation develops and persists. |
| If swallowed | : | If swallowed, DO NOT induce vomiting.
Get medical attention.
Rinse mouth thoroughly with water. |

4.2 Most important symptoms and effects, both acute and delayed

- | | | |
|-------|---|--------------------------------------|
| Risks | : | May cause an allergic skin reaction. |
|-------|---|--------------------------------------|

4.3 Indication of any immediate medical attention and special treatment needed

- | | | |
|-----------|---|---|
| Treatment | : | Treat symptomatically and supportively. |
|-----------|---|---|

SECTION 5: Firefighting measures

5.1 Extinguishing media

- | | | |
|--------------------------------|---|--|
| Suitable extinguishing media | : | Water spray
Alcohol-resistant foam
Carbon dioxide (CO ₂)
Dry chemical |
| Unsuitable extinguishing media | : | None known. |

5.2 Special hazards arising from the substance or mixture

- | | | |
|---------------------------------------|---|--|
| Specific hazards during fire-fighting | : | Exposure to combustion products may be a hazard to health. |
|---------------------------------------|---|--|

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



SMP ADHESIVE SEALANT GREY - 290 ML

Version	Revision Date:	SDS Number:	Date of last issue: 07.12.2016
1.4	10.03.2017	564828-00005	Date of first issue: 17.03.2016

Hazardous combustion products : Carbon oxides
Metal oxides
Silicon oxides
Nitrogen oxides (NO_x)

5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.
Use personal protective equipment.

Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Use water spray to cool unopened containers.
Remove undamaged containers from fire area if it is safe to do so.
Evacuate area.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.
Follow safe handling advice and personal protective equipment recommendations.

6.2 Environmental precautions

Environmental precautions : Discharge into the environment must be avoided.
Prevent further leakage or spillage if safe to do so.
Retain and dispose of contaminated wash water.
Local authorities should be advised if significant spillages cannot be contained.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material.
For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped, store recovered material in appropriate container.
Clean up remaining materials from spill with suitable absorbent.
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



SMP ADHESIVE SEALANT GREY - 290 ML

Version	Revision Date:	SDS Number:	Date of last issue: 07.12.2016
1.4	10.03.2017	564828-00005	Date of first issue: 17.03.2016

SECTION 7: Handling and storage

7.1 Precautions for safe handling

- | | |
|-------------------------|--|
| Technical measures | : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section. |
| Local/Total ventilation | : Use only with adequate ventilation. |
| Advice on safe handling | : Do not get on skin or clothing.
Do not swallow.
Avoid contact with eyes.
Handle in accordance with good industrial hygiene and safety practice.
Keep away from water.
Protect from moisture.
Take care to prevent spills, waste and minimize release to the environment. |
| Hygiene measures | : Ensure that eye flushing systems and safety showers are located close to the working place. When using do not eat, drink or smoke. Wash contaminated clothing before re-use. |

7.2 Conditions for safe storage, including any incompatibilities

- | | |
|---|---|
| Requirements for storage areas and containers | : Keep in properly labelled containers. Store in accordance with the particular national regulations. |
| Advice on common storage | : Do not store with the following product types:
Strong oxidizing agents |
| Storage class (TRGS 510) | : 11, Combustible Solids |
| Recommended storage temperature | : 5 - 25 °C |

7.3 Specific end use(s)

- | | |
|-----------------|---------------------|
| Specific use(s) | : No data available |
|-----------------|---------------------|

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Titanium dioxide	13463-67-7	AGW (Inhalable fraction)	10 mg/m ³ (Titanium dioxide)	DE TRGS 900
Peak-limit: excursion factor (category)	2;(II)			
Further information	General dust value. For this substance no specific occupational exposure limit			

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



SMP ADHESIVE SEALANT GREY - 290 ML

Version 1.4 Revision Date: 10.03.2017 SDS Number: 564828-00005 Date of last issue: 07.12.2016
Date of first issue: 17.03.2016

	value is established, since the AGS does not yet have information regarding unspecific action on the respiratory organs in excess of the normal values., Commission for dangerous substances, Senate commission for the review of compounds at the work place dangerous for the health (MAK-commission).			
		AGW (Alveolate fraction)	1,25 mg/m ³ (Titanium dioxide)	DE TRGS 900
Peak-limit: excursion factor (category)	2;(II)			
Further information	General dust value. For this substance no specific occupational exposure limit value is established, since the AGS does not yet have information regarding unspecific action on the respiratory organs in excess of the normal values., Commission for dangerous substances, Senate commission for the review of compounds at the work place dangerous for the health (MAK-commission).			

These substance(s) are inextricably bound in the product and therefore do not contribute to a dust inhalation hazard.

Titanium dioxide

Occupational exposure limits of decomposition products

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Methanol	67-56-1	TWA	200 ppm 260 mg/m ³	2006/15/EC
Further information	Indicative, Identifies the possibility of significant uptake through the skin			
		AGW	200 ppm 270 mg/m ³	DE TRGS 900
Peak-limit: excursion factor (category)	4;(II)			
Further information	Senate commission for the review of compounds at the work place dangerous for the health (MAK-commission)., European Union (The EU has established a limit value: deviations in value and peak limit are possible), Skin absorption, When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
Calcium carbonate	Workers	Inhalation	Long-term systemic effects	10 mg/m ³
	Consumers	Ingestion	Acute systemic effects	6,1 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	10 mg/m ³
	Consumers	Ingestion	Long-term systemic effects	6,1 mg/kg bw/day
Di-isononyl phthalate	Workers	Inhalation	Long-term systemic effects	51,72 mg/m ³
	Workers	Skin contact	Long-term systemic effects	366 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	15,3 mg/m ³

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

**SMP ADHESIVE SEALANT GREY - 290 ML**Version
1.4Revision Date:
10.03.2017SDS Number:
564828-00005Date of last issue: 07.12.2016
Date of first issue: 17.03.2016

	Consumers	Skin contact	Long-term systemic effects	220 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	4,4 mg/kg bw/day
trimethoxyvinylsilane	Workers	Inhalation	Long-term systemic effects	4,9 mg/m3
	Workers	Skin contact	Long-term systemic effects	0,69 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	1,04 mg/m3
	Consumers	Inhalation	Acute systemic effects	93,4 mg/m3
	Consumers	Skin contact	Long-term systemic effects	0,3 mg/kg bw/day
	Consumers	Skin contact	Acute systemic effects	26,9 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	0,3 mg/kg bw/day
Octadecanoic acid, 12-hydroxy-, reaction products with decanoic acid and ethylenediamine	Workers	Inhalation	Acute systemic effects	3 mg/m3
	Workers	Inhalation	Long-term local effects	3 mg/m3
	Workers	Inhalation	Acute local effects	3 mg/m3
	Workers	Skin contact	Long-term local effects	3,75 mg/cm2
	Workers	Skin contact	Acute local effects	11,2 mg/cm2
	Consumers	Skin contact	Long-term local effects	3,75 mg/cm2
	Consumers	Skin contact	Acute local effects	11,2 mg/cm2
	Consumers	Ingestion	Long-term systemic effects	0,56 mg/kg bw/day
Titanium dioxide	Workers	Inhalation	Long-term local effects	10 mg/m3
	Consumers	Ingestion	Long-term systemic effects	700 mg/kg bw/day
3-(2-aminoethylamino) propyltrimethoxysilane	Workers	Inhalation	Long-term systemic effects	35,3 mg/m3
	Workers	Skin contact	Long-term systemic effects	5 mg/kg bw/day
	Workers	Skin contact	Acute systemic effects	5 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	8,7 mg/m3
	Consumers	Skin contact	Long-term systemic effects	2,5 mg/kg bw/day
	Consumers	Skin contact	Acute systemic effects	17 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic	2,5 mg/kg

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



SMP ADHESIVE SEALANT GREY - 290 ML

Version
1.4

Revision Date:
10.03.2017

SDS Number:
564828-00005

Date of last issue: 07.12.2016
Date of first issue: 17.03.2016

			effects	bw/day
Diocetyl tin bis(acetylacetonate)	Workers	Inhalation	Long-term systemic effects	0,091 mg/m3
	Workers	Inhalation	Acute local effects	0,091 mg/m3
	Workers	Inhalation	Long-term local effects	0,091 mg/m3
	Consumers	Inhalation	Long-term systemic effects	0,018 mg/m3
	Consumers	Inhalation	Acute local effects	0,018 mg/m3
	Consumers	Inhalation	Long-term local effects	0,018 mg/m3
N-[3-(dimethoxymethylsilyl)propyl]ethylenediamine	Workers	Inhalation	Long-term systemic effects	12 mg/m3
	Workers	Inhalation	Acute systemic effects	12 mg/m3
	Workers	Skin contact	Long-term systemic effects	1,7 mg/kg bw/day
	Workers	Skin contact	Acute systemic effects	1,7 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	2,9 mg/m3
	Consumers	Inhalation	Acute systemic effects	2,9 mg/m3
	Consumers	Skin contact	Long-term systemic effects	0,83 mg/kg bw/day
	Consumers	Skin contact	Acute systemic effects	0,83 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	0,83 mg/kg bw/day
	Consumers	Ingestion	Acute systemic effects	0,83 mg/kg bw/day
	Workers	Inhalation	Long-term systemic effects	2,35 mg/m3
	Workers	Inhalation	Acute systemic effects	2,35 mg/m3
Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	Workers	Inhalation	Acute local effects	2,35 mg/m3
	Workers	Skin contact	Long-term systemic effects	2,5 mg/kg bw/day
	Workers	Skin contact	Acute systemic effects	2,5 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	0,58 mg/m3
	Consumers	Inhalation	Acute systemic effects	0,58 mg/m3
	Consumers	Inhalation	Acute local effects	0,58 mg/m3
	Consumers	Skin contact	Long-term systemic	1,25 mg/kg

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

**SMP ADHESIVE SEALANT GREY - 290 ML**Version
1.4Revision Date:
10.03.2017SDS Number:
564828-00005Date of last issue: 07.12.2016
Date of first issue: 17.03.2016

			effects	bw/day
	Consumers	Skin contact	Acute systemic effects	1,25 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	1,25 mg/kg bw/day
	Consumers	Ingestion	Acute systemic effects	1,25 mg/kg bw/day

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
Calcium carbonate	Sewage treatment plant	100 mg/l
Di-isononyl phthalate	Soil	30 mg/kg
trimethoxyvinylsilane	Fresh water	0,34 mg/l
	Marine water	0,034 mg/l
	Intermittent use/release	3,4 mg/l
	Sewage treatment plant	110 mg/l
	Fresh water sediment	1,24 mg/kg
	Marine sediment	0,12 mg/kg
	Soil	0,052 mg/kg
Octadecanoic acid, 12-hydroxy-, reaction products with decanoic acid and ethylenediamine	Fresh water	740 µg/l
	Marine water	74 µg/l
	Soil	3714,9 mg/kg
Titanium dioxide	Fresh water	0,184 mg/l
	Marine water	0,0184 mg/l
	Intermittent use/release	0,193 mg/l
	Sewage treatment plant	100 mg/l
	Fresh water sediment	1000 mg/kg
	Marine sediment	100 mg/kg
	Soil	100 mg/kg
3-(2-aminoethylamino) propyltrimethoxysilane	Fresh water	0,062 mg/l
	Marine water	0,0062 mg/l
	Intermittent use/release	0,62 mg/l
	Sewage treatment plant	25 mg/l
	Fresh water sediment	0,22 mg/kg
	Marine sediment	0,022 mg/kg
	Soil	0,0085 mg/kg
N-[3-(dimethoxymethylsilyl)propyl]ethylenediamine	Fresh water	0,062 mg/l
	Marine water	0,0062 mg/l
	Intermittent use/release	0,62 mg/l
	Sewage treatment plant	25 mg/l
	Fresh water sediment	0,24 mg/kg
	Marine sediment	0,024 mg/kg
	Soil	0,01 mg/kg
Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	Fresh water	0,0022 mg/l
	Marine water	0,00022 mg/l

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



SMP ADHESIVE SEALANT GREY - 290 ML

Version 1.4 Revision Date: 10.03.2017 SDS Number: 564828-00005 Date of last issue: 07.12.2016
Date of first issue: 17.03.2016

	Intermittent use/release	0,009 mg/l
	Sewage treatment plant	1 mg/l
	Fresh water sediment	1,05 mg/kg
	Marine sediment	0,11 mg/kg
	Soil	0,21 mg/kg

8.2 Exposure controls

Engineering measures

Processing may form hazardous compounds (see section 10).
Ensure adequate ventilation, especially in confined areas.
Minimize workplace exposure concentrations.

Personal protective equipment

Eye protection : Wear the following personal protective equipment:
Safety glasses

Hand protection

Material : butyl-rubber
Break through time : ≥ 480 min
Glove thickness : 0,5 mm

Material : Fluorinated rubber
Break through time : ≥ 480 min
Glove thickness : 0,4 mm

Remarks : Choose gloves to protect hands against chemicals depending on the concentration and quantity of the hazardous substance and specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.

Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.
Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).

Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Filter type : Self-contained breathing apparatus

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance : paste

Colour : coloured

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



SMP ADHESIVE SEALANT GREY - 290 ML

Version 1.4	Revision Date: 10.03.2017	SDS Number: 564828-00005	Date of last issue: 07.12.2016 Date of first issue: 17.03.2016
----------------	------------------------------	-----------------------------	---

Odour	: characteristic
Odour Threshold	: No data available
pH	: No data available
Melting point/freezing point	: No data available
Initial boiling point and boiling range	: > 34 °C
Flash point	: > 100 °C
Evaporation rate	: Not applicable
Flammability (solid, gas)	: Not classified as a flammability hazard
Upper explosion limit / Upper flammability limit	: 0,2 %(V)
Lower explosion limit / Lower flammability limit	: 0,1 %(V)
Vapour pressure	: Not applicable
Relative vapour density	: Not applicable
Density	: 1,58 g/cm ³ (20 °C)
Solubility(ies) Water solubility	: insoluble
Partition coefficient: n-octanol/water	: Not applicable
Auto-ignition temperature	: 420 °C
Decomposition temperature	: No data available
Viscosity Viscosity, kinematic	: > 20,5 mm ² /s (40 °C)
Flow time	: > 30 s Cross section: 3 mm Method: ISO 2431
Explosive properties	: Not explosive
Oxidizing properties	: The substance or mixture is not classified as oxidizing.

9.2 Other information

Particle size	: No data available
---------------	---------------------

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



SMP ADHESIVE SEALANT GREY - 290 ML

Version	Revision Date:	SDS Number:	Date of last issue: 07.12.2016
1.4	10.03.2017	564828-00005	Date of first issue: 17.03.2016

SECTION 10: Stability and reactivity

10.1 Reactivity

Not classified as a reactivity hazard.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions : Can react with strong oxidizing agents.
Hazardous decomposition products will be formed upon contact with water or humid air.

10.4 Conditions to avoid

Conditions to avoid : Exposure to moisture

10.5 Incompatible materials

Materials to avoid : Oxidizing agents
Water

10.6 Hazardous decomposition products

Contact with water or humid air : Methanol

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Information on likely routes of exposure : Skin contact
Ingestion
Eye contact

Acute toxicity

Not classified based on available information.

Product:

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: Calculation method

Components:

trimethoxyvinylsilane:

Acute oral toxicity : LD50 (Rat): > 5.000 mg/kg
Acute inhalation toxicity : LC50 (Rat): 16,8 mg/l
Exposure time: 4 h
Test atmosphere: vapour

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



SMP ADHESIVE SEALANT GREY - 290 ML

Version	Revision Date:	SDS Number:	Date of last issue: 07.12.2016
1.4	10.03.2017	564828-00005	Date of first issue: 17.03.2016

Acute dermal toxicity : LD50 (Rabbit): > 2.000 mg/kg
Assessment: The substance or mixture has no acute dermal toxicity

3-(2-aminoethylamino) propyltrimethoxysilane:

Acute oral toxicity : LD50 (Rat): 2.295 mg/kg
Method: OPPTS 870.1100

Acute inhalation toxicity : LC50 (Rat): 1,49 - 2,44 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist

Acute dermal toxicity : LD50 (Rabbit): > 2.000 mg/kg
Method: OPPTS 870.1200
Assessment: The substance or mixture has no acute dermal toxicity

Diocetyl tin bis(acetylacetonate):

Acute oral toxicity : LD50 (Rat): 2.500 mg/kg
Method: OECD Test Guideline 423

Acute dermal toxicity : LD50 (Rat): > 2.000 mg/kg
Method: OECD Test Guideline 402
Assessment: The substance or mixture has no acute dermal toxicity

N-[3-(dimethoxymethylsilyl)propyl]ethylenediamine:

Acute oral toxicity : LD50 (Rat): > 200 - 2.000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 5,2 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 (Rabbit): > 5.000 mg/kg

Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate:

Acute oral toxicity : LD50 (Rat): 3.230 mg/kg

Acute dermal toxicity : LD50 (Rat): > 3.170 mg/kg
Assessment: The substance or mixture has no acute dermal toxicity
Remarks: Based on data from similar materials

Skin corrosion/irritation

Not classified based on available information.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



SMP ADHESIVE SEALANT GREY - 290 ML

Version	Revision Date:	SDS Number:	Date of last issue: 07.12.2016
1.4	10.03.2017	564828-00005	Date of first issue: 17.03.2016

Components:

trimethoxyvinylsilane:

Species: Rabbit

Result: No skin irritation

3-(2-aminoethylamino) propyltrimethoxysilane:

Species: Rabbit

Result: Mild skin irritation

Diocetyl tin bis(acetylacetonate):

Species: Rabbit

Method: OECD Test Guideline 404

Result: No skin irritation

N-[3-(dimethoxymethylsilyl)propyl]ethylenediamine:

Species: Rabbit

Method: OECD Test Guideline 404

Result: Skin irritation

Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate:

Species: Rabbit

Result: No skin irritation

Serious eye damage/eye irritation

Not classified based on available information.

Components:

trimethoxyvinylsilane:

Species: Rabbit

Method: OECD Test Guideline 405

Result: No eye irritation

3-(2-aminoethylamino) propyltrimethoxysilane:

Species: Rabbit

Method: OECD Test Guideline 405

Result: Irreversible effects on the eye

Diocetyl tin bis(acetylacetonate):

Species: Rabbit

Method: OECD Test Guideline 405

Result: No eye irritation

N-[3-(dimethoxymethylsilyl)propyl]ethylenediamine:

Species: Rabbit

Method: OECD Test Guideline 405

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



SMP ADHESIVE SEALANT GREY - 290 ML

Version	Revision Date:	SDS Number:	Date of last issue: 07.12.2016
1.4	10.03.2017	564828-00005	Date of first issue: 17.03.2016

Result: Irreversible effects on the eye

Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate:

Species: Rabbit

Result: No eye irritation

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

Not classified based on available information.

Components:

trimethoxyvinylsilane:

Test Type: Maximisation Test

Exposure routes: Skin contact

Species: Guinea pig

Method: OECD Test Guideline 406

Result: negative

3-(2-aminoethylamino) propyltrimethoxysilane:

Test Type: Maximisation Test

Species: Guinea pig

Method: OECD Test Guideline 406

Result: positive

Assessment: Probability or evidence of skin sensitisation in humans

Diocetyl tin bis(acetylacetonate):

Test Type: Local lymph node assay (LLNA)

Exposure routes: Skin contact

Species: Mouse

Method: OECD Test Guideline 429

Result: positive

Assessment: Probability or evidence of low to moderate skin sensitisation rate in humans

N-[3-(dimethoxymethylsilyl)propyl]ethylenediamine:

Test Type: Maximisation Test

Exposure routes: Skin contact

Species: Guinea pig

Method: OECD Test Guideline 406

Result: positive

Assessment: Probability or evidence of high skin sensitisation rate in humans

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



SMP ADHESIVE SEALANT GREY - 290 ML

Version	Revision Date:	SDS Number:	Date of last issue: 07.12.2016
1.4	10.03.2017	564828-00005	Date of first issue: 17.03.2016

Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate:

Test Type: Maximisation Test
Exposure routes: Skin contact
Species: Guinea pig
Method: OECD Test Guideline 406
Result: positive
Remarks: Based on data from similar materials

Assessment: Probability or evidence of high skin sensitisation rate in humans

Germ cell mutagenicity

Not classified based on available information.

Components:

trimethoxyvinylsilane:

Genotoxicity in vitro	: Test Type: In vitro mammalian cell gene mutation test Method: OECD Test Guideline 476 Result: negative
Genotoxicity in vivo	: Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay) Species: Mouse Application Route: Intraperitoneal injection Result: negative

3-(2-aminoethylamino) propyltrimethoxysilane:

Genotoxicity in vitro	: Test Type: Bacterial reverse mutation assay (AMES) Metabolic activation: with and without metabolic activation Result: negative
	: Test Type: In vitro mammalian cell gene mutation test Metabolic activation: with and without metabolic activation Result: negative
	: Test Type: Chromosome aberration test in vitro Metabolic activation: with and without metabolic activation Result: negative
Genotoxicity in vivo	: Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay) Species: Mouse Application Route: Intraperitoneal injection Result: negative

Diocetyl tin bis(acetylacetonate):

Genotoxicity in vitro	: Test Type: In vitro mammalian cell gene mutation test Method: OECD Test Guideline 476 Result: negative
-----------------------	--

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



SMP ADHESIVE SEALANT GREY - 290 ML

Version	Revision Date:	SDS Number:	Date of last issue: 07.12.2016
1.4	10.03.2017	564828-00005	Date of first issue: 17.03.2016

N-[3-(dimethoxymethylsilyl)propyl]ethylenediamine:

Genotoxicity in vitro	: Test Type: Bacterial reverse mutation assay (AMES) Method: OECD Test Guideline 471 Result: negative
Genotoxicity in vivo	: Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay) Species: Mouse Application Route: Intraperitoneal injection Method: OECD Test Guideline 474 Result: negative Remarks: Based on data from similar materials

Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate:

Genotoxicity in vitro	: Test Type: Bacterial reverse mutation assay (AMES) Result: negative
	: Test Type: Chromosome aberration test in vitro Method: OECD Test Guideline 473 Result: negative
Genotoxicity in vivo	: Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay) Species: Mouse Application Route: Ingestion Method: OECD Test Guideline 474 Result: negative

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

Components:

trimethoxyvinylsilane:

Effects on fertility	: Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test Species: Rat Application Route: Ingestion Method: OECD Test Guideline 422 Result: negative
Effects on foetal development	: Test Type: Embryo-foetal development Species: Rat Application Route: inhalation (vapour) Result: negative

3-(2-aminoethylamino) propyltrimethoxysilane:

Effects on fertility	: Test Type: Combined repeated dose toxicity study with the
----------------------	---

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



SMP ADHESIVE SEALANT GREY - 290 ML

Version	Revision Date:	SDS Number:	Date of last issue: 07.12.2016
1.4	10.03.2017	564828-00005	Date of first issue: 17.03.2016

reproduction/developmental toxicity screening test
Species: Rat
Application Route: Oral
Result: negative

Effects on foetal development : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: Oral
Result: negative

Diocetyl tin bis(acetylacetonate):

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 422
Result: negative
Remarks: Based on data from similar materials

Effects on foetal development : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 422
Result: positive
Remarks: Based on data from similar materials

Reproductive toxicity - Assessment : Some evidence of adverse effects on development, based on animal experiments.

N-[3-(dimethoxymethylsilyl)propyl]ethylenediamine:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Result: negative
Remarks: Based on data from similar materials

Effects on foetal development : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Result: negative
Remarks: Based on data from similar materials

Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate:

Effects on fertility : Test Type: One-generation reproduction toxicity study
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 415

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



SMP ADHESIVE SEALANT GREY - 290 ML

Version	Revision Date:	SDS Number:	Date of last issue: 07.12.2016
1.4	10.03.2017	564828-00005	Date of first issue: 17.03.2016

Result: negative

Remarks: Based on data from similar materials

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Components:

trimethoxyvinylsilane:

Exposure routes: Ingestion

Assessment: No significant health effects observed in animals at concentrations of 100 mg/kg bw or less.

Diocetyl tin bis(acetylacetonate):

Target Organs: thymus gland

Assessment: Shown to produce significant health effects in animals at concentrations of 10 mg/kg bw or less.

Exposure routes: Ingestion

Target Organs: thymus gland

Assessment: Shown to produce significant health effects in animals at concentrations of 10 mg/kg bw or less.

Repeated dose toxicity

Components:

trimethoxyvinylsilane:

Species: Rat

LOAEL: 62,5 mg/kg

Application Route: Ingestion

Exposure time: 54 Days

Method: OECD Test Guideline 422

3-(2-aminoethylamino) propyltrimethoxysilane:

Species: Rat

NOAEL: > 500 mg/kg

Application Route: Oral

Exposure time: 28 Days

Diocetyl tin bis(acetylacetonate):

Species: Rat

NOAEL: 5 mg/kg

LOAEL: 25 mg/kg

Application Route: Ingestion

Exposure time: 28 Days

Method: OECD Test Guideline 422

Remarks: Based on data from similar materials

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



SMP ADHESIVE SEALANT GREY - 290 ML

Version	Revision Date:	SDS Number:	Date of last issue: 07.12.2016
1.4	10.03.2017	564828-00005	Date of first issue: 17.03.2016

N-[3-(dimethoxymethylsilyl)propyl]ethylenediamine:

Species: Rat
NOAEL: 500 mg/kg
Application Route: Ingestion
Exposure time: 29 Days
Remarks: Based on data from similar materials

Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate:

Species: Rat
NOAEL: 300 mg/kg
Application Route: Ingestion
Exposure time: 28 Days
Method: OECD Test Guideline 407
Remarks: Based on data from similar materials

Aspiration toxicity

Not classified based on available information.

SECTION 12: Ecological information

12.1 Toxicity

Components:

trimethoxyvinylsilane:

Toxicity to fish	:	LC50 (Oncorhynchus mykiss (rainbow trout)): 191 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): 168,7 mg/l Exposure time: 48 h
Toxicity to algae	:	ErC50 (Desmodesmus subspicatus (green algae)): > 957 mg/l Exposure time: 72 h NOEC (Desmodesmus subspicatus (green algae)): > 957 mg/l Exposure time: 72 h

3-(2-aminoethylamino) propyltrimethoxysilane:

Toxicity to fish	:	LC50 (Brachydanio rerio (zebrafish)): 597 mg/l Exposure time: 96 h Method: Directive 67/548/EEC, Annex V, C.1.
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): 81 mg/l Exposure time: 48 h Method: Directive 67/548/EEC, Annex V, C.2.
Toxicity to algae	:	EC50 (Pseudokirchneriella subcapitata (green algae)): 8,8 mg/l Exposure time: 72 h

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



SMP ADHESIVE SEALANT GREY - 290 ML

Version	Revision Date:	SDS Number:	Date of last issue:
1.4	10.03.2017	564828-00005	07.12.2016
			Date of first issue: 17.03.2016

NOEC (Pseudokirchneriella subcapitata (green algae)): 3,1 mg/l
Exposure time: 72 h

Toxicity to microorganisms : EC10 (Pseudomonas putida): 25 mg/l
Exposure time: 16 h
Method: DIN 38 412 Part 8

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: ≥ 1 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)

Diocetyl tin bis(acetylacetonate):

Toxicity to fish : LC50 (Lepomis macrochirus (Bluegill sunfish)): 60,1 mg/l
Exposure time: 96 h
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 47,6 mg/l
Exposure time: 48 h
Remarks: Based on data from similar materials

Toxicity to microorganisms : EC50 : > 1.000 mg/l
Exposure time: 3 h

N-[3-(dimethoxymethylsilyl)propyl]ethylenediamine:

Toxicity to fish : LC50 (Danio rerio (zebra fish)): 597 mg/l
Exposure time: 96 h
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 100 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202

Toxicity to algae : EC50 (Pseudokirchneriella subcapitata (green algae)): 8,8 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

NOEC (Pseudokirchneriella subcapitata (green algae)): 3,1 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

Toxicity to microorganisms : EC50 (Pseudomonas putida): 67 mg/l
Exposure time: 16 h
Method: DIN 38 412 Part 8
Remarks: Based on data from similar materials

Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate:

Toxicity to fish : LC50 (Danio rerio (zebra fish)): 0,90 mg/l

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



SMP ADHESIVE SEALANT GREY - 290 ML

Version	Revision Date:	SDS Number:	Date of last issue: 07.12.2016
1.4	10.03.2017	564828-00005	Date of first issue: 17.03.2016

	Exposure time: 96 h Method: OECD Test Guideline 203
Toxicity to algae	: EC50 (Desmodesmus subspicatus (green algae)): 1,68 mg/l Exposure time: 72 h Method: OECD Test Guideline 201 EC10 (Desmodesmus subspicatus (green algae)): 0,34 mg/l Exposure time: 72 h Method: OECD Test Guideline 201
M-Factor (Acute aquatic toxicity)	: 1
Toxicity to microorganisms	: EC50 : > 100 mg/l Exposure time: 3 h Method: OECD Test Guideline 209 Remarks: Based on data from similar materials
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	: NOEC: 1 mg/l Exposure time: 21 d Species: Daphnia magna (Water flea) Method: OECD Test Guideline 211

12.2 Persistence and degradability

Components:

trimethoxyvinylsilane:

Biodegradability	: Result: Not readily biodegradable. Biodegradation: 51 % Exposure time: 28 d Method: OECD Test Guideline 301F
------------------	---

3-(2-aminoethylamino) propyltrimethoxysilane:

Biodegradability	: Result: Not readily biodegradable. Biodegradation: 39 % Exposure time: 28 d Method: Regulation (EC) No. 440/2008, Annex, C.4-A
------------------	---

Stability in water	: Degradation half life (DT50): 0,025 h pH: 7
--------------------	--

Diocetyl tin bis(acetylacetonate):

Biodegradability	: Result: rapidly degradable
------------------	------------------------------

N-[3-(dimethoxymethylsilyl)propyl]ethylenediamine:

Biodegradability	: Result: Not readily biodegradable. Biodegradation: 39 % Exposure time: 28 d Method: Regulation (EC) No. 440/2008, Annex, C.4-A Remarks: Based on data from similar materials
------------------	--

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



SMP ADHESIVE SEALANT GREY - 290 ML

Version	Revision Date:	SDS Number:	Date of last issue: 07.12.2016
1.4	10.03.2017	564828-00005	Date of first issue: 17.03.2016

Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate:

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 38 %
Exposure time: 28 d
Method: OECD Test Guideline 301E
Remarks: Based on data from similar materials

12.3 Bioaccumulative potential

Components:

3-(2-aminoethylamino) propyltrimethoxysilane:

Partition coefficient: n- : log Pow: -0,3
octanol/water

Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate:

Partition coefficient: n- : log Pow: 2,37
octanol/water

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Not relevant

12.6 Other adverse effects

No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Dispose of in accordance with local regulations.
According to the European Waste Catalogue, Waste Codes are not product specific, but application specific.
Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.
If not otherwise specified: Dispose of as unused product.

Waste Code : The following Waste Codes are only suggestions:

used product
080409, waste adhesives and sealants containing organic solvents or other dangerous substances

unused product

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



SMP ADHESIVE SEALANT GREY - 290 ML

Version	Revision Date:	SDS Number:	Date of last issue: 07.12.2016
1.4	10.03.2017	564828-00005	Date of first issue: 17.03.2016

080409, waste adhesives and sealants containing organic solvents or other dangerous substances

uncleaned packagings
150106, mixed packaging

Acc. Packaging Ordinance properly emptied packaging:
Properly emptied, non-contaminated packaging of non-hazardous products can be supplied to a system for the collection of sales packaging.

SECTION 14: Transport information

14.1 UN number

Not regulated as a dangerous good

14.2 UN proper shipping name

Not regulated as a dangerous good

14.3 Transport hazard class(es)

Not regulated as a dangerous good

14.4 Packing group

Not regulated as a dangerous good

14.5 Environmental hazards

Not regulated as a dangerous good

14.6 Special precautions for user

Not applicable

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Remarks : Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII) : Di-isononyl phthalate (52)
Dioctyltin bis(acetylacetonate) (20)

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : Not applicable

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

Regulation (EC) No 850/2004 on persistent organic pollutants : Not applicable

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import : Not applicable

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



SMP ADHESIVE SEALANT GREY - 290 ML

Version	Revision Date:	SDS Number:	Date of last issue: 07.12.2016
1.4	10.03.2017	564828-00005	Date of first issue: 17.03.2016

of dangerous chemicals

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

Not applicable

Water contaminating class : WGK 1 slightly water endangering
(Germany) Classification according VwVwS, Annex 4.

Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)
Volatile organic compounds (VOC) content: 2,3 %, 37,9 g/l
Remarks: VOC content excluding water

Other regulations:

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

15.2 Chemical safety assessment

A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

Full text of H-Statements

H226	: Flammable liquid and vapour.
H302	: Harmful if swallowed.
H315	: Causes skin irritation.
H317	: May cause an allergic skin reaction.
H318	: Causes serious eye damage.
H332	: Harmful if inhaled.
H361d	: Suspected of damaging the unborn child.
H372	: Causes damage to organs through prolonged or repeated exposure.
H400	: Very toxic to aquatic life.
H410	: Very toxic to aquatic life with long lasting effects.

Full text of other abbreviations

Acute Tox.	: Acute toxicity
Aquatic Acute	: Acute aquatic toxicity
Aquatic Chronic	: Chronic aquatic toxicity
Eye Dam.	: Serious eye damage
Flam. Liq.	: Flammable liquids
Repr.	: Reproductive toxicity
Skin Irrit.	: Skin irritation
Skin Sens.	: Skin sensitisation
STOT RE	: Specific target organ toxicity - repeated exposure
2006/15/EC	: Europe. Indicative occupational exposure limit values
DE TRGS 900	: Germany. TRGS 900 - Occupational exposure limit values.
2006/15/EC / TWA	: Limit Value - eight hours
DE TRGS 900 / AGW	: Time Weighted Average

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



SMP ADHESIVE SEALANT GREY - 290 ML

Version	Revision Date:	SDS Number:	Date of last issue: 07.12.2016
1.4	10.03.2017	564828-00005	Date of first issue: 17.03.2016

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Sources of key data used to compile the Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Classification of the mixture:

Skin Sens. 1 H317

Classification procedure:

Calculation method

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



SMP ADHESIVE SEALANT GREY - 290 ML

Version	Revision Date:	SDS Number:	Date of last issue: 07.12.2016
1.4	10.03.2017	564828-00005	Date of first issue: 17.03.2016

DE / EN