

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## BRAKE FLUID DOT 4 LOW VISCOSITY - 5 L

|         |                |              |                                 |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number:  | Date of last issue: 24.11.2016  |
| 3.4     | 24.03.2017     | 325602-00005 | Date of first issue: 27.09.2012 |

---

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : BRAKE FLUID DOT 4 LOW VISCOSITY - 5 L  
Product code : 0892009405

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-  
stance/Mixture : Brake fluid

#### 1.3 Details of the supplier of the safety data sheet

Company : Adolf Wuerth GmbH & Co. KG  
Reinhold-Würth-Str. 12-17  
74653 Künzelsau  
  
Telephone : +49 794015 0  
  
Telefax : +49 794015 10 00  
  
E-mail address of person  
responsible for the SDS : prodsafe@wuerth.com

#### 1.4 Emergency telephone number

Giftnotrufzentrale Berlin +49 30 30686 790. Gesellschaft (07:00 – 18:00 Uhr) +49 794015 2552

---

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

**Classification (REGULATION (EC) No 1272/2008)**  
Not a hazardous substance or mixture.

#### 2.2 Label elements

**Labelling (REGULATION (EC) No 1272/2008)**  
Not a hazardous substance or mixture.

#### **Additional Labelling**

EUH210 Safety data sheet available on request.

#### 2.3 Other hazards

None known.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## BRAKE FLUID DOT 4 LOW VISCOSITY - 5 L

Version 3.4      Revision Date: 24.03.2017      SDS Number: 325602-00005      Date of last issue: 24.11.2016  
Date of first issue: 27.09.2012

### SECTION 3: Composition/information on ingredients

#### 3.2 Mixtures

##### Hazardous components

| Chemical name                       | CAS-No.<br>EC-No.<br>Index-No.<br>Registration number | Classification     | Concentration<br>(% w/w) |
|-------------------------------------|---|--------------------|--------------------------|
| 2-[2-(2-butoxyethoxy)ethoxy]ethanol | 143-22-6<br>205-592-6<br>603-183-00-0                 | Eye Dam. 1; H318   | $\geq 3 - < 10$          |
| Diethylene glycol methyl ether      | 111-77-3<br>203-906-6<br>603-107-00-6                 | Repr. 2; H361d     | $\geq 1 - < 3$           |
| Diisopropanolamine                  | 110-97-4<br>203-820-9<br>603-083-00-7                 | Eye Irrit. 2; H319 | $\geq 1 - < 10$          |

For explanation of abbreviations see section 16.

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

- General advice : In the case of accident or if you feel unwell, seek medical advice immediately.  
When symptoms persist or in all cases of doubt seek medical advice.
- Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists.
- If inhaled : If inhaled, remove to fresh air.  
Get medical attention.
- In case of skin contact : In case of contact, immediately flush skin with soap and plenty of water.  
Remove contaminated clothing and shoes.  
Get medical attention.  
Wash clothing before reuse.  
Thoroughly clean shoes before reuse.
- In case of eye contact : Flush eyes with water as a precaution.  
Get medical attention if irritation develops and persists.
- If swallowed : If swallowed, DO NOT induce vomiting.  
Get medical attention.  
Rinse mouth thoroughly with water.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## BRAKE FLUID DOT 4 LOW VISCOSITY - 5 L

|         |                |              |                                 |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number:  | Date of last issue: 24.11.2016  |
| 3.4     | 24.03.2017     | 325602-00005 | Date of first issue: 27.09.2012 |

---

### 4.2 Most important symptoms and effects, both acute and delayed

None known.

### 4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically and supportively.

---

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

Suitable extinguishing media : Water spray  
Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical

Unsuitable extinguishing media : None known.

### 5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Exposure to combustion products may be a hazard to health.

Hazardous combustion products : Carbon oxides  
Metal oxides  
Nitrogen oxides (NO<sub>x</sub>)

### 5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.  
Use personal protective equipment.

Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  
Use water spray to cool unopened containers.  
Remove undamaged containers from fire area if it is safe to do so.  
Evacuate area.

---

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.  
Follow safe handling advice and personal protective equipment recommendations.

### 6.2 Environmental precautions

Environmental precautions : Discharge into the environment must be avoided.  
Prevent further leakage or spillage if safe to do so.  
Prevent spreading over a wide area (e.g. by containment or oil barriers).

---

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## BRAKE FLUID DOT 4 LOW VISCOSITY - 5 L

Version 3.4      Revision Date: 24.03.2017      SDS Number: 325602-00005      Date of last issue: 24.11.2016  
Date of first issue: 27.09.2012

---

Retain and dispose of contaminated wash water.  
Local authorities should be advised if significant spillages cannot be contained.

### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material.  
For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped, store recovered material in appropriate container. Clean up remaining materials from spill with suitable absorbent.  
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.  
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

### 6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

---

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation : Use only with adequate ventilation.

Advice on safe handling : Avoid inhalation of vapour or mist.  
Do not swallow.  
Avoid contact with eyes.  
Avoid prolonged or repeated contact with skin.  
Handle in accordance with good industrial hygiene and safety practice.  
Take care to prevent spills, waste and minimize release to the environment.

Hygiene measures : Ensure that eye flushing systems and safety showers are located close to the working place. When using do not eat, drink or smoke. Wash contaminated clothing before re-use.

### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Keep in properly labelled containers. Store in accordance with the particular national regulations.

Advice on common storage : Do not store with the following product types:  
Strong oxidizing agents

Storage class (TRGS 510) : 10, Combustible liquids

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## BRAKE FLUID DOT 4 LOW VISCOSITY - 5 L

Version 3.4      Revision Date: 24.03.2017      SDS Number: 325602-00005      Date of last issue: 24.11.2016  
Date of first issue: 27.09.2012

### 7.3 Specific end use(s)

Specific use(s) : No data available

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational Exposure Limits

| Components                              | CAS-No.  | Value type (Form of exposure)                 | Control parameters               | Basis       |
|---|--|---|----------------------------------|-------------|
| Triethylene glycol monomethyl ether     | 112-35-6   | AGW (Vapour and aerosols, inhalable fraction) | 50 mg/m <sup>3</sup>             | DE TRGS 900 |
| Peak-limit: excursion factor (category) | 2;(II)   |   |                                  |             |
| Further information                     | Senate commission for the review of compounds at the work place dangerous for the health (MAK-commission)., Sum of vapor and aerosols., When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child              |   |                                  |             |
| Diethylene glycol methyl ether          | 111-77-3   | TWA   | 10 ppm<br>50,1 mg/m <sup>3</sup> | 2006/15/EC  |
| Further information                     | Identifies the possibility of significant uptake through the skin, Indicative  |   |                                  |             |
|   |  | AGW (Vapour and aerosols)                     | 10 ppm<br>50 mg/m <sup>3</sup>   | DE TRGS 900 |
| Further information                     | European Union (The EU has established a limit value: deviations in value and peak limit are possible), Sum of vapor and aerosols., Skin absorption, When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child |   |                                  |             |

#### Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

| Substance name                                       | End Use   | Exposure routes | Potential health effects   | Value                 |
|--|-----------|-----------------|----------------------------|-----------------------|
| Tris[2-[2-(2-methoxyethoxy)ethoxy]ethyl] orthoborate | Workers   | Skin contact    | Long-term systemic effects | 16,7 mg/kg bw/day     |
|  | Consumers | Skin contact    | Long-term systemic effects | 10 mg/kg bw/day       |
|  | Consumers | Ingestion       | Long-term systemic effects | 10 mg/kg bw/day       |
| Triethylene glycol monomethyl ether                  | Workers   | Inhalation      | Long-term systemic effects | 156 mg/m <sup>3</sup> |
|  | Workers   | Skin contact    | Long-term systemic effects | 40 mg/kg bw/day       |
|  | Consumers | Inhalation      | Long-term systemic effects | 93 mg/m <sup>3</sup>  |
|  | Consumers | Skin contact    | Long-term systemic effects | 20 mg/kg bw/day       |
|  | Consumers | Skin contact    | Long-term systemic         | 2 mg/kg               |

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## BRAKE FLUID DOT 4 LOW VISCOSITY - 5 L

Version  
3.4

Revision Date:  
24.03.2017

SDS Number:  
325602-00005

Date of last issue: 24.11.2016  
Date of first issue: 27.09.2012

|                                       |           |              | effects                    | bw/day                 |
|---------------------------------------|-----------|--------------|----------------------------|------------------------|
| Tetraethylene glycol monomethyl ether | Workers   | Inhalation   | Long-term systemic effects | 156 mg/m <sup>3</sup>  |
|                                       | Workers   | Skin contact | Long-term systemic effects | 40 mg/kg bw/day        |
|                                       | Consumers | Inhalation   | Long-term systemic effects | 94 mg/m <sup>3</sup>   |
|                                       | Consumers | Skin contact | Long-term systemic effects | 20 mg/kg bw/day        |
|                                       | Consumers | Ingestion    | Long-term systemic effects | 2 mg/kg bw/day         |
| 2-[2-(2-butoxyethoxy)ethoxy]ethanol   | Workers   | Inhalation   | Long-term systemic effects | 195 mg/m <sup>3</sup>  |
|                                       | Workers   | Skin contact | Long-term systemic effects | 208 mg/kg bw/day       |
|                                       | Consumers | Inhalation   | Long-term systemic effects | 117 mg/m <sup>3</sup>  |
|                                       | Consumers | Skin contact | Long-term systemic effects | 125 mg/kg bw/day       |
|                                       | Consumers | Ingestion    | Long-term systemic effects | 12,5 mg/kg bw/day      |
| Diethylene glycol methyl ether        | Workers   | Inhalation   | Long-term systemic effects | 50,1 mg/m <sup>3</sup> |
|                                       | Workers   | Skin contact | Long-term systemic effects | 0,53 mg/kg bw/day      |
|                                       | Consumers | Inhalation   | Long-term systemic effects | 25 mg/m <sup>3</sup>   |
|                                       | Consumers | Skin contact | Long-term systemic effects | 0,27 mg/kg bw/day      |
|                                       | Consumers | Ingestion    | Long-term systemic effects | 1,5 mg/kg bw/day       |
| Diisopropanolamine                    | Workers   | Inhalation   | Long-term systemic effects | 16 mg/m <sup>3</sup>   |
|                                       | Workers   | Skin contact | Long-term systemic effects | 12,5 mg/kg bw/day      |
|                                       | Consumers | Inhalation   | Long-term systemic effects | 3,9 mg/m <sup>3</sup>  |
|                                       | Consumers | Skin contact | Long-term systemic effects | 6,3 mg/kg bw/day       |
|                                       | Consumers | Ingestion    | Long-term systemic effects | 1,3 mg/kg bw/day       |

### Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

| Substance name                                       | Environmental Compartment | Value        |
|--|---------------------------|--------------|
| Tris[2-[2-(2-methoxyethoxy)ethoxy]ethyl] orthoborate | Fresh water               | 0,2112 mg/l  |
|  | Marine water              | 0,02112 mg/l |
|  | Intermittent use/release  | 2,112 mg/l   |
|  | Sewage treatment plant    | 100 mg/l     |
|  | Fresh water sediment      | 0,76 mg/kg   |
|  | Marine sediment           | 0,076 mg/kg  |

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## BRAKE FLUID DOT 4 LOW VISCOSITY - 5 L

Version  
3.4

Revision Date:  
24.03.2017

SDS Number:  
325602-00005

Date of last issue: 24.11.2016  
Date of first issue: 27.09.2012

|                                       |                            |                |
|---------------------------------------|----------------------------|----------------|
|                                       | Soil                       | 0,0283 mg/kg   |
| Triethylene glycol monomethyl ether   | Fresh water                | 10 mg/l        |
|                                       | Marine water               | 1 mg/l         |
|                                       | Intermittent use/release   | 50 mg/l        |
|                                       | Sewage treatment plant     | 200 mg/l       |
|                                       | Fresh water sediment       | 36,6 mg/kg     |
|                                       | Marine sediment            | 0,8 mg/kg      |
|                                       | Soil                       | 1,73 mg/kg     |
|                                       | Oral (Secondary Poisoning) | 89 mg/kg food  |
| Tetraethylene glycol monomethyl ether | Fresh water                | 10 mg/l        |
|                                       | Marine sediment            | 1 mg/l         |
|                                       | Intermittent use/release   | 50 mg/l        |
|                                       | Sewage treatment plant     | 200 mg/l       |
|                                       | Fresh water sediment       | 36,5 mg/kg     |
|                                       | Marine sediment            | 0,365          |
|                                       | Soil                       | 1,67 mg/kg     |
|                                       | Oral (Secondary Poisoning) | 90 mg/kg food  |
| 2-[2-(2-butoxyethoxy)ethoxy]ethanol   | Fresh water                | 1,5 mg/l       |
|                                       | Marine water               | 0,15 mg/l      |
|                                       | Intermittent use/release   | 5 mg/l         |
|                                       | Sewage treatment plant     | 200 mg/l       |
|                                       | Fresh water sediment       | 5,77 mg/kg     |
|                                       | Marine sediment            | 0,577 mg/kg    |
|                                       | Soil                       | 0,35 mg/kg     |
|                                       | Oral (Secondary Poisoning) | 111 mg/kg food |
| Diethylene glycol methyl ether        | Fresh water                | 12 mg/l        |
|                                       | Marine water               | 1,2 mg/l       |
|                                       | Intermittent use/release   | 12 mg/l        |
|                                       | Sewage treatment plant     | 10000 mg/l     |
|                                       | Fresh water sediment       | 44,4 mg/kg     |
|                                       | Marine sediment            | 0,44 mg/kg     |
|                                       | Soil                       | 2,44 mg/kg     |
| Diisopropanolamine                    | Fresh water                | 0,2777 mg/l    |
|                                       | Marine water               | 0,02777 mg/l   |
|                                       | Intermittent use/release   | 2,777 mg/l     |
|                                       | Sewage treatment plant     | 15000 mg/l     |
|                                       | Fresh water sediment       | 2,19 mg/kg     |
|                                       | Marine sediment            | 0,219 mg/kg    |
|                                       | Soil                       | 0,275 mg/kg    |

### 8.2 Exposure controls

#### Engineering measures

Ensure adequate ventilation, especially in confined areas.  
Minimize workplace exposure concentrations.

#### Personal protective equipment

Eye protection : Wear the following personal protective equipment:  
Safety glasses

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## BRAKE FLUID DOT 4 LOW VISCOSITY - 5 L

Version 3.4      Revision Date: 24.03.2017      SDS Number: 325602-00005      Date of last issue: 24.11.2016  
Date of first issue: 27.09.2012

---

### Hand protection

Material : butyl-rubber  
Break through time : > 30 min  
Glove thickness : 0,7 mm  
Directive : DIN EN 374  
Protective index : Class 2

Material : Nitrile rubber  
Break through time : > 30 min  
Glove thickness : 0,4 mm  
Directive : DIN EN 374  
Protective index : Class 2

Remarks : Choose gloves to protect hands against chemicals depending on the concentration and quantity of the hazardous substance and specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.

Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.  
Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).

Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Filter type : Combined particulates and organic vapour type (A-P)

---

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Appearance : liquid  
Colour : yellow  
Odour : characteristic  
Odour Threshold : No data available  
pH : 7 - 8,5  
Melting point/freezing point : No data available  
Solidification / Setting point : < -50 °C  
Method: ISO 3016  
Initial boiling point and boiling : 265 °C



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## BRAKE FLUID DOT 4 LOW VISCOSITY - 5 L

|         |                |              |                                 |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number:  | Date of last issue: 24.11.2016  |
| 3.4     | 24.03.2017     | 325602-00005 | Date of first issue: 27.09.2012 |

---

|  |  |
|--|--|
| range  | Method: ASTM D 1120-72   |
| Flash point                                      | : 135,5 °C<br>Method: ISO 2719<br>Other information: No data available |
| Evaporation rate                                 | : No data available  |
| Flammability (solid, gas)                        | : Not applicable   |
| Upper explosion limit / Upper flammability limit | : No data available  |
| Lower explosion limit / Lower flammability limit | : No data available  |
| Vapour pressure                                  | : 1 mbar (20 °C)   |
| Relative vapour density                          | : No data available  |
| Density  | : ca. 1,06 g/cm <sup>3</sup> (20 °C)                                   |
| Solubility(ies)<br>Water solubility              | : soluble  |
| Partition coefficient: n-octanol/water           | : Not applicable   |
| Auto-ignition temperature                        | : > 200 °C   |
| Decomposition temperature                        | : No data available  |
| Viscosity<br>Viscosity, kinematic                | : No data available  |
| Explosive properties                             | : Not explosive  |
| Oxidizing properties                             | : The substance or mixture is not classified as oxidizing.             |

### 9.2 Other information

|               |                  |
|---------------|------------------|
| Particle size | : Not applicable |
|---------------|------------------|

---

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

Not classified as a reactivity hazard.

### 10.2 Chemical stability

Stable under normal conditions.

### 10.3 Possibility of hazardous reactions

|                     |   |
|---------------------|---|
| Hazardous reactions | : Can react with strong oxidizing agents. |
|---------------------|---|

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## BRAKE FLUID DOT 4 LOW VISCOSITY - 5 L

Version 3.4      Revision Date: 24.03.2017      SDS Number: 325602-00005      Date of last issue: 24.11.2016  
Date of first issue: 27.09.2012

---

### 10.4 Conditions to avoid

Conditions to avoid : None known.

### 10.5 Incompatible materials

Materials to avoid : Oxidizing agents

### 10.6 Hazardous decomposition products

No hazardous decomposition products are known.

---

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

Information on likely routes of exposure : Inhalation  
Skin contact  
Ingestion  
Eye contact

#### Acute toxicity

Not classified based on available information.

#### Components:

##### **2-[2-(2-butoxyethoxy)ethoxy]ethanol:**

Acute oral toxicity : LD50 (Rat): 5.170 mg/kg

Acute dermal toxicity : LD50 (Rabbit): 3.540 mg/kg

##### **Diethylene glycol methyl ether:**

Acute oral toxicity : LD50 (Rat): 7.128 mg/kg

Acute inhalation toxicity : LC0 (Rat): > 1,2 mg/l  
Exposure time: 6 h  
Test atmosphere: vapour  
Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 (Rabbit): 9.404 mg/kg

##### **Diisopropanolamine:**

Acute oral toxicity : LD50 (Rat): > 2.000 mg/kg  
Method: OECD Test Guideline 401

Acute inhalation toxicity : LC0 (Mouse): 2069 mg/m<sup>3</sup>  
Exposure time: 3 h  
Test atmosphere: dust/mist

Acute dermal toxicity : LD50 (Rabbit): 8.000 mg/kg

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## BRAKE FLUID DOT 4 LOW VISCOSITY - 5 L

Version  
3.4

Revision Date:  
24.03.2017

SDS Number:  
325602-00005

Date of last issue: 24.11.2016  
Date of first issue: 27.09.2012

---

### **Skin corrosion/irritation**

Not classified based on available information.

### **Components:**

#### **2-[2-(2-butoxyethoxy)ethoxy]ethanol:**

Species: Rabbit

Result: No skin irritation

#### **Diethylene glycol methyl ether:**

Species: Rabbit

Result: No skin irritation

#### **Diisopropanolamine:**

Species: Rabbit

Method: OECD Test Guideline 404

Result: No skin irritation

### **Serious eye damage/eye irritation**

Not classified based on available information.

### **Components:**

#### **2-[2-(2-butoxyethoxy)ethoxy]ethanol:**

Species: Rabbit

Method: OECD Test Guideline 405

Result: Irreversible effects on the eye

Remarks: Based on data from similar materials

#### **Diethylene glycol methyl ether:**

Species: Rabbit

Result: No eye irritation

#### **Diisopropanolamine:**

Species: Rabbit

Method: OECD Test Guideline 405

Result: Irritation to eyes, reversing within 21 days

### **Respiratory or skin sensitisation**

#### **Skin sensitisation**

Not classified based on available information.

#### **Respiratory sensitisation**

Not classified based on available information.

### **Components:**

#### **2-[2-(2-butoxyethoxy)ethoxy]ethanol:**

Test Type: Maximisation Test

Exposure routes: Skin contact

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## BRAKE FLUID DOT 4 LOW VISCOSITY - 5 L

Version 3.4      Revision Date: 24.03.2017      SDS Number: 325602-00005      Date of last issue: 24.11.2016  
Date of first issue: 27.09.2012

---

Species: Guinea pig  
Result: negative  
Remarks: Based on data from similar materials

### **Diethylene glycol methyl ether:**

Test Type: Maximisation Test  
Exposure routes: Skin contact  
Species: Guinea pig  
Method: OECD Test Guideline 406  
Result: negative

### **Diisopropanolamine:**

Test Type: Buehler Test  
Exposure routes: Skin contact  
Species: Guinea pig  
Method: OECD Test Guideline 406  
Result: negative

### **Germ cell mutagenicity**

Not classified based on available information.

### **Components:**

#### **2-[2-(2-butoxyethoxy)ethoxy]ethanol:**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Method: OECD Test Guideline 471  
Result: negative

#### **Diethylene glycol methyl ether:**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Method: OECD Test Guideline 471  
Result: negative

#### **Diisopropanolamine:**

Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro  
Method: OECD Test Guideline 473  
Result: negative

: Test Type: Bacterial reverse mutation assay (AMES)  
Method: OECD Test Guideline 471  
Result: negative

: Test Type: In vitro mammalian cell gene mutation test  
Method: OECD Test Guideline 476  
Result: negative

### **Carcinogenicity**

Not classified based on available information.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## BRAKE FLUID DOT 4 LOW VISCOSITY - 5 L

Version 3.4      Revision Date: 24.03.2017      SDS Number: 325602-00005      Date of last issue: 24.11.2016  
Date of first issue: 27.09.2012

---

### Components:

#### **Diisopropanolamine:**

Species: Rat  
Application Route: Ingestion  
Exposure time: 94 weeks  
Result: negative

#### **Reproductive toxicity**

Not classified based on available information.

### Components:

#### **2-[2-(2-butoxyethoxy)ethoxy]ethanol:**

Effects on fertility : Test Type: Two-generation reproduction toxicity study  
Species: Mouse  
Application Route: Ingestion  
Result: negative  
Remarks: Based on data from similar materials

Effects on foetal development : Test Type: Embryo-foetal development  
Species: Rat  
Application Route: Ingestion  
Result: negative  
Remarks: Based on data from similar materials

#### **Diethylene glycol methyl ether:**

Effects on fertility : Test Type: Two-generation reproduction toxicity study  
Species: Rat  
Application Route: Ingestion  
Method: OECD Test Guideline 416  
Result: negative  
Remarks: Based on data from similar materials

Effects on foetal development : Test Type: Embryo-foetal development  
Species: Rat  
Application Route: Ingestion  
Result: positive  
Remarks: Based on data from similar materials

Reproductive toxicity - Assessment : Some evidence of adverse effects on development, based on animal experiments.

#### **Diisopropanolamine:**

Effects on fertility : Test Type: One-generation reproduction toxicity study  
Species: Rat  
Application Route: Ingestion  
Result: negative

Effects on foetal development : Test Type: Embryo-foetal development  
Species: Rat  
Application Route: Ingestion

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## BRAKE FLUID DOT 4 LOW VISCOSITY - 5 L

Version 3.4      Revision Date: 24.03.2017      SDS Number: 325602-00005      Date of last issue: 24.11.2016  
Date of first issue: 27.09.2012

---

Method: OECD Test Guideline 414  
Result: negative

### STOT - single exposure

Not classified based on available information.

### STOT - repeated exposure

Not classified based on available information.

### Repeated dose toxicity

#### Components:

#### **2-[2-(2-butoxyethoxy)ethoxy]ethanol:**

Species: Rat  
NOAEL: 250 mg/kg  
Application Route: Ingestion  
Exposure time: 90 Days  
Method: OECD Test Guideline 408  
Remarks: Based on data from similar materials

#### **Diethylene glycol methyl ether:**

Species: Rat  
NOAEL: 900 mg/kg  
Application Route: Ingestion  
Exposure time: 6 Weeks

### Aspiration toxicity

Not classified based on available information.

---

## SECTION 12: Ecological information

### 12.1 Toxicity

#### Components:

#### **2-[2-(2-butoxyethoxy)ethoxy]ethanol:**

Toxicity to fish : LC50 (Leuciscus idus (Golden orfe)): 2.200 - 4.600 mg/l  
Exposure time: 96 h  
Method: DIN 38412

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): 2.210 mg/l  
aquatic invertebrates Exposure time: 48 h

Toxicity to algae : ErC50 (Desmodesmus subspicatus (green algae)): > 612,6 mg/l  
Exposure time: 72 h

EC10 (Desmodesmus subspicatus (green algae)): 612,6 mg/l  
Exposure time: 72 h

Toxicity to microorganisms : EC10 : > 1.995 mg/l

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## BRAKE FLUID DOT 4 LOW VISCOSITY - 5 L

Version 3.4      Revision Date: 24.03.2017      SDS Number: 325602-00005      Date of last issue: 24.11.2016  
Date of first issue: 27.09.2012

---

Exposure time: 30 min

### Diethylene glycol methyl ether:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 5.741 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 1.192 mg/l  
Exposure time: 48 h

Toxicity to algae : EC50 (Pseudokirchneriella subcapitata (green algae)): > 1.000 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 201

Toxicity to microorganisms : EC50 : > 1.000 mg/l  
Exposure time: 30 min  
Method: OECD Test Guideline 209

### Diisopropanolamine:

Toxicity to fish : LC50 (Brachydanio rerio (zebrafish)): 1.466 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 277,7 mg/l  
Exposure time: 48 h

Toxicity to algae : EC50 (Desmodesmus subspicatus (green algae)): 339 mg/l  
Exposure time: 72 h

NOEC (Desmodesmus subspicatus (green algae)): 125 mg/l  
Exposure time: 72 h

## 12.2 Persistence and degradability

### Components:

#### 2-[2-(2-butoxyethoxy)ethoxy]ethanol:

Biodegradability : Result: Not readily biodegradable.  
Biodegradation: 85 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301D

#### Diethylene glycol methyl ether:

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 100 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301B

#### Diisopropanolamine:

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 94 %

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## BRAKE FLUID DOT 4 LOW VISCOSITY - 5 L

Version 3.4      Revision Date: 24.03.2017      SDS Number: 325602-00005      Date of last issue: 24.11.2016  
Date of first issue: 27.09.2012

---

Exposure time: 28 d  
Method: OECD Test Guideline 301

### 12.3 Bioaccumulative potential

#### Components:

##### **2-[2-(2-butoxyethoxy)ethoxy]ethanol:**

Partition coefficient: n-octanol/water : log Pow: 0,51

##### **Diethylene glycol methyl ether:**

Partition coefficient: n-octanol/water : log Pow: -0,47

##### **Diisopropanolamine:**

Partition coefficient: n-octanol/water : log Pow: -0,88

### 12.4 Mobility in soil

No data available

### 12.5 Results of PBT and vPvB assessment

Not relevant

### 12.6 Other adverse effects

No data available

---

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

- Product : Dispose of in accordance with local regulations.  
According to the European Waste Catalogue, Waste Codes are not product specific, but application specific.  
Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities.
- Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.  
If not otherwise specified: Dispose of as unused product.
- Waste Code : The following Waste Codes are only suggestions:
- used product  
160113, brake fluids
  - unused product  
160113, brake fluids
  - uncleaned packagings  
150110, packaging containing residues of or contaminated by



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## BRAKE FLUID DOT 4 LOW VISCOSITY - 5 L

|         |                |              |                                 |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number:  | Date of last issue: 24.11.2016  |
| 3.4     | 24.03.2017     | 325602-00005 | Date of first issue: 27.09.2012 |

dangerous substances

Acc. Packaging Ordinance properly emptied packaging:  
Properly emptied, non-contaminated packaging of non-hazardous products can be supplied to a system for the collection of sales packaging.

### SECTION 14: Transport information

#### 14.1 UN number

Not regulated as a dangerous good

#### 14.2 UN proper shipping name

Not regulated as a dangerous good

#### 14.3 Transport hazard class(es)

Not regulated as a dangerous good

#### 14.4 Packing group

Not regulated as a dangerous good

#### 14.5 Environmental hazards

Not regulated as a dangerous good

#### 14.6 Special precautions for user

Not applicable

#### 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Remarks : Not applicable for product as supplied.

### SECTION 15: Regulatory information

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII) : Diethylene glycol methyl ether (54)

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : Not applicable

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

Regulation (EC) No 850/2004 on persistent organic pollutants : Not applicable

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals : Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## BRAKE FLUID DOT 4 LOW VISCOSITY - 5 L

|         |                |              |                                 |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number:  | Date of last issue: 24.11.2016  |
| 3.4     | 24.03.2017     | 325602-00005 | Date of first issue: 27.09.2012 |

Not applicable

Water contaminating class (Germany) : WGK 1 slightly water endangering  
Classification according VwVwS, Annex 4.

Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)  
Volatile organic compounds (VOC) content: 0 %

Other regulations:

Take note of Directive 92/85/EEC regarding maternity protection or stricter national regulations, where applicable.

### 15.2 Chemical safety assessment

A Chemical Safety Assessment has not been carried out.

## SECTION 16: Other information

### Full text of H-Statements

H318 : Causes serious eye damage.  
H319 : Causes serious eye irritation.  
H361d : Suspected of damaging the unborn child.

### Full text of other abbreviations

Eye Dam. : Serious eye damage  
Eye Irrit. : Eye irritation  
Repr. : Reproductive toxicity  
2006/15/EC : Europe. Indicative occupational exposure limit values  
DE TRGS 900 : Germany. TRGS 900 - Occupational exposure limit values.  
2006/15/EC / TWA : Limit Value - eight hours  
DE TRGS 900 / AGW : Time Weighted Average

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## BRAKE FLUID DOT 4 LOW VISCOSITY - 5 L

|         |                |              |                                 |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number:  | Date of last issue: 24.11.2016  |
| 3.4     | 24.03.2017     | 325602-00005 | Date of first issue: 27.09.2012 |

---

Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

### Further information

Sources of key data used to compile the Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

DE / EN