

# FIRE STOP FOAM FZ PLUS

55



Can 600 ml / light red

Valve gripper  
Adapter/spray tube



## General construction permit/test reports

ABP  
P-NDS04-868

T 30-/RS-doors  
**neuformtür**  
info@neuform-tuer.de

### 1. Applications

- For installation in system **L1**  
– Joint system B1 **L1**
- For sealing joints and cavities with the requirement B1 flame retardant.
- T 30 doors from the neuform-Türenwerk company.
- Precise notes on installation can be found in the general construction test report, the neuform-Türenwerk door approvals.

### 2. Features


- B1 flame retardant.
- 2C system of very fast-hardening foam.
- No preliminary and interim wetting, the foam hardens chemically.

- Dimensionally-stable foam, no pressing.
- Fast processing.
- High foam yield
- Thermally insulating.
- Free of CFCs.
- Can be plastered over or painted over once hardened.
- Resistant to aging, but not UV-resistant.
- Excellent installation properties. Foam bonds very well and does not run off.

### 3. Notes

- Store frost-free.
- Use in well-ventilated rooms.
- Not for connecting joints that are subjected to expansion stress.
- Store in a cool, dry place.
- Note and adhere to the safety recommendations.


### Note on processing



Clean the joint.



Apply fire stop foam FZ plus



Cut off any projections.