

CLEAR VARNISH



Similar to illustration



Painting over

Clear varnish for untreated wood surfaces to be painted over.

Compatibility

Clear varnish is compatible with all AC and NC lacquers.

Speediness

The varnish dries in an extremely short time.

Contents	Degree of gloss	Art. No.	P. Qty.
400 ml	High-gloss	0893 188 1	1
400 ml	High-gloss		6
400 ml	Silk matt	0893 188	1
400 ml	Silk matt		6

Supplement to Art. No.:	Designation	Art. No.
0893 188 1	Dry Sandpaper for wood, SPS quality	0582 570 240
	Hook-And-Loop Hand Sanding Block	0587 70 120
	Spraymaster Aerosol Attachment	0891 090
	Penetrating Primer	0893 18
	Disposable Paint-Spray Mask	0899 160
	Dust Binder Cloth	0899 700 001

Application

Colorless protective varnish for untreated wood surfaces to be painted over.

Note

Not suitable for synthetic resin paints.

Instructions

Shake can well (at least 2 minutes) from point at which the mixing ball can be heard, briefly spray into the air to blow any residual particles out of the lift tube and the spraying head, then conduct test spraying. When coating entire surfaces for the first time, spray the surface evenly with a back-and-forth motion while maintaining a distance of 20 - 30 cm. Turn over can after use and spray until valve is empty.

With this information we want to advise you to the best of our knowledge based on our tests and experience. However, we assume no liability for the application results in individual cases due to the large number of applications and the storage and application conditions that lie outside the scope of our influence. This also applies to the use of the non-binding technical and commercial customer service we provide. We always recommend conducting your own tests. We guarantee the consistent quality of our products. We reserve the right to make technical changes and carry out further development.