

SUPPORTING PRODUCT LINE FOR OIL



Hand-Lever Barrel Pump

Self-priming rugged polypropylene hand-lever pump

Features:

- Suitable for pumping engine oil, diesel oil, hydraulic oil and anti-freeze.
- 2" barrel connection.
- Secure hold thanks to the locking ring.
- Telescopic pump tube for 60 and 200 L barrels; variable from 500 - 900 mm.
- Pump rate: Approx. 300 mL/stroke.

Art. No. 0891 621

P. Qty. 1

Adapter for plastic barrels with 2" coarse Mauser thread

Art. No. 0891 621 0

P. Qty. 1

Adapter for plastic canisters

With male thread

Art. No. 0891 621 10

P. Qty. 1

Pneumatic Barrel Pump

Pneumatically driven, double-action pump for non-aggressive liquids, oils, liquid greases etc.

Features:

- Pneumatic suction and pressure pump with 2" connection.
- Pressure ratio of 1 : 3.
- Min. air pressure: 3 bar.
- Max. air pressure: 10 bar (may not be exceeded under any circumstances!)
- Operating temperatures from 5°C to 50°C (pump performance drops at under 10°C!).
- Min./max. output: 25 Liter per minute.
- Hose length: 3 m, 1/2" connection.
- Digital measuring unit with LCD (cannot be calibrated!).
- Dimensions of the pump tube:
Dia.: 50 mm, length: 930 mm.
- Total height/weight: 1,230 mm, 8 kg.

Art. No. 0891 625

P. Qty. 1