

HOT MELT ADHESIVE 103



For effective dent removal on different materials and surfaces.

- Short processing and setting times
- Waterproof and resistant to UV and ageing

Notice

Heat occurring during storage (e.g. due to solar radiation) must be avoided due to the changes to the outer shape of the hot melt adhesive this can cause.

Art. No.	0890 100 058
P. Qty.	1
Weight of content	500 g
Length	180 mm
Diameter	11.5 mm
Chemical basis	Polymer-based compound
Colour	Black
Min./max. open time	20-40 s
Softening point	85 °C
Min./max. processing temperature	190 to 210 °C
Shelf life from production	24 Month

Related products	Art. No.
Hot glue gun HKP 220	0702 623 1

Application area

Ideal for the automotive industry for effective dent removal on different materials and surfaces by affixing pulling tabs.



The usage instructions are recommendations based on the tests we have conducted and are based on our experience; carry out your own tests before each application. We do not assume any liability for a specific application result due to the large number of applications and storage and processing conditions. Insofar as our free customer service provides technical information or acts as an advisory service, no responsibility is assumed by this service except where the advice or information given falls within the scope of our specified, contractually agreed service or the advisor was acting deliberately. We guarantee consistent quality of our products. We reserve the right to make technical changes and further develop products.