

HOT GLUE GUN



Especially high-performance glue gun, excellently suited for all assembly, repair, fixation and decoration work.

HKP 220
in carrying case
Art. No. 0702 623 1

Adjustable working temperature
Melting point and application temperature can vary from adhesive to adhesive. The HKP 220 enables the heating capacity to be matched and adjusted individually to the adhesive.

Exact dosing
The trigger can be adjusted via a mechanical stroke limitation so that the same amount of adhesive is applied each time it is operated.

Fatigue-free working
The long trigger corresponds to ergonomically perfect use. The stroke limitation described above can also be used for the optimal ergonomic adjustment of the distance of the trigger from the handle to the user's own hand size.

Scope of delivery		
Designation	Art. No.	P. Qty.
Hot Glue Gun HKP 220	0702 623 X	1
Round nozzle	0708 623 008	1
Hot-melt adhesive, standard - transparent -	0890 100 052	10
Empty Carrying Case	0955 702 623	1

Technical Data					
Operating voltage	Power draw	Application temperature	Melting capacity	Weight	Size
220-240 V/ 50 Hz	220 W	140-220°C	0.7-1.2 kg/h	0.6 kg	290 mm x 230 mm

Available in ORSY® fleet management.

Suitable hot-melt adhesive sticks					
Designation	Hot-melt adhesive, high-strength, 11.5 mm dia.	Hot-melt adhesive, strong, 11.5 mm dia.	Hot-melt adhesive, universal, 11.5 mm dia.	Hot-melt adhesive, standard, 11.5 mm dia.	
Color	Transparent light brown	Yellow	Black	Transparent	
Length	195 mm	195 mm	180 mm	195 mm	
Contents P. Qty.	Approx. 10	Approx. 26	Approx. 29	Approx. 26	Approx. 280
Contents P. g	180	500	500	500	5,000
Art. No.	0890 100 050	0890 100 057	0890 100 058	0890 100 052	0890 100 054

Features					
Hardness	++	++	++	+	
Adhesion	++	++	+++	+	
Removability	+	+	++	+	

+++ = very good ++ = good + = satisfactory