

ENGINE WASH



Designation	Contents in L	Art. No.	P. Qty.
Canister	5	0893 013 05	1/12
Canister	20	0893 013 20	1
Plastic drum	60	0893 013 60	

Use:

Spray Engine Wash undiluted onto the engine, engine compartment and transmission. Rinse off thoroughly after a short time with a steam jet. Can also be used in the high-pressure cleaner. Can be used with cold and warm water. Mixing ratio 1:1 to 1:10.

Powerful engine cleaner for the engine, engine compartment and transmission.

High cleaning performance

- Removes oil, grease and other contamination quickly and thoroughly
- Thanks to its viscosity, the cleaner sticks to vertical surfaces and can therefore get under the dirt and optimally detach it

Gentle on materials.

- The absence of aggressive substances and the neutral pH value mean that sensitive surfaces such as aluminium, tin and zinc, as well as painted surfaces, plastics and rubber, are not attacked.

Especially gentle on the skin

- neutral pH

Biodegradability ≥ 95% (OECD and closed bottle test)

Fast-separating in accordance with German Ecological Standard Test B 5105

Oily, greasy contamination is not emulsified, rather it is penetrated and separated. This enables the resulting waste water to be separated out via light-oil separator.

Contains no AOX compounds and organic solvents

Contains no phosphates and no complex agents

Silicone-free

Additional articles:

Tap for 5 L:

Art. No. 0891 302 01

Tap for 20 l and 60 l:

Art. No. 0891 302 03

Pump spray bottle

Art. No. 0891 501

Foam gun

Art. No. 0891 612