

TYRE MOUNTING PASTE CARGO SPECIAL



Art. No.	0890 123 404
P. Qty.	1
Weight of content	4 kg
Colour	Yellow/brown
Shelf life from production	12 Month

Related products	Art. No.
Brush for tyre mounting paste	0693 080 0

Application area

For fitting and removing all large and heavy-duty tyres, such as truck, agricultural and industrial tyres (EM tyres)

Notice

Not suitable for fitting motorcycle and truck tyres due to long flash-off behaviour.

Instructions

Before the new tyres are fitted, the rim should be cleaned of old mounting adhesive around the rim flange sealing area. We recommend our brake cleaner Art. No. 08901087. Remove loose rust using a wire brush. Then apply a thin layer of tyre mounting paste with a brush or sponge to the tyre rim, the tyre bed and the bead seat ring.

For fitting and removing all large and heavy-duty tyres, such as truck, agricultural and industrial tyres (EM tyres)

Very good gliding properties

- Low effort and time
- Facilitates fitting and subsequent removal
- Economical material usage
- Reduced machine wear
- Protects tyres and rim

Long flash-off time

No re-greasing required

Tyre and rim care

- Prevents cracking and tyre ageing
- Prevents rusting (not corrosive)
- Prevents the tyre adhering to the rim

Frost-proof

Remains flexible even at minus temperatures

Physiologically safe and biodegradable

- No contact allergies for wheel fitters
- pH-neutral

Silicone-free

Free from substances that impair wetting of paint

The usage instructions are recommendations based on the tests we have conducted and are based on our experience; carry out your own tests before each application. We do not assume any liability for a specific application result due to the large number of applications and storage and processing conditions. Insofar as our free customer service provides technical information or acts as an advisory service, no responsibility is assumed by this service except where the advice or information given falls within the scope of our specified, contractually agreed service or the advisor was acting deliberately. We guarantee consistent quality of our products. We reserve the right to make technical changes and further develop products.