



Automotive Sealing Tape

- Pre-compressed.
- Self adhesive on one side.
- Temperature resistance: -30°C to +90°C.

Automotive sealing tape protects against vibration and will seal gaps securely and permanently in one go. After release of the compression the tape will expand and develop a pressure which firmly presses against the gap surfaces and levels up uneven parts.

Advantages

- Can be painted over with common dispersion lacquers.
- Open to diffusion, thus avoiding of water accumulation.

Assembly Instructions

- Clean the gap/surface from oil, grease and loose particles.
- Remove cover paper from the sealing tape.
- Adhere sealing tape to the surface or apply directly from the roll to the gap.

Application Areas

- Sealing and protecting parts against vibration in ventilation and heating systems, tanks, frame supports or lateral supports of the boot lid etc.
- To protect against vibration when fitting radios and speakers etc.
- For coating aerial cable (i.e. VW, Ford).

Automotive Sealing Tape			Gap width mm	Roll length m	Art. No.	Pack Qty.
Width mm	Thickn. ¹⁾ mm	Thickn. ²⁾ mm				
10	2	10	2-3	12.5	0875 410 2	1
20	2	10	2-3	12.5	0875 420 2	
15	3	15	3-4	10.0	0875 415 3	
15	4	20	4-5	8.0	0875 415 4	

¹⁾ Thickness compressed to 20%.

²⁾ Thickness when expanded.