

ULTIMATE WINDSCREEN ADHESIVE



Designation	Content ml	Art. no.	PU/Qty.
Complete set	*	0890 023 800	1
Cartridge	310	0890 023 801	1/12
Professional set	**	0890 023 830	1
Bag	400	0890 023 831	15

* Set= cartridge, active cleaner (double cloth), Varioprimer safe + easy (20 ml), primer brush, window application nozzle, repair instructions.

** Set = bag, Active Cleaner (double cloth), Vario primer safe + easy (20 ml), primer brush, window application nozzle, repair instructions.

Applications:

Replacement glazing of cars and small vans.

Application:

When applying the material, ensure that the working environment is clean. It is essential to use the product with the accompanying Würth system components to ensure correct and faultless work. The work instructions provided with the product must be followed during application.

Note:

It is imperative that the Würth active cleaner and Würth Varioprimer are used when preparing surfaces. The products must be checked to ensure that they have not expired before they are used. Apply the adhesive while guiding the gun vertically, starting from the centre at the bottom of the window. Do not position the vehicle on the lifting platform. Observe the information regarding bead geometry provided by the vehicle manufacturer. The application and drive-away times must be observed.

High-modulus, non-conductive 1C window adhesive that can be used in any season.

Can be used in any season

1-hour drive-away time with airbag at an ambient temperature of -10 °C to +35 °C

High-modulus

Vehicle-strengthening window adhesive

Suitable for aerials, non-conductive

Prevents contact corrosion

Suitable for use on aluminium, magnesium and hybrid vehicle bodies (e.g. Audi A8, Jaguar XJ etc.)

Safety tested

- Drive-away time confirmed with crash test and TÜV certificate in accordance with FMVSS208/212
- Meets requirements of original equipment manufacturers (vehicle manufacturers)

Technical data:	
Chemical basis	1-comp. polyurethane (moisture-hardening)
Colour	Black
Processing temperature	+5 °C to +35 °C
Processing time	15 min.*
Storage temperature	+5 °C to +25 °C
Drive-away time without airbag	30 min.**
Drive-away time with airbag	1 h**

* Measured at 23 °C/50% relative humidity
** at an ambient temperature of -10 °C to +35 °C

Additional article:

Active Cleaner, 500 ml
Art. no. **0890 024 1**

Varioprimer, stick, 10 ml
Art. no. **0890 024 010**

Varioprimer, bottle, 20 ml
Art. no. **0890 024 021**

Varioprimer, bottle, 100 ml
Art. no. **0890 024 101**

This information is only a recommendation based on our experience. Preliminary testing required!
For further information, refer to the technical information leaflet.