

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



WINDSCREEN ADHESIVE XL - 600 ML

Version	Revision Date:	SDS Number:	Date of last issue: 17.03.2017
5.0	17.05.2017	549029-00004	Date of first issue: 11.06.2010

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : WINDSCREEN ADHESIVE XL - 600 ML

Product code : 0890023600

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub- : Adhesives
stance/Mixture

1.3 Details of the supplier of the safety data sheet

Company : Adolf Wuerth GmbH & Co. KG
Reinhold-Würth-Str. 12-17
74653 Künzelsau

Telephone : +49 794015 0

Telefax : +49 794015 10 00

E-mail address of person : prodsafe@wuerth.com
responsible for the SDS

1.4 Emergency telephone number

Giftnotrufzentrale Berlin +49 30 30686 790. Gesellschaft (07:00 – 18:00 Uhr) +49 794015 2552

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Respiratory sensitisation, Category 1 H334: May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Skin sensitisation, Category 1 H317: May cause an allergic skin reaction.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : Danger

Hazard statements : H317 May cause an allergic skin reaction.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



WINDSCREEN ADHESIVE XL - 600 ML

Version 5.0 Revision Date: 17.05.2017 SDS Number: 549029-00004 Date of last issue: 17.03.2017
Date of first issue: 11.06.2010

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Precautionary statements :

Prevention:

P272 Contaminated work clothing should not be allowed out of the workplace.

P280 Wear protective gloves.

Response:

P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.

P342 + P311 If experiencing respiratory symptoms: Call a POISON CENTER/doctor.

P362 + P364 Take off contaminated clothing and wash it before reuse.

Hazardous components which must be listed on the label:

Hexamethylene diisocyanate, oligomers

4,4'-Diphenylmethane diisocyanate

Additional Labelling

EUH204 Contains isocyanates. May produce an allergic reaction.

2.3 Other hazards

None known.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
Hexamethylene diisocyanate, oligomers	28182-81-2 500-060-2 01-2119485796-17	Acute Tox. 4; H332 Skin Sens. 1; H317 STOT SE 3; H335	$\geq 1 - < 10$
4,4'-Diphenylmethane diisocyanate	101-68-8 202-966-0 615-005-00-9 01-2119457014-47	Acute Tox. 4; H332 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Resp. Sens. 1; H334 Skin Sens. 1; H317 Carc. 2; H351 STOT SE 3; H335 STOT RE 2; H373	$\geq 0,1 - < 1$

For explanation of abbreviations see section 16.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



WINDSCREEN ADHESIVE XL - 600 ML

Version	Revision Date:	SDS Number:	Date of last issue: 17.03.2017
5.0	17.05.2017	549029-00004	Date of first issue: 11.06.2010

SECTION 4: First aid measures

4.1 Description of first aid measures

- | | | |
|----------------------------|---|---|
| General advice | : | In the case of accident or if you feel unwell, seek medical advice immediately.
When symptoms persist or in all cases of doubt seek medical advice. |
| Protection of first-aiders | : | First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists. |
| If inhaled | : | If inhaled, remove to fresh air.
If not breathing, give artificial respiration.
If breathing is difficult, give oxygen.
Get medical attention. |
| In case of skin contact | : | In case of contact, immediately flush skin with soap and plenty of water.
Remove contaminated clothing and shoes.
Get medical attention.
Wash clothing before reuse.
Thoroughly clean shoes before reuse. |
| In case of eye contact | : | Flush eyes with water as a precaution.
Get medical attention if irritation develops and persists. |
| If swallowed | : | If swallowed, DO NOT induce vomiting.
Get medical attention.
Rinse mouth thoroughly with water. |

4.2 Most important symptoms and effects, both acute and delayed

- | | | |
|-------|---|--|
| Risks | : | May cause an allergic skin reaction.
May cause allergy or asthma symptoms or breathing difficulties if inhaled. |
|-------|---|--|

4.3 Indication of any immediate medical attention and special treatment needed

- | | | |
|-----------|---|---|
| Treatment | : | Treat symptomatically and supportively. |
|-----------|---|---|

SECTION 5: Firefighting measures

5.1 Extinguishing media

- | | | |
|--------------------------------|---|--|
| Suitable extinguishing media | : | Water spray
Alcohol-resistant foam
Carbon dioxide (CO ₂)
Dry chemical |
| Unsuitable extinguishing media | : | None known. |

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



WINDSCREEN ADHESIVE XL - 600 ML

Version	Revision Date:	SDS Number:	Date of last issue: 17.03.2017
5.0	17.05.2017	549029-00004	Date of first issue: 11.06.2010

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Exposure to combustion products may be a hazard to health.

Hazardous combustion products : Carbon oxides
Nitrogen oxides (NO_x)

5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.
Use personal protective equipment.

Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Use water spray to cool unopened containers.
Remove undamaged containers from fire area if it is safe to do so.
Evacuate area.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.
Follow safe handling advice and personal protective equipment recommendations.

6.2 Environmental precautions

Environmental precautions : Discharge into the environment must be avoided.
Prevent further leakage or spillage if safe to do so.
Retain and dispose of contaminated wash water.
Local authorities should be advised if significant spillages cannot be contained.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material.
For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped, store recovered material in appropriate container.
Clean up remaining materials from spill with suitable absorbent.
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



WINDSCREEN ADHESIVE XL - 600 ML

Version 5.0 Revision Date: 17.05.2017 SDS Number: 549029-00004 Date of last issue: 17.03.2017
Date of first issue: 11.06.2010

SECTION 7: Handling and storage

7.1 Precautions for safe handling

- Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.
- Local/Total ventilation : Use only with adequate ventilation.
- Advice on safe handling : Do not get on skin or clothing.
Do not swallow.
Avoid contact with eyes.
Handle in accordance with good industrial hygiene and safety practice.
Keep container tightly closed.
Keep away from water.
Protect from moisture.
Take care to prevent spills, waste and minimize release to the environment.
- Hygiene measures : Ensure that eye flushing systems and safety showers are located close to the working place. When using do not eat, drink or smoke. Wash contaminated clothing before re-use.

7.2 Conditions for safe storage, including any incompatibilities

- Requirements for storage areas and containers : Keep in properly labelled containers. Keep tightly closed.
Store in accordance with the particular national regulations.
- Advice on common storage : Do not store with the following product types:
Strong oxidizing agents
- Storage class (TRGS 510) : 11, Combustible Solids
- Recommended storage temperature : 5 - 25 °C

7.3 Specific end use(s)

- Specific use(s) : No data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Talc	14807-96-6	AGW (Inhalable fraction)	10 mg/m ³	DE TRGS 900
Peak-limit: excursion factor (category)	2;(II)			

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

**WINDSCREEN ADHESIVE XL - 600 ML**Version
5.0Revision Date:
17.05.2017SDS Number:
549029-00004Date of last issue: 17.03.2017
Date of first issue: 11.06.2010

Further information	General dust value. For this substance no specific occupational exposure limit value is established, since the AGS does not yet have information regarding unspecific action on the respiratory organs in excess of the normal values., Commission for dangerous substances, Senate commission for the review of compounds at the work place dangerous for the health (MAK-commission).			
		AGW (Alveolate fraction)	1,25 mg/m3	DE TRGS 900
Peak-limit: excursion factor (category)	2;(II)			
Further information	General dust value. For this substance no specific occupational exposure limit value is established, since the AGS does not yet have information regarding unspecific action on the respiratory organs in excess of the normal values., Commission for dangerous substances, Senate commission for the review of compounds at the work place dangerous for the health (MAK-commission).			
4,4'-Diphenylmethane diisocyanate	101-68-8	AGW (Vapour and aerosols)	0,05 mg/m3	TRGS 430
Peak-limit: excursion factor (category)	1;=2=(I)			
Further information	Sum of vapour and aerosols, The exposure limit is established for monomers. For regulatory details on oligomers and polymers see TRGS 430 'Isocyanate', airway sensitizing substance			
		AGW (Vapour and aerosols, inhalable fraction)	0,05 mg/m3	DE TRGS 900
Peak-limit: excursion factor (category)	1;=2=(I)			
Further information	Senate commission for the review of compounds at the work place dangerous for the health (MAK-commission)., Sum of vapor and aerosols., The exposure limit is established for monomers. For regulatory details on oligomers and polymers see TRGS 430 'Isocyanate', Skin absorption, When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child, Substance sensitizing through the skin and respiratory system			

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
1,2-Benzenedicarboxylic acid, di-C8-10-alkyl esters	Workers	Inhalation	Long-term systemic effects	5,61 mg/m3
	Workers	Skin contact	Long-term systemic effects	0,8 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	1,386 mg/m3
	Consumers	Skin contact	Long-term systemic effects	0,4 mg/kg bw/day

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



WINDSCREEN ADHESIVE XL - 600 ML

Version
5.0

Revision Date:
17.05.2017

SDS Number:
549029-00004

Date of last issue: 17.03.2017
Date of first issue: 11.06.2010

	Consumers	Ingestion	Long-term systemic effects	0,4 mg/kg bw/day
Carbon black	Consumers	Inhalation	Long-term systemic effects	0,06 mg/m3
	Workers	Inhalation	Long-term systemic effects	1 mg/m3
Kaolin, calcined	Workers	Inhalation	Long-term systemic effects	3 mg/m3
	Workers	Inhalation	Acute systemic effects	3 mg/m3
	Workers	Inhalation	Long-term local effects	3 mg/m3
	Workers	Inhalation	Acute local effects	3 mg/m3
Hexamethylene diisocyanate, oligomers	Workers	Inhalation	Long-term local effects	0,5 mg/m3
	Workers	Inhalation	Acute local effects	1 mg/m3
4,4'-Diphenylmethane diisocyanate	Workers	Inhalation	Long-term local effects	0,05 mg/m3
	Workers	Inhalation	Acute local effects	0,1 mg/m3
	Consumers	Inhalation	Long-term local effects	0,025 mg/m3
	Consumers	Inhalation	Acute local effects	0,05 mg/m3

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
1,2-Benzenedicarboxylic acid, di-C8-10-alkyl esters	Sewage treatment plant	990 mg/l
Carbon black	Fresh water	50 mg/l
Kaolin, calcined	Fresh water	4,1 mg/l
	Marine water	0,41 mg/l
	Intermittent use/release	25 mg/l
	Sewage treatment plant	1400 mg/l
Hexamethylene diisocyanate, oligomers	Fresh water	0,127 mg/l
	Marine water	0,0127 mg/l
	Intermittent use/release	1,27 mg/l
	Sewage treatment plant	38,3 mg/l
	Fresh water sediment	266700 mg/kg
	Marine sediment	26670 mg/kg
	Soil	53182 mg/kg
4,4'-Diphenylmethane diisocyanate	Fresh water	1 mg/l
	Marine water	0,1 mg/l
	Intermittent use/release	10 mg/l
	Sewage treatment plant	1 mg/l
	Soil	1 mg/kg

8.2 Exposure controls

Engineering measures

Processing may form hazardous compounds (see section 10).
Ensure adequate ventilation, especially in confined areas.
Minimize workplace exposure concentrations.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



WINDSCREEN ADHESIVE XL - 600 ML

Version	Revision Date:	SDS Number:	Date of last issue: 17.03.2017
5.0	17.05.2017	549029-00004	Date of first issue: 11.06.2010

Personal protective equipment

- | | | |
|--------------------------|---|---|
| Eye protection | : | Wear the following personal protective equipment:
Safety glasses |
| Hand protection | : | |
| Material | : | Neoprene |
| Break through time | : | > 240 min |
| Glove thickness | : | > 0,35 mm |
| Directive | : | DIN EN 374 |
| Protective index | : | Class 5 |
| Material | : | Nitrile rubber |
| Break through time | : | > 240 min |
| Glove thickness | : | > 0,35 mm |
| Directive | : | DIN EN 374 |
| Protective index | : | Class 5 |
| Remarks | : | Choose gloves to protect hands against chemicals depending on the concentration and quantity of the hazardous substance and specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday. |
| Skin and body protection | : | Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.
Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc). |
| Respiratory protection | : | Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. |
| Filter type | : | Combined particulates and organic vapour type (A-P) |

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

- | | | |
|------------------------------|---|-------------------|
| Appearance | : | paste |
| Colour | : | black |
| Odour | : | slight |
| Odour Threshold | : | No data available |
| pH | : | No data available |
| Melting point/freezing point | : | No data available |

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



WINDSCREEN ADHESIVE XL - 600 ML

Version	Revision Date:	SDS Number:	Date of last issue: 17.03.2017
5.0	17.05.2017	549029-00004	Date of first issue: 11.06.2010

Initial boiling point and boiling range	:	No data available
Flash point	:	100 °C Method: closed cup
Evaporation rate	:	Not applicable
Flammability (solid, gas)	:	Not classified as a flammability hazard
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Vapour pressure	:	Not applicable
Relative vapour density	:	Not applicable
Relative density	:	1,265
Solubility(ies) Water solubility	:	No data available
Partition coefficient: n-octanol/water	:	Not applicable
Auto-ignition temperature	:	No data available
Decomposition temperature	:	No data available
Viscosity Viscosity, kinematic	:	Not applicable
Explosive properties	:	Not explosive
Oxidizing properties	:	The substance or mixture is not classified as oxidizing.

9.2 Other information

Particle size	:	No data available
---------------	---	-------------------

SECTION 10: Stability and reactivity

10.1 Reactivity

Not classified as a reactivity hazard.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions	:	Can react with strong oxidizing agents.
---------------------	---	---

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



WINDSCREEN ADHESIVE XL - 600 ML

Version	Revision Date:	SDS Number:	Date of last issue: 17.03.2017
5.0	17.05.2017	549029-00004	Date of first issue: 11.06.2010

Hazardous decomposition products will be formed upon contact with water or humid air.

10.4 Conditions to avoid

Conditions to avoid : Exposure to moisture

10.5 Incompatible materials

Materials to avoid : Oxidizing agents
Water

10.6 Hazardous decomposition products

No hazardous decomposition products are known.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Information on likely routes of exposure : Skin contact
Ingestion
Eye contact

Acute toxicity

Not classified based on available information.

Product:

Acute inhalation toxicity : Acute toxicity estimate: > 5 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: Calculation method

Components:

Hexamethylene diisocyanate, oligomers:

Acute oral toxicity	: LD50 (Rat, female): > 2.500 mg/kg Method: OECD Test Guideline 423 Assessment: The substance or mixture has no acute oral toxicity
Acute inhalation toxicity	: Acute toxicity estimate: 1,5 mg/l Exposure time: 4 h Test atmosphere: dust/mist Method: Expert judgement
Acute dermal toxicity	: LD50 (Rat): > 2.000 mg/kg Method: OECD Test Guideline 402 Assessment: The substance or mixture has no acute dermal toxicity

4,4'-Diphenylmethane diisocyanate:

Acute oral toxicity : LD50 (Rat): > 2.000 mg/kg

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



WINDSCREEN ADHESIVE XL - 600 ML

Version	Revision Date:	SDS Number:	Date of last issue: 17.03.2017
5.0	17.05.2017	549029-00004	Date of first issue: 11.06.2010

Assessment: The substance or mixture has no acute oral toxicity

Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): > 2,24 mg/l
Exposure time: 1 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 (Rabbit): > 5.000 mg/kg
Remarks: Based on data from similar materials

Skin corrosion/irritation

Not classified based on available information.

Components:

Hexamethylene diisocyanate, oligomers:

Species: Rabbit
Method: OECD Test Guideline 404
Result: No skin irritation

4,4'-Diphenylmethane diisocyanate:

Species: Rabbit
Method: OECD Test Guideline 404
Result: Skin irritation
Remarks: Based on data from similar materials

Serious eye damage/eye irritation

Not classified based on available information.

Components:

Hexamethylene diisocyanate, oligomers:

Species: Rabbit
Method: OECD Test Guideline 405
Result: No eye irritation

4,4'-Diphenylmethane diisocyanate:

Result: Irritation to eyes, reversing within 7 days
Remarks: Based on harmonised classification in EU regulation 1272/2008, Annex VI

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



WINDSCREEN ADHESIVE XL - 600 ML

Version	Revision Date:	SDS Number:	Date of last issue: 17.03.2017
5.0	17.05.2017	549029-00004	Date of first issue: 11.06.2010

Components:

Hexamethylene diisocyanate, oligomers:

Test Type: Local lymph node assay (LLNA)
Exposure routes: Skin contact
Species: Mouse
Method: OECD Test Guideline 429
Result: positive

Assessment: Probability or evidence of skin sensitisation in humans

Exposure routes: Inhalation
Species: Guinea pig
Result: negative

4,4'-Diphenylmethane diisocyanate:

Test Type: Buehler Test
Exposure routes: Skin contact
Species: Guinea pig
Result: positive

Assessment: Probability or evidence of skin sensitisation in humans

Exposure routes: Inhalation
Species: Rat
Result: positive
Remarks: Based on data from similar materials

Assessment: Probability of respiratory sensitisation in humans based on animal testing

Germ cell mutagenicity

Not classified based on available information.

Components:

Hexamethylene diisocyanate, oligomers:

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test
Method: OECD Test Guideline 476
Result: negative

: Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative

: Test Type: Chromosome aberration test in vitro
Method: OECD Test Guideline 473
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Mouse
Application Route: Ingestion
Result: negative

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



WINDSCREEN ADHESIVE XL - 600 ML

Version	Revision Date:	SDS Number:	Date of last issue: 17.03.2017
5.0	17.05.2017	549029-00004	Date of first issue: 11.06.2010

||

4,4'-Diphenylmethane diisocyanate:

Genotoxicity in vitro	:	Test Type: Bacterial reverse mutation assay (AMES) Result: negative
Genotoxicity in vivo	:	Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay) Species: Rat Application Route: inhalation (dust/mist/fume) Method: OECD Test Guideline 474 Result: negative

Carcinogenicity

Not classified based on available information.

Components:

4,4'-Diphenylmethane diisocyanate:

Species: Rat	
Application Route: inhalation (dust/mist/fume)	
Exposure time: 2 Years	
Result: positive	
Remarks: Based on data from similar materials	
Carcinogenicity - Assessment	: Limited evidence of carcinogenicity in animal studies

Reproductive toxicity

Not classified based on available information.

Components:

4,4'-Diphenylmethane diisocyanate:

Effects on foetal development	:	Test Type: Embryo-foetal development Species: Rat Application Route: inhalation (dust/mist/fume) Result: negative Remarks: Based on data from similar materials
-------------------------------	---	---

STOT - single exposure

Not classified based on available information.

Components:

Hexamethylene diisocyanate, oligomers:

Assessment: May cause respiratory irritation.

4,4'-Diphenylmethane diisocyanate:

Assessment: May cause respiratory irritation.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



WINDSCREEN ADHESIVE XL - 600 ML

Version	Revision Date:	SDS Number:	Date of last issue: 17.03.2017
5.0	17.05.2017	549029-00004	Date of first issue: 11.06.2010

STOT - repeated exposure

Not classified based on available information.

Components:

4,4'-Diphenylmethane diisocyanate:

Exposure routes: inhalation (dust/mist/fume)

Target Organs: Respiratory system

Assessment: Shown to produce significant health effects in animals at concentrations of >0.02 to 0.2 mg/l/6h/d.

Repeated dose toxicity

Components:

4,4'-Diphenylmethane diisocyanate:

Species: Rat

NOAEL: 0,2 mg/m³

LOAEL: 1 mg/m³

Application Route: inhalation (dust/mist/fume)

Exposure time: 2 yr

Remarks: Based on data from similar materials

Aspiration toxicity

Not classified based on available information.

SECTION 12: Ecological information

12.1 Toxicity

Components:

Hexamethylene diisocyanate, oligomers:

Toxicity to fish : LC50 (Danio rerio (zebra fish)): > 100 mg/l
Exposure time: 96 h
Method: Directive 67/548/EEC, Annex V, C.1.

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): 127 mg/l
Exposure time: 48 h
Method: Directive 67/548/EEC, Annex V, C.2.

Toxicity to algae : EC10 (Desmodesmus subspicatus (green algae)): 370 mg/l
Exposure time: 72 h

ErC50 (Desmodesmus subspicatus (green algae)): > 1.000 mg/l
Exposure time: 72 h

Toxicity to microorganisms : EC10 : 880 mg/l
Exposure time: 3 h
Method: OECD Test Guideline 209

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



WINDSCREEN ADHESIVE XL - 600 ML

Version	Revision Date:	SDS Number:	Date of last issue: 17.03.2017
5.0	17.05.2017	549029-00004	Date of first issue: 11.06.2010

4,4'-Diphenylmethane diisocyanate:

Toxicity to fish	: LC50 (Oryzias latipes (Orange-red killifish)): > 3.000 mg/l Exposure time: 96 h Remarks: Based on data from similar materials
Toxicity to daphnia and other aquatic invertebrates	: EC50 (Daphnia magna (Water flea)): 129,7 mg/l Exposure time: 24 h Method: OECD Test Guideline 202
Toxicity to algae	: EC50 (Desmodesmus subspicatus (green algae)): > 1.640 mg/l Exposure time: 72 h Method: OECD Test Guideline 201 Remarks: Based on data from similar materials NOEC (Desmodesmus subspicatus (green algae)): 1.640 mg/l Exposure time: 72 h Method: OECD Test Guideline 201 Remarks: Based on data from similar materials
Toxicity to microorganisms	: EC50 : > 100 mg/l Exposure time: 3 h Method: OECD Test Guideline 209 Remarks: Based on data from similar materials
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	: NOEC: 10 mg/l Exposure time: 21 d Species: Daphnia magna (Water flea) Method: OECD Test Guideline 211 Remarks: Based on data from similar materials

12.2 Persistence and degradability

Components:

Hexamethylene diisocyanate, oligomers:

Biodegradability	: Result: Not readily biodegradable. Biodegradation: 1 % Exposure time: 28 d Method: Regulation (EC) No. 440/2008, Annex, C.4-E
------------------	--

4,4'-Diphenylmethane diisocyanate:

Biodegradability	: Result: Not readily biodegradable. Biodegradation: 0 % Exposure time: 28 d Method: OECD Test Guideline 302 Remarks: Based on data from similar materials
------------------	--

12.3 Bioaccumulative potential

Components:

Hexamethylene diisocyanate, oligomers:

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



WINDSCREEN ADHESIVE XL - 600 ML

Version	Revision Date:	SDS Number:	Date of last issue: 17.03.2017
5.0	17.05.2017	549029-00004	Date of first issue: 11.06.2010

Partition coefficient: n-octanol/water	:	log Pow: > 4
	:	Remarks: Calculation

4,4'-Diphenylmethane diisocyanate:

Bioaccumulation	:	Species: Cyprinus carpio (Carp)
	:	Bioconcentration factor (BCF): 200

Partition coefficient: n-octanol/water	:	log Pow: 4,51
--	---	---------------

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Not relevant

12.6 Other adverse effects

No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product	:	Dispose of in accordance with local regulations. According to the European Waste Catalogue, Waste Codes are not product specific, but application specific. Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities.
---------	---	---

Contaminated packaging	:	Empty containers should be taken to an approved waste handling site for recycling or disposal. If not otherwise specified: Dispose of as unused product.
------------------------	---	---

Waste Code	:	The following Waste Codes are only suggestions: used product 080501, waste isocyanates unused product 080501, waste isocyanates uncleaned packagings 150110, packaging containing residues of or contaminated by dangerous substances
------------	---	---

SECTION 14: Transport information

14.1 UN number

ADN	:	Not regulated as a dangerous good
ADR	:	Not regulated as a dangerous good

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



WINDSCREEN ADHESIVE XL - 600 ML

Version	Revision Date:	SDS Number:	Date of last issue: 17.03.2017
5.0	17.05.2017	549029-00004	Date of first issue: 11.06.2010

RID	: Not regulated as a dangerous good
IMDG	: Not regulated as a dangerous good
IATA	: UN 3335

14.2 UN proper shipping name

ADN	: Not regulated as a dangerous good
ADR	: Not regulated as a dangerous good
RID	: Not regulated as a dangerous good
IMDG	: Not regulated as a dangerous good
IATA	: Aviation regulated solid, n.o.s. (4,4'-Diphenylmethane diisocyanate)

14.3 Transport hazard class(es)

ADN	: Not regulated as a dangerous good
ADR	: Not regulated as a dangerous good
RID	: Not regulated as a dangerous good
IMDG	: Not regulated as a dangerous good
IATA	: 9

14.4 Packing group

ADN	: Not regulated as a dangerous good
ADR	: Not regulated as a dangerous good
RID	: Not regulated as a dangerous good
IMDG	: Not regulated as a dangerous good

IATA (Cargo)

Packing instruction (cargo aircraft)	: 956
Packing instruction (LQ)	: Y956
Packing group	: III
Labels	: Miscellaneous

IATA (Passenger)

Packing instruction (passenger aircraft)	: 956
Packing instruction (LQ)	: Y956
Packing group	: III
Labels	: Miscellaneous

14.5 Environmental hazards

ADN	: Not regulated as a dangerous good
ADR	: Not regulated as a dangerous good
RID	: Not regulated as a dangerous good
IMDG	: Not regulated as a dangerous good

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



WINDSCREEN ADHESIVE XL - 600 ML

Version	Revision Date:	SDS Number:	Date of last issue: 17.03.2017
5.0	17.05.2017	549029-00004	Date of first issue: 11.06.2010

14.6 Special precautions for user

Not applicable

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Remarks : Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII) : 4,4'-Diphenylmethane diisocyanate (56)

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : Not applicable

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

Regulation (EC) No 850/2004 on persistent organic pollutants : Not applicable

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals : Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

Not applicable

Water contaminating class (Germany) : WGK 1 slightly water endangering
Classification according VwVwS, Annex 4.

Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)
Volatile organic compounds (VOC) content: 0 %, 0 g/l
Remarks: VOC content excluding water

Other regulations:

TRGS 430 (German regulatory requirements)

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

15.2 Chemical safety assessment

A Chemical Safety Assessment has not been carried out.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



WINDSCREEN ADHESIVE XL - 600 ML

Version	Revision Date:	SDS Number:	Date of last issue: 17.03.2017
5.0	17.05.2017	549029-00004	Date of first issue: 11.06.2010

SECTION 16: Other information

Full text of H-Statements

H315	: Causes skin irritation.
H317	: May cause an allergic skin reaction.
H319	: Causes serious eye irritation.
H332	: Harmful if inhaled.
H334	: May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	: May cause respiratory irritation.
H351	: Suspected of causing cancer.
H373	: May cause damage to organs through prolonged or repeated exposure if inhaled.

Full text of other abbreviations

Acute Tox.	: Acute toxicity
Carc.	: Carcinogenicity
Eye Irrit.	: Eye irritation
Resp. Sens.	: Respiratory sensitisation
Skin Irrit.	: Skin irritation
Skin Sens.	: Skin sensitisation
STOT RE	: Specific target organ toxicity - repeated exposure
STOT SE	: Specific target organ toxicity - single exposure
DE TRGS 900	: Germany. TRGS 900 - Occupational exposure limit values.
TRGS 430	: Germany. TRGS 430 - Isocyanates
DE TRGS 900 / AGW	: Time Weighted Average
TRGS 430 / AGW	: Occupational Exposure Limit

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organization for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



WINDSCREEN ADHESIVE XL - 600 ML

Version	Revision Date:	SDS Number:	Date of last issue: 17.03.2017
5.0	17.05.2017	549029-00004	Date of first issue: 11.06.2010

1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Sources of key data used to compile the Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Classification of the mixture:

Resp. Sens. 1	H334
Skin Sens. 1	H317

Classification procedure:

Calculation method
Calculation method

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

DE / EN