according to Regulation (EC) No. 1907/2006



TRIATHLON 2T-SAFETYMIX - 200 L

Version Revision Date: SDS Number: Date of last issue: -

1.0 10.04.2017 506664-00005 Date of first issue: 10.04.2017

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : TRIATHLON 2T-SAFETYMIX - 200 L

Product code : 0897055200

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub- : Fuel

stance/Mixture

1.3 Details of the supplier of the safety data sheet

Company : Adolf Wuerth GmbH & Co. KG

Reinhold-Würth-Str. 12-17

74653 Künzelsau

Telephone : +49 794015 0

Telefax : +49 794015 10 00

E-mail address of person

responsible for the SDS

: prodsafe@wuerth.com

1.4 Emergency telephone number

Giftnotrufzentrale Berlin +49 30 30686 790. Gesellschaft (07:00 – 18:00 Uhr) +49 794015 2552

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 1 H224: Extremely flammable liquid and vapour.

Skin irritation, Category 2 H315: Causes skin irritation.

Specific target organ toxicity - single ex-

posure, Category 3

H336: May cause drowsiness or dizziness.

Aspiration hazard, Category 1 H304: May be fatal if swallowed and enters air-

ways.

Chronic aquatic toxicity, Category 2 H411: Toxic to aquatic life with long lasting effects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

according to Regulation (EC) No. 1907/2006



TRIATHLON 2T-SAFETYMIX - 200 L

Version Revision Date: SDS Number: Date of last issue: -

1.0 10.04.2017 506664-00005 Date of first issue: 10.04.2017

Hazard pictograms :









Signal word : Danger

Hazard statements : H224 Extremely flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements : Prevention:

P210 Keep away from heat, hot surfaces, sparks, open

flames and other ignition sources. No smoking.

P233 Keep container tightly closed.
P273 Avoid release to the environment.

Response:

P301 + P310 IF SWALLOWED: Immediately call a POISON

CENTER/doctor.

P331 Do NOT induce vomiting.

Storage:

P403 + P235 Store in a well-ventilated place. Keep cool.

Hazardous components which must be listed on the label:

Gasoline

2.3 Other hazards

Vapours may form explosive mixture with air.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
Gasoline	86290-81-5 289-220-8 649-378-00-4 01-2119471335-39	Flam. Liq. 1; H224 Skin Irrit. 2; H315 STOT SE 3; H336 Asp. Tox. 1; H304 Aquatic Chronic 2; H411	>= 90 - <= 100

For explanation of abbreviations see section 16.

according to Regulation (EC) No. 1907/2006



TRIATHLON 2T-SAFETYMIX - 200 L

Version Revision Date: SDS Number: Date of last issue: -

1.0 10.04.2017 506664-00005 Date of first issue: 10.04.2017

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : In the case of accident or if you feel unwell, seek medical ad-

vice immediately.

When symptoms persist or in all cases of doubt seek medical

advice.

Protection of first-aiders : First Aid responders should pay attention to self-protection,

and use the recommended personal protective equipment

when the potential for exposure exists.

If inhaled : If inhaled, remove to fresh air.

Get medical attention if symptoms occur.

In case of skin contact : In case of contact, immediately flush skin with plenty of water

for at least 15 minutes while removing contaminated clothing

and shoes.

Get medical attention. Wash clothing before reuse.

Thoroughly clean shoes before reuse.

In case of eye contact : Flush eyes with water as a precaution.

Get medical attention if irritation develops and persists.

If swallowed, DO NOT induce vomiting.

If vomiting occurs have person lean forward.

Call a physician or poison control centre immediately.

Rinse mouth thoroughly with water.

Never give anything by mouth to an unconscious person.

4.2 Most important symptoms and effects, both acute and delayed

Risks : May be fatal if swallowed and enters airways.

Causes skin irritation.

May cause drowsiness or dizziness.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically and supportively.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Water spray

Alcohol-resistant foam Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

High volume water jet

according to Regulation (EC) No. 1907/2006



TRIATHLON 2T-SAFETYMIX - 200 L

Version Revision Date: SDS Number: Date of last issue: -

1.0 10.04.2017 506664-00005 Date of first issue: 10.04.2017

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-

fighting

Do not use a solid water stream as it may scatter and spread

fire.

Flash back possible over considerable distance.

Exposure to combustion products may be a hazard to health.

Hazardous combustion prod: :

ucts

Carbon oxides

5.3 Advice for firefighters

Special protective equipment:

for firefighters

In the event of fire, wear self-contained breathing apparatus.

Use personal protective equipment.

Specific extinguishing meth-

ods

Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment. Use water spray to cool unopened containers.

Remove undamaged containers from fire area if it is safe to do

SO.

Evacuate area.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Remove all sources of ignition.

Ventilate the area.

Use personal protective equipment.

Follow safe handling advice and personal protective equip-

ment recommendations.

6.2 Environmental precautions

Environmental precautions : Discharge into the environment must be avoided.

Prevent further leakage or spillage if safe to do so.

Prevent spreading over a wide area (e.g. by containment or oil

barriers).

Retain and dispose of contaminated wash water.

Local authorities should be advised if significant spillages

cannot be contained.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Non-sparking tools should be used.

Soak up with inert absorbent material.

Suppress (knock down) gases/vapours/mists with a water

spray jet.

For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped, store recovered material in appropriate container. Clean up remaining materials from spill with suitable absor-

bent.

Local or national regulations may apply to releases and disposal of this material, as well as those materials and items

according to Regulation (EC) No. 1907/2006



TRIATHLON 2T-SAFETYMIX - 200 L

Version Revision Date: SDS Number: Date of last issue: -

1.0 10.04.2017 506664-00005 Date of first issue: 10.04.2017

employed in the cleanup of releases. You will need to deter-

mine which regulations are applicable.

Sections 13 and 15 of this SDS provide information regarding

certain local or national requirements.

6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Technical measures : See Engineering measures under EXPOSURE

CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation : Use with local exhaust ventilation.

Use only in an area equipped with explosion proof exhaust

ventilation.

Advice on safe handling : Do not get on skin or clothing.

Do not breathe vapours or spray mist.

Do not swallow.

Avoid contact with eyes.

Handle in accordance with good industrial hygiene and safety

practice.

Non-sparking tools should be used. Keep container tightly closed.

Keep away from heat and sources of ignition.

Take precautionary measures against static discharges.

Take care to prevent spills, waste and minimize release to the

environment.

Hygiene measures : Ensure that eye flushing systems and safety showers are

located close to the working place. When using do not eat, drink or smoke. Wash contaminated clothing before re-use.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

: Keep in properly labelled containers. Store locked up. Keep tightly closed. Keep in a cool, well-ventilated place. Store in accordance with the particular national regulations. Keep

away from heat and sources of ignition.

Advice on common storage : Do not store with the following product types:

Strong oxidizing agents Organic peroxides Flammable solids Pyrophoric liquids Pyrophoric solids

Self-heating substances and mixtures

Substances and mixtures, which in contact with water, emit

flammable gases

Explosives Gases

according to Regulation (EC) No. 1907/2006



TRIATHLON 2T-SAFETYMIX - 200 L

Version Revision Date: SDS Number: Date of last issue: -

1.0 10.04.2017 506664-00005 Date of first issue: 10.04.2017

Storage class (TRGS 510) : 3, Flammable liquids

7.3 Specific end use(s)

Specific use(s) : No data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Contains no substances with occupational exposure limit values.

8.2 Exposure controls

Engineering measures

Minimize workplace exposure concentrations.

Use only in an area equipped with explosion proof exhaust ventilation.

Use with local exhaust ventilation.

Personal protective equipment

Eye protection : Wear the following personal protective equipment:

Safety glasses

Hand protection

Material : Nitrile rubber
Break through time : > 240 min
Glove thickness : 0,425 mm

Remarks : Choose gloves to protect hands against chemicals depending

on the concentration and quantity of the hazardous substance and specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.

Skin and body protection : Select appropriate protective clothing based on chemical

resistance data and an assessment of the local exposure

potential.

Wear the following personal protective equipment:

Flame retardant antistatic protective clothing.

Skin contact must be avoided by using impervious protective

clothing (gloves, aprons, boots, etc).

Respiratory protection : Use respiratory protection unless adequate local exhaust

ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Filter type : Organic gas and low boiling vapour type (AX)

according to Regulation (EC) No. 1907/2006



TRIATHLON 2T-SAFETYMIX - 200 L

Version Revision Date: SDS Number: Date of last issue: -

1.0 10.04.2017 506664-00005 Date of first issue: 10.04.2017

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance : liquid

Colour : green

Odour : characteristic

Odour Threshold : No data available

pH : No data available

Melting point/freezing point : No data available

Initial boiling point and boiling

range

< 35 °C

ange

Method: DIN 51751

Flash point : < -18 °C

Other information: No data available

Evaporation rate : No data available

Flammability (solid, gas) : Not applicable

Upper explosion limit / Upper

flammability limit

7,6 %(V)

Lower explosion limit / Lower :

flammability limit

1,4 %(V)

Vapour pressure : No data available

Relative vapour density : No data available

Relative density : No data available

Density : 0,685 g/cm3 (20 °C)

Solubility(ies)

Water solubility : insoluble

Partition coefficient: n-

octanol/water

Not applicable

Auto-ignition temperature : No data available

Decomposition temperature : No data available

Viscosity

Viscosity, kinematic : < 7 mm2/s (40 °C)

Explosive properties : Not explosive

according to Regulation (EC) No. 1907/2006



TRIATHLON 2T-SAFETYMIX - 200 L

Version Revision Date: SDS Number: Date of last issue: -

1.0 10.04.2017 506664-00005 Date of first issue: 10.04.2017

Oxidizing properties : The substance or mixture is not classified as oxidizing.

9.2 Other information

Particle size : Not applicable

Self-ignition : not auto-flammable

SECTION 10: Stability and reactivity

10.1 Reactivity

Not classified as a reactivity hazard.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions : Extremely flammable liquid and vapour.

Can react with strong oxidizing agents.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : Oxidizing agents

10.6 Hazardous decomposition products

No hazardous decomposition products are known.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Information on likely routes of :

exposure Inhalation

Skin contact Ingestion Eye contact

Acute toxicity

Not classified based on available information.

Components:

Gasoline:

Acute oral toxicity : LD50 (Rat): > 5.000 mg/kg

Acute dermal toxicity : LD50 (Rabbit): > 2.000 mg/kg

Assessment: The substance or mixture has no acute dermal

according to Regulation (EC) No. 1907/2006



TRIATHLON 2T-SAFETYMIX - 200 L

Version Revision Date: SDS Number: Date of last issue: -

1.0 10.04.2017 506664-00005 Date of first issue: 10.04.2017

toxicity

Skin corrosion/irritation

Causes skin irritation.

Components:

Gasoline:

Species: Rabbit

Method: OECD Test Guideline 404

Result: Skin irritation

Serious eye damage/eye irritation

Not classified based on available information.

Components:

Gasoline:

Species: Rabbit

Result: No eye irritation

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Components:

Gasoline:

Test Type: Buehler Test Exposure routes: Skin contact

Species: Guinea pig Result: negative

Germ cell mutagenicity

Not classified based on available information.

Components:

Gasoline:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo

cytogenetic assay) Species: Rat

Application Route: inhalation (vapour)

Method: OPPTS 870.5395

Result: negative

according to Regulation (EC) No. 1907/2006



TRIATHLON 2T-SAFETYMIX - 200 L

Version Revision Date: SDS Number: Date of last issue: -

1.0 10.04.2017 506664-00005 Date of first issue: 10.04.2017

Carcinogenicity

Not classified based on available information.

Components:

Gasoline:

Species: Mouse

Application Route: Skin contact Exposure time: 102 weeks

Result: negative

Reproductive toxicity

Not classified based on available information.

Components:

Gasoline:

Effects on fertility : Test Type: Two-generation reproduction toxicity study

Species: Rat

Application Route: inhalation (vapour)

Result: negative

Effects on foetal develop-

ment

Test Type: Embryo-foetal development

Species: Rat

Application Route: inhalation (vapour)

Result: negative

STOT - single exposure

May cause drowsiness or dizziness.

Components:

Gasoline:

Assessment: May cause drowsiness or dizziness.

STOT - repeated exposure

Not classified based on available information.

Repeated dose toxicity

Components:

Gasoline:

Species: Rat

NOAEL: 3.750 mg/kg

Application Route: Skin contact Exposure time: 4 Weeks

Remarks: Based on data from similar materials

Aspiration toxicity

May be fatal if swallowed and enters airways.

according to Regulation (EC) No. 1907/2006



TRIATHLON 2T-SAFETYMIX - 200 L

Version Revision Date: SDS Number: Date of last issue: -

1.0 10.04.2017 506664-00005 Date of first issue: 10.04.2017

Components:

Gasoline:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

SECTION 12: Ecological information

12.1 Toxicity

Components:

Gasoline:

Toxicity to fish : LL50 (Pimephales promelas (fathead minnow)): 8,2 mg/l

Exposure time: 96 h

Test substance: Water Accommodated Fraction Remarks: Based on data from similar materials

Toxicity to daphnia and other :

aquatic invertebrates

EL50 (Daphnia magna (Water flea)): 4,5 mg/l

Exposure time: 48 h

Test substance: Water Accommodated Fraction

Method: OECD Test Guideline 202

Remarks: Based on data from similar materials

Toxicity to algae : NOELR (Pseudokirchneriella subcapitata (green algae)): 0,5

mg/l

Exposure time: 72 h

Test substance: Water Accommodated Fraction

Method: OECD Test Guideline 201

Remarks: Based on data from similar materials

EL50 (Pseudokirchneriella subcapitata (green algae)): 3,1

mg/l

Exposure time: 72 h

Test substance: Water Accommodated Fraction

Method: OECD Test Guideline 201

Remarks: Based on data from similar materials

Toxicity to fish (Chronic tox-

icity)

NOELR: 2,6 mg/l

Exposure time: 14 d

Species: Pimephales promelas (fathead minnow) Test substance: Water Accommodated Fraction

Method: OECD Test Guideline 204

Remarks: Based on data from similar materials

Toxicity to daphnia and other

aquatic invertebrates (Chron-

ic toxicity)

NOELR: 2,6 mg/l Exposure time: 21 d

Species: Daphnia magna (Water flea)

Test substance: Water Accommodated Fraction

Method: OECD Test Guideline 211

Remarks: Based on data from similar materials

according to Regulation (EC) No. 1907/2006



TRIATHLON 2T-SAFETYMIX - 200 L

Version Revision Date: SDS Number: Date of last issue: -

1.0 10.04.2017 506664-00005 Date of first issue: 10.04.2017

12.2 Persistence and degradability

Components:

Gasoline:

Biodegradability : Result: Inherently biodegradable.

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Not relevant

12.6 Other adverse effects

No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Dispose of in accordance with local regulations.

According to the European Waste Catalogue, Waste Codes

are not product specific, but application specific.

Waste codes should be assigned by the user, preferably in

discussion with the waste disposal authorities.

Contaminated packaging : Empty containers should be taken to an approved waste han-

dling site for recycling or disposal.

Empty containers retain residue and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury and/or death. If not otherwise specified: Dispose of as unused product.

Waste Code : The following Waste Codes are only suggestions:

used product 130702, petrol

unused product 130702, petrol

uncleaned packagings

150110, packaging containing residues of or contaminated by

dangerous substances

SECTION 14: Transport information

14.1 UN number

according to Regulation (EC) No. 1907/2006



TRIATHLON 2T-SAFETYMIX - 200 L

Version Revision Date: SDS Number: Date of last issue: -

10.04.2017 506664-00005 Date of first issue: 10.04.2017 1.0

ADN UN 1203 **ADR** UN 1203 RID UN 1203 **IMDG** UN 1203 **IATA** UN 1203

14.2 UN proper shipping name

ADN GASOLINE ADR GASOLINE RID **GASOLINE IMDG GASOLINE** (Gasoline)

IATA Gasoline

14.3 Transport hazard class(es)

ADN 3 **ADR** 3 **RID** 3 **IMDG** 3 **IATA** 3

14.4 Packing group

ADN

Packing group Ш F1 Classification Code Hazard Identification Number 33 Labels 3

ADR

Packing group Ш Classification Code F1 Hazard Identification Number : 33 Labels 3 Tunnel restriction code (D/E)

RID

Packing group Ш Classification Code F1 Hazard Identification Number 33 Labels 3

IMDG

Ш Packing group Labels 3

F-E, S-E **EmS Code**

IATA (Cargo)

Packing instruction (cargo 364

according to Regulation (EC) No. 1907/2006



TRIATHLON 2T-SAFETYMIX - 200 L

Version Revision Date: SDS Number: Date of last issue: -

1.0 10.04.2017 506664-00005 Date of first issue: 10.04.2017

aircraft)

Packing instruction (LQ) : Y341
Packing group : II

Labels : Flammable Liquids

IATA (Passenger)

Packing instruction (passen: 353

ger aircraft)

Packing instruction (LQ) : Y341
Packing group : II

Labels : Flammable Liquids

14.5 Environmental hazards

ADN

Environmentally hazardous : yes

ADR

Environmentally hazardous : yes

RID

Environmentally hazardous : yes

IMDG

Marine pollutant : yes

14.6 Special precautions for user

Not applicable

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Remarks : Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on

the market and use of certain dangerous substances,

preparations and articles (Annex XVII)

REACH - Candidate List of Substances of Very High

Concern for Authorisation (Article 59).

Not applicable

Gasoline (29, 28)

Regulation (EC) No 1005/2009 on substances that de-

plete the ozone layer

: Not applicable

Regulation (EC) No 850/2004 on persistent organic pol-

lutants

Not applicable

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import

of dangerous chemicals

Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

Quantity 1 Quantity 2

according to Regulation (EC) No. 1907/2006



TRIATHLON 2T-SAFETYMIX - 200 L

Version 1.0	Revision Date: 10.04.2017		OS Number: 16664-00005		ast issue: - rst issue: 10.04.20)17
P5a			FLAMMABLE LIC	UIDS	10 t	50 t
E2			ENVIRONMENTA HAZARDS	AL	200 t	500 t
34			Petroleum products: (a) gasolines and naphthas, (b) kerosenes (including jet fuels), (c) gas oils (including diesel fuels, home heating oils and gas oil blending streams),(d) heavy fuel oils (e) alternative fuels serving the same purposes and with similar properties as regards flammability and environmental hazards as the products referred to in points (a) to (d)		2.500 t	25.000 t
Water (Germ	contaminating class any)	:	WGK 2 water end Classification acc		√wS, Annex 4.	

Other regulations:

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control) Volatile organic compounds (VOC) content: 97,50 %

15.2 Chemical safety assessment

Volatile organic compounds

A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

Full text of H-Statements

H224 : Extremely flammable liquid and vapour.
H304 : May be fatal if swallowed and enters airways.

H315 : Causes skin irritation.

H336 : May cause drowsiness or dizziness.

H411 : Toxic to aquatic life with long lasting effects.

Full text of other abbreviations

Aquatic Chronic : Chronic aquatic toxicity
Asp. Tox. : Aspiration hazard
Flam. Liq. : Flammable liquids
Skin Irrit. : Skin irritation

STOT SE : Specific target organ toxicity - single exposure

according to Regulation (EC) No. 1907/2006



TRIATHLON 2T-SAFETYMIX - 200 L

Version Revision Date: SDS Number: Date of last issue: -

506664-00005 Date of first issue: 10.04.2017 1.0 10.04.2017

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways: ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road: AICS - Australian Inventory of Chemical Substances: ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx -Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx -Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals: OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

compile the Safety Data Sheet

Sources of key data used to : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agen-

cy, http://echa.europa.eu/

Classification of the mixture:

Classification procedure:

Flam. Liq. 1	H224	Based on product data or assessment
Skin Irrit. 2	H315	Calculation method
STOT SE 3	H336	Calculation method
Asp. Tox. 1	H304	Calculation method
Aquatic Chronic 2	H411	Calculation method

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only

according to Regulation (EC) No. 1907/2006



TRIATHLON 2T-SAFETYMIX - 200 L

Version Revision Date: SDS Number: Date of last issue: -

1.0 10.04.2017 506664-00005 Date of first issue: 10.04.2017

to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

DE / EN