

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



ENGINE OIL TRIATHLON LONGLIFE SHPD 15W40 - 20 L

Version	Revision Date:	SDS Number:	Date of last issue: 17.01.2017
1.2	10.04.2017	857053-00003	Date of first issue: 24.08.2016

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : ENGINE OIL TRIATHLON LONGLIFE SHPD 15W40 - 20 L
Product code : 0897325403

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-
stance/Mixture : Engine oil

1.3 Details of the supplier of the safety data sheet

Company : Adolf Wuerth GmbH & Co. KG
Reinhold-Würth-Str. 12-17
74653 Künzelsau

Telephone : +49 794015 0

Telefax : +49 794015 10 00

E-mail address of person
responsible for the SDS : prodsafe@wuerth.com

1.4 Emergency telephone number

Giftnotrufzentrale Berlin +49 30 30686 790. Gesellschaft (07:00 – 18:00 Uhr) +49 794015
2552

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Eye irritation, Category 2 H319: Causes serious eye irritation.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : Warning

Hazard statements : H319 Causes serious eye irritation.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



ENGINE OIL TRIATHLON LONGLIFE SHPD 15W40 - 20 L

Version 1.2 Revision Date: 10.04.2017 SDS Number: 857053-00003 Date of last issue: 17.01.2017
Date of first issue: 24.08.2016

Precautionary statements : **Prevention:**
P264 Wash skin thoroughly after handling.
P280 Wear eye protection/ face protection.
Response:
P337 + P313 If eye irritation persists: Get medical advice/ attention.

Additional Labelling

EUH208 Contains Benzenesulfonic acid methyl-, mono C20-26 branched alkyl derivs., calcium salt, Benzenesulfonic acid, methyl-, mono-C20-24-branched alkyl derivs., calcium salts. May produce an allergic reaction.

2.3 Other hazards

None known.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
Polyolefin-polyaminesuccinimide, polyol	Proprietary Ingredient	Aquatic Chronic 4; H413	$\geq 2,5$ - < 10
Phosphorodithioic acid, mixed O,O-bis(sec-Bu and 1,3-dimethylbutyl) esters, zinc salts	68784-31-6 272-238-5 01-2119657973-23	Eye Dam. 1; H318 Aquatic Chronic 2; H411	≥ 1 - $< 2,5$
Calcium alkaryl sulphonate, long chain	Proprietary Ingredient	Aquatic Chronic 4; H413	≥ 1 - $< 2,5$
Benzenesulfonic acid methyl-, mono C20-26 branched alkyl derivs., calcium salt	722503-69-7	Skin Sens. 1; H317 Aquatic Chronic 4; H413	$\geq 0,25$ - < 1
Benzenesulfonic acid, methyl-, mono-C20-24-branched alkyl derivs., calcium salts	722503-68-6	Skin Sens. 1; H317 Aquatic Chronic 4; H413	$\geq 0,1$ - $< 0,25$

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : In the case of accident or if you feel unwell, seek medical advice immediately.
When symptoms persist or in all cases of doubt seek medical advice.

Protection of first-aiders : First Aid responders should pay attention to self-protection,

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



ENGINE OIL TRIATHLON LONGLIFE SHPD 15W40 - 20 L

Version	Revision Date:	SDS Number:	Date of last issue: 17.01.2017
1.2	10.04.2017	857053-00003	Date of first issue: 24.08.2016

- and use the recommended personal protective equipment when the potential for exposure exists.
- If inhaled : If inhaled, remove to fresh air.
Get medical attention if symptoms occur.
- In case of skin contact : In case of contact, immediately flush skin with soap and plenty of water.
Remove contaminated clothing and shoes.
Get medical attention.
Wash clothing before reuse.
Thoroughly clean shoes before reuse.
- In case of eye contact : In case of contact, immediately flush eyes with plenty of water for at least 15 minutes.
If easy to do, remove contact lens, if worn.
Get medical attention.
- If swallowed : If swallowed, DO NOT induce vomiting.
Get medical attention if symptoms occur.
Rinse mouth thoroughly with water.

4.2 Most important symptoms and effects, both acute and delayed

- Risks : May produce an allergic reaction.

Causes serious eye irritation.

4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : Treat symptomatically and supportively.
-

SECTION 5: Firefighting measures

5.1 Extinguishing media

- Suitable extinguishing media : Water spray
Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical
- Unsuitable extinguishing media : None known.

5.2 Special hazards arising from the substance or mixture

- Specific hazards during fire-fighting : Exposure to combustion products may be a hazard to health.
- Hazardous combustion products : Carbon oxides
Nitrogen oxides (NO_x)
Sulphur oxides
Metal oxides

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



ENGINE OIL TRIATHLON LONGLIFE SHPD 15W40 - 20 L

Version	Revision Date:	SDS Number:	Date of last issue: 17.01.2017
1.2	10.04.2017	857053-00003	Date of first issue: 24.08.2016

Oxides of phosphorus

5.3 Advice for firefighters

- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus. Use personal protective equipment.
- Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Use water spray to cool unopened containers. Remove undamaged containers from fire area if it is safe to do so. Evacuate area.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

- Personal precautions : Use personal protective equipment. Follow safe handling advice and personal protective equipment recommendations.

6.2 Environmental precautions

- Environmental precautions : Discharge into the environment must be avoided. Prevent further leakage or spillage if safe to do so. Prevent spreading over a wide area (e.g. by containment or oil barriers). Retain and dispose of contaminated wash water. Local authorities should be advised if significant spillages cannot be contained.

6.3 Methods and material for containment and cleaning up

- Methods for cleaning up : Soak up with inert absorbent material. For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped, store recovered material in appropriate container. Clean up remaining materials from spill with suitable absorbent. Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable. Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



ENGINE OIL TRIATHLON LONGLIFE SHPD 15W40 - 20 L

Version 1.2 Revision Date: 10.04.2017 SDS Number: 857053-00003 Date of last issue: 17.01.2017
Date of first issue: 24.08.2016

SECTION 7: Handling and storage

7.1 Precautions for safe handling

- Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.
- Local/Total ventilation : Use only with adequate ventilation.
- Advice on safe handling : Do not get on skin or clothing.
Avoid inhalation of vapour or mist.
Do not swallow.
Do not get in eyes.
Handle in accordance with good industrial hygiene and safety practice.
Take care to prevent spills, waste and minimize release to the environment.
- Hygiene measures : Ensure that eye flushing systems and safety showers are located close to the working place. When using do not eat, drink or smoke. Wash contaminated clothing before re-use.

7.2 Conditions for safe storage, including any incompatibilities

- Requirements for storage areas and containers : Keep in properly labelled containers. Store in accordance with the particular national regulations.
- Advice on common storage : Do not store with the following product types:
Strong oxidizing agents
- Storage class (TRGS 510) : 10, Combustible liquids

7.3 Specific end use(s)

- Specific use(s) : No data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Contains no substances with occupational exposure limit values.

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
Phosphorodithioic acid, mixed O,O-bis(sec-Bu and 1,3-dimethylbutyl) esters, zinc salts	Workers	Inhalation	Long-term systemic effects	2,93 mg/m ³
	Workers	Inhalation	Acute systemic ef-	496,4 mg/m ³

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



ENGINE OIL TRIATHLON LONGLIFE SHPD 15W40 - 20 L

Version 1.2 Revision Date: 10.04.2017 SDS Number: 857053-00003 Date of last issue: 17.01.2017
Date of first issue: 24.08.2016

Exposure Scenario	Exposure Route	Effect	Value
Workers	Skin contact	Long-term systemic effects	10,42 mg/kg bw/day
Workers	Skin contact	Acute systemic effects	100 mg/kg bw/day
Consumers	Inhalation	Long-term systemic effects	11,75 mg/m ³
Consumers	Inhalation	Acute systemic effects	198,6 mg/m ³
Consumers	Skin contact	Long-term systemic effects	2,1 mg/kg bw/day
Consumers	Skin contact	Acute systemic effects	50 mg/kg bw/day
Consumers	Ingestion	Long-term systemic effects	0,21 mg/kg bw/day
Consumers	Ingestion	Acute systemic effects	29 mg/kg bw/day

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
Phosphorodithioic acid, mixed O,O-bis(sec-Bu and 1,3-dimethylbutyl) esters, zinc salts	Fresh water	0,004 mg/l
	Marine water	0,0046 mg/l
	Intermittent use/release	0,044 mg/l
	Sewage treatment plant	0,0038 mg/l
	Fresh water sediment	0,0701 mg/kg
	Marine sediment	0,00701 mg/kg
	Soil	0,0548 mg/kg
	Oral (Secondary Poisoning)	8,33 mg/kg food

8.2 Exposure controls

Engineering measures

Ensure adequate ventilation, especially in confined areas.
Minimize workplace exposure concentrations.

Personal protective equipment

Eye protection : Wear the following personal protective equipment:
Safety goggles

Hand protection
Material : Nitrile rubber
Break through time : > 480 min
Glove thickness : 0,4 mm
Directive : DIN EN 374

Remarks : Choose gloves to protect hands against chemicals depending on the concentration and quantity of the hazardous substance and specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



ENGINE OIL TRIATHLON LONGLIFE SHPD 15W40 - 20 L

Version	Revision Date:	SDS Number:	Date of last issue: 17.01.2017
1.2	10.04.2017	857053-00003	Date of first issue: 24.08.2016

er. Wash hands before breaks and at the end of workday.

Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.
Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).

Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Filter type : Organic vapour type (A)

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance	: liquid
Colour	: brown
Odour	: characteristic
Odour Threshold	: No data available
pH	: No data available
Melting point/freezing point	: No data available
Initial boiling point and boiling range	: No data available
Flash point	: 226 °C Other information: No data available
Evaporation rate	: No data available
Flammability (solid, gas)	: Not applicable
Upper explosion limit / Upper flammability limit	: No data available
Lower explosion limit / Lower flammability limit	: No data available
Vapour pressure	: No data available
Relative vapour density	: No data available
Relative density	: No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



ENGINE OIL TRIATHLON LONGLIFE SHPD 15W40 - 20 L

Version	Revision Date:	SDS Number:	Date of last issue: 17.01.2017
1.2	10.04.2017	857053-00003	Date of first issue: 24.08.2016

Density	:	0,880 g/cm ³ (20 °C)
Solubility(ies) Water solubility	:	insoluble
Partition coefficient: n- octanol/water	:	Not applicable
Auto-ignition temperature	:	No data available
Decomposition temperature	:	No data available
Viscosity Viscosity, kinematic	:	103 mm ² /s (40 °C) 14,4 mm ² /s (100 °C)
Explosive properties	:	Not explosive
Oxidizing properties	:	The substance or mixture is not classified as oxidizing.

9.2 Other information

Particle size	:	Not applicable
---------------	---	----------------

SECTION 10: Stability and reactivity

10.1 Reactivity

Not classified as a reactivity hazard.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions	:	Can react with strong oxidizing agents.
---------------------	---	---

10.4 Conditions to avoid

Conditions to avoid	:	None known.
---------------------	---	-------------

10.5 Incompatible materials

Materials to avoid	:	Oxidizing agents
--------------------	---	------------------

10.6 Hazardous decomposition products

No hazardous decomposition products are known.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Information on likely routes of	:	Inhalation
---------------------------------	---	------------

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



ENGINE OIL TRIATHLON LONGLIFE SHPD 15W40 - 20 L

Version	Revision Date:	SDS Number:	Date of last issue: 17.01.2017
1.2	10.04.2017	857053-00003	Date of first issue: 24.08.2016

Species: Rabbit
Method: OECD Test Guideline 405
Result: Irreversible effects on the eye

Benzenesulfonic acid, methyl-, mono-C20-24-branched alkyl derivs., calcium salts:

Species: Rabbit
Method: OECD Test Guideline 405
Result: No eye irritation
Remarks: Based on data from similar materials

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Components:

Phosphorodithioic acid, mixed O,O-bis(sec-Bu and 1,3-dimethylbutyl) esters, zinc salts:

Test Type: Buehler Test
Exposure routes: Skin contact
Species: Guinea pig
Method: OECD Test Guideline 406
Result: negative

Benzenesulfonic acid methyl-, mono C20-26 branched alkyl derivs., calcium salt:

Assessment: Probability or evidence of skin sensitisation in humans

Benzenesulfonic acid, methyl-, mono-C20-24-branched alkyl derivs., calcium salts:

Test Type: Buehler Test
Exposure routes: Skin contact
Species: Guinea pig
Method: OECD Test Guideline 406
Result: positive
Remarks: Based on data from similar materials

Assessment: Probability or evidence of skin sensitisation in humans

Germ cell mutagenicity

Not classified based on available information.

Components:

Phosphorodithioic acid, mixed O,O-bis(sec-Bu and 1,3-dimethylbutyl) esters, zinc salts:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



ENGINE OIL TRIATHLON LONGLIFE SHPD 15W40 - 20 L

Version	Revision Date:	SDS Number:	Date of last issue: 17.01.2017
1.2	10.04.2017	857053-00003	Date of first issue: 24.08.2016

cytogenetic assay)
Species: Mouse
Application Route: Intraperitoneal injection
Method: OECD Test Guideline 474
Result: negative

Benzenesulfonic acid methyl-, mono C20-26 branched alkyl derivs., calcium salt:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative
Remarks: Based on data from similar materials

Benzenesulfonic acid, methyl-, mono-C20-24-branched alkyl derivs., calcium salts:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative
Remarks: Based on data from similar materials

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

Components:

Benzenesulfonic acid methyl-, mono C20-26 branched alkyl derivs., calcium salt:

Effects on fertility : Test Type: One-generation reproduction toxicity study
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 415
Result: negative

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Repeated dose toxicity

Components:

Phosphorodithioic acid, mixed O,O-bis(sec-Bu and 1,3-dimethylbutyl) esters, zinc salts:

Species: Rat
NOAEL: 125 mg/kg
Application Route: Ingestion
Exposure time: 28 Days

Aspiration toxicity

Not classified based on available information.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



ENGINE OIL TRIATHLON LONGLIFE SHPD 15W40 - 20 L

Version	Revision Date:	SDS Number:	Date of last issue: 17.01.2017
1.2	10.04.2017	857053-00003	Date of first issue: 24.08.2016

SECTION 12: Ecological information

12.1 Toxicity

Components:

Polyolefin-polyaminesuccinimide, polyol:

Ecotoxicology Assessment

Chronic aquatic toxicity : May cause long lasting harmful effects to aquatic life.

Phosphorodithioic acid, mixed O,O-bis(sec-Bu and 1,3-dimethylbutyl) esters, zinc salts:

Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): 4,4 mg/l
Exposure time: 96 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 203

Toxicity to daphnia and other : EL50 (Daphnia magna (Water flea)): 75 mg/l
aquatic invertebrates : Exposure time: 48 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 202

Toxicity to algae : EL50 (Desmodesmus subspicatus (green algae)): 410 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

Toxicity to microorganisms : EC50 (Pseudomonas putida): 380 mg/l
Exposure time: 16 h

Calcium alkaryl sulphonate, long chain:

Ecotoxicology Assessment

Chronic aquatic toxicity : May cause long lasting harmful effects to aquatic life.

Benzenesulfonic acid methyl-, mono C20-26 branched alkyl derivs., calcium salt:

Toxicity to fish : LL50 : > 100 mg/l
Exposure time: 96 h
Test substance: Water Accommodated Fraction
Remarks: Based on data from similar materials

Toxicity to daphnia and other : EL50 (Daphnia magna (Water flea)): > 100 mg/l
aquatic invertebrates : Exposure time: 48 h
Test substance: Water Accommodated Fraction
Remarks: Based on data from similar materials

Toxicity to algae : ErC50 (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l
Exposure time: 96 h
Test substance: Water Accommodated Fraction
Remarks: Based on data from similar materials

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



ENGINE OIL TRIATHLON LONGLIFE SHPD 15W40 - 20 L

Version	Revision Date:	SDS Number:	Date of last issue: 17.01.2017
1.2	10.04.2017	857053-00003	Date of first issue: 24.08.2016

NOEC (Pseudokirchneriella subcapitata (green algae)): 100 mg/l

Exposure time: 96 h

Test substance: Water Accommodated Fraction

Remarks: Based on data from similar materials

Toxicity to microorganisms : EC50 : > 10.000 mg/l
Exposure time: 3 h
Method: OECD Test Guideline 209
Remarks: Based on data from similar materials

Benzenesulfonic acid, methyl-, mono-C20-24-branched alkyl derivs., calcium salts:

Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l

Exposure time: 96 h

Test substance: Water Accommodated Fraction

Method: OECD Test Guideline 203

Remarks: Based on data from similar materials

Toxicity to daphnia and other : EL50 (Daphnia magna (Water flea)): > 1.000 mg/l

aquatic invertebrates

Exposure time: 48 h

Test substance: Water Accommodated Fraction

Remarks: Based on data from similar materials

Toxicity to algae : NOELR (Pseudokirchneriella subcapitata (microalgae)): 1.000

mg/l

Exposure time: 72 h

Test substance: Water Accommodated Fraction

Remarks: Based on data from similar materials

Toxicity to microorganisms : EC50 : > 10.000 mg/l

Exposure time: 3 h

Method: OECD Test Guideline 209

Remarks: Based on data from similar materials

12.2 Persistence and degradability

Components:

Phosphorodithioic acid, mixed O,O-bis(sec-Bu and 1,3-dimethylbutyl) esters, zinc salts:

Biodegradability : Result: Not readily biodegradable.

Biodegradation: < 5 %

Exposure time: 27 d

Method: Directive 67/548/EEC, Annex V, C.6

Benzenesulfonic acid methyl-, mono C20-26 branched alkyl derivs., calcium salt:

Biodegradability : Result: Not readily biodegradable.

Remarks: Based on data from similar materials

Benzenesulfonic acid, methyl-, mono-C20-24-branched alkyl derivs., calcium salts:

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



ENGINE OIL TRIATHLON LONGLIFE SHPD 15W40 - 20 L

Version	Revision Date:	SDS Number:	Date of last issue: 17.01.2017
1.2	10.04.2017	857053-00003	Date of first issue: 24.08.2016

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 8 %
Exposure time: 28 d
Method: OECD Test Guideline 301D
Remarks: Based on data from similar materials

12.3 Bioaccumulative potential

Components:

Phosphorodithioic acid, mixed O,O-bis(sec-Bu and 1,3-dimethylbutyl) esters, zinc salts:

Partition coefficient: n- : log Pow: 4
octanol/water

Benzenesulfonic acid methyl-, mono C20-26 branched alkyl derivs., calcium salt:

Partition coefficient: n- : log Pow: > 4
octanol/water Remarks: Expert judgement

Benzenesulfonic acid, methyl-, mono-C20-24-branched alkyl derivs., calcium salts:

Partition coefficient: n- : log Pow: > 5,47
octanol/water Remarks: Based on data from similar materials

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Not relevant

12.6 Other adverse effects

No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Dispose of in accordance with local regulations.
According to the European Waste Catalogue, Waste Codes
are not product specific, but application specific.
Waste codes should be assigned by the user, preferably in
discussion with the waste disposal authorities.

Contaminated packaging : Empty containers should be taken to an approved waste han-
dling site for recycling or disposal.
If not otherwise specified: Dispose of as unused product.

Waste Code : The following Waste Codes are only suggestions:

used product
130205, mineral-based non-chlorinated engine, gear and lu-
bricating oils

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



ENGINE OIL TRIATHLON LONGLIFE SHPD 15W40 - 20 L

Version	Revision Date:	SDS Number:	Date of last issue: 17.01.2017
1.2	10.04.2017	857053-00003	Date of first issue: 24.08.2016

unused product
130205, mineral-based non-chlorinated engine, gear and lubricating oils

uncleaned packagings
150110, packaging containing residues of or contaminated by dangerous substances

SECTION 14: Transport information

14.1 UN number

Not regulated as a dangerous good

14.2 UN proper shipping name

Not regulated as a dangerous good

14.3 Transport hazard class(es)

Not regulated as a dangerous good

14.4 Packing group

Not regulated as a dangerous good

14.5 Environmental hazards

Not regulated as a dangerous good

14.6 Special precautions for user

Not applicable

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Remarks : Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII) : Not applicable

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : Not applicable

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

Regulation (EC) No 850/2004 on persistent organic pollutants : Not applicable

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals : Not applicable

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



ENGINE OIL TRIATHLON LONGLIFE SHPD 15W40 - 20 L

Version	Revision Date:	SDS Number:	Date of last issue: 17.01.2017
1.2	10.04.2017	857053-00003	Date of first issue: 24.08.2016

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

		Quantity 1	Quantity 2
34	Petroleum products: (a) gasolines and naphthas, (b) kerosenes (including jet fuels), (c) gas oils (including diesel fuels, home heating oils and gas oil blending streams),(d) heavy fuel oils (e) alternative fuels serving the same purposes and with similar properties as regards flammability and environmental hazards as the products referred to in points (a) to (d)	2.500 t	25.000 t

Water contaminating class (Germany) : WGK 2 water endangering Classification according VwVwS, Annex 4.

Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control) Volatile organic compounds (VOC) content: 0 %

15.2 Chemical safety assessment

A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

Full text of H-Statements

H317 : May cause an allergic skin reaction.
H318 : Causes serious eye damage.
H411 : Toxic to aquatic life with long lasting effects.
H413 : May cause long lasting harmful effects to aquatic life.

Full text of other abbreviations

Aquatic Chronic : Chronic aquatic toxicity
Eye Dam. : Serious eye damage
Skin Sens. : Skin sensitisation

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx -

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



ENGINE OIL TRIATHLON LONGLIFE SHPD 15W40 - 20 L

Version	Revision Date:	SDS Number:	Date of last issue: 17.01.2017
1.2	10.04.2017	857053-00003	Date of first issue: 24.08.2016

Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Sources of key data used to compile the Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Classification of the mixture:

Eye Irrit. 2

H319

Classification procedure:

Calculation method

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

DE / EN