

## TRIATHLON® ENGINE OILS



Triathlon® Engine Oils are produced and packaged in compliance with the most stringent quality specifications according to DIN EN ISO 9001.

- High level of product safety.
- Broad manufacturer approvals.

With Triathlon® Oils, only high-quality first raffinates and raw materials are used.

- Fulfills the major specifications of automobile manufacturers.

Orange = fully synthetic

Purple = partly synthetic

Green = HC synthetic

Yellow = mineral

### For trucks

Designation	Area of use	Performance class/Approval	Contents	Art. No.	P. Qty.
<b>LOGLIFE 15W-40</b> Modern multi-use engine oil for high-performance diesel engines. Outstanding lubricating film stability under various operating conditions. Excellently suited for long oil-change intervals.	<b>MINERAL</b> Optimal for the most modern diesel engines with and without exhaust-gas turbocharging (EGT) and charge-air cooling (CAC). Especially well-suited for mixed vehicle fleets.	ACEA E7-04/B4-04/A3-04 API SL/CH-4/CF MAN M3275-1, MB Approval 228.3 Würth also recommends this product for vehicles which comply with the following specifications: Mack EO-M Plus, Renault RD-2, MTU type 2, KHD, Volvo VDS-2, Cummins 20076/20077	20 L	<b>0897 315 403</b>	1
			60 L	<b>0897 315 404</b>	1
			208 L	<b>0897 315 405</b>	1
<b>DYNAMIK 10W-40</b> Modern smooth-running engine oil for diesel engines. Fast oil supply at low temperatures. High shearing and aging stability. Suitable for long oil-change intervals.	<b>HC SYNTHETIC</b> Optimal for diesel engines with and without exhaust-gas turbocharging (EGT) and charge-air cooling (CAC). Especially suited for mixed vehicle fleets.	ACEA A3-02/A3-04/B3-02/B3-04/B4-04/E7-04/E5-02, API SL/CI-4 MAN M3275-1, MB Approval 228.3 Würth also recommends this product for vehicles which comply with the following specifications: MB 229.1, Volvo VDS-2/VDS-3, Global DHD-1, Mack EO-M Plus, MTU type 2, Renault RLD-2, Cummins 20076/20077/20078, Caterpillar ECF-2/ECF-1-a, Deutz DQC III-05	20 L	<b>0897 210 403</b>	1
			60 L	<b>0897 210 404</b>	1
			208 L	<b>0897 210 405</b>	1
<b>DIESEL 15W-40</b> Multi-use engine oil for year-round use. High shearing stability, prevents black sludge formation. Optimal lubrication.	<b>MINERAL</b> Optimal for diesel engines with and without exhaust-gas turbocharging (EGT) and charge-air cooling (CAC).	ACEA A2-96/B3-98/E2-96 #5 API SJ/CF-4/CF MAN 271, MB Approval 228.1 Würth also recommends this product for vehicles which comply with the following specifications: Volvo VDS, Allison C4, Caterpillar TO-2, MIL-L 2104 E, MIL-L 46152 D, MTU type 1	20 L	<b>0897 215 403</b>	1
			60 L	<b>0897 215 404</b>	1
			208 L	<b>0897 215 405</b>	1
<b>CARGO SUPER 5W-30</b> Year-round engine oil for diesel engines. Reduces fuel consumption and provides outstanding wear protection. Ensures good cold-starting behavior. Depending on the manufacturer's specifications, oil-change intervals of up to 120,000 km are possible.	<b>FULLY-SYNTHETIC</b> Optimally suited for exhaust gas-optimized diesel engines in commercial vehicles subject to extremely high loads. Specially matched to the exhaust regulations of the Euro II and Euro III emission standards.	ACEA E4-99 Issue 3/E7-04/E5-02 API CF Volvo VDS-3, MB Approval 228.5, MAN M3277, Scania LDF, DAF HP 1/HP 2, Renault RXD Würth also recommends this product for vehicles which comply with the following specifications: MTU type 3, Cummins 20077, MB 235.28	20 L	<b>0897 305 303</b>	1
			60 L	<b>0897 305 304</b>	1
			208 L	<b>0897 305 305</b>	1

Oil    Grease    Paste    Dry lubricant    Corrosion protection