

# WOOD FILLER



## Note on application:

Apply the wood filler paste to the areas to be filled with a stopping knife or similar tool. Depending on the crack or hole depth, the process must be repeated due to material shrinkage. If necessary, the wood filler paste can be diluted with acetone (Art. No. 0893 460).

## Applications:

For filling deep holes and cracks, e.g. knot holes, screw holes, parquet floors etc. of all solid woods and real wood veneers.

Colour	Fig.	Can: 250 g Art. No.	P. Qty.	Tube: 50 g Art. No.	P. Qty.
Natural		<b>0890 304 0</b>	1/6	<b>0890 304 00</b>	1/10
Oak, light		<b>0890 304 1</b>		<b>0890 304 10</b>	
Oak, medium		<b>0890 304 2</b>		<b>0890 304 20</b>	
Beech		<b>0890 304 7</b>		<b>0890 304 70</b>	

Please note that the colours shown may differ from the original tone for printing-related reasons.

## Technical data

Base	Nitrocellulose base
Density	approx. 1.0 g/cm <sup>3</sup>
Thermal stability	-20°C to +70°C
Processing temperature	at least +10°C
Hardening speed	depending on layer thickness, up to 60 min.
Shrinkage	approx. 30%
Shelf life	24 months (in unopened original container)

► Fast.

### Your advantage:

The pasty, easy-to-shape, fine-grained mass dries extremely quickly.

► Colour tones can be intermixed.

### Your advantage:

Better adjustment of colour tone to wood surface.

► Excellent finishing.

### Your advantage:

After drying completely, the wood filler can be sawed, sanded, nailed, stained, glazed, painted and polished like wood.

With this information we want to advise you to the best of our knowledge based on our tests and experience. However, we shall assume no liability for the application results in individual cases due to the large number of applications and the storage and application conditions which lie outside the scope of our influence. This also

applies to the use of the non-binding technical and commercial Customer Service we provide. We always recommend that you conduct your own tests. We guarantee the consistent quality of our products. We reserve the right to make technical changes and carry out further development.



**Clear Varnish  
(Anti-Fogging)  
Matt**

**Art. No. 0893 188 2**

**Silk Matt**

**Art. No. 0893 188 3**

**Touch-Up Box**

**Art. No. 0890 305 1**