

TRIATHLON® OILS

Orange = fully synthetic

Purple = partly synthetic

Green = HC synthetic

Yellow = mineral

Gear oils

Designation	Area of use	Performance class/Approval	Contents	Art. No.	P. Qty.
GEAR TRAX 75W-80 High-performance, high-pressure gear oil. Reduces running noises and provides outstanding protection against wear. Optimum lubrication, even with extremely long oil-change intervals.	HC SYNTHETIC Optimally suited for heavily loaded manual, auxiliary and transaxial transmissions requiring a lubricant according to API GL 3/4. For use in passenger cars and commercial vehicles.	API GL 3+ Würth also recommends this product for vehicles which comply with the following specifications: DAF, Iveco, Renault trucks, MAN 341 type E3/type Z3, ZF-TE-ML 02D, Volvo 97305, Eaton Extended Drain (300,000 km)	1 L	0897 475 801	1/6
			20 L	0897 475 803	1
			60 L	0897 475 804	1
			208 L	0897 475 805	1
GEAR CARGO 75W-90 Multi-use gear oil, suitable for lubrication of all drive elements, such as synchronized and non-synchronized manual transmissions and hypoid-toothed final drives. Reduces friction and saves fuel.	PARTLY-SYNTHETIC Multi-use gear oil for universal use in commercial vehicles.	API GL 4/GL 5/MT1 MIL-L-2105 D/MIL-PRF-2105 E Würth also recommends this product for vehicles which comply with the following specifications: ZF-TE-ML 12E, 16B, 17B, 19B; Volvo (axles), Scania STO 1:0, DAF, MAN M3343 type M, Eaton	1 L	0897 475 941	1/6
			20 L	0897 475 943	1
			60 L	0897 475 944	1
			208 L	0897 475 945	1
AUTOMATIC SUPER Gear oil for universal use with high thermal stability and excellent low-temperature properties. Outstanding wear and corrosion protection.	HC SYNTHETIC Optimally suited for steering gears, manual and automatic transmissions and for hydraulic systems and auxiliary drives. For use in passenger cars and commercial vehicles.	Dexron III H/III G/II E/II D, TASA, Allison C4, Caterpillar TO-2, Ford Mercon, ZF-TE-ML 04D/14A/17C, Voith H55.6335.xx, MAN 339 type V1/type Z1, MB Approval 236.1 Würth also recommends this product for vehicles which comply with the following specifications: ZF-TE-ML 02F/03D/09/11B/14B	1 L	0897 410 001	1/6
			20 L	0897 410 003	1
AUTOMATIC ULTRA High-performance gear oil for automatic transmissions. Outstanding wear protection, even with extended oil-change intervals. High thermal stability and excellent low-temperature properties.	HC SYNTHETIC Optimally suited for automatic transmissions, manual transmissions, steering systems, hydraulic systems and auxiliary drives, not only in passenger cars and commercial vehicles, but also in industrial applications.	GM Dexron IIIH, Mercon V, JASO 1-A, Toyota type T-II/T-IV, Allison C4, TES 295, Nissan Matic Fluid/D/J/K, Kia SP II/SP III, Mitsubishi SP II/SP III, Hyundai SP II/SP III, Mazda ATF M III/ATF M V, Honda ATF Z1 (except CVTs), Voith H 55.6335.xx Würth also recommends this product for vehicles which comply with the following specifications: JWS 3309, Chrysler ATF +3/+4, MB 236.1/236.2/236.5/236.6/236.7/236.9/236.10, Daimler NAG-1, BMW LT 71 141/LA 2634/7045 E/8072-B, MAN 339 type Z-2/type V-1, ZF TE-ML 02F/03D/04D/05L/09/11A/11B/14B/16L/17C, VW G 052 162/G 055 025, Volvo 97340 / 97341, Subaru ATF	1 L	0897 420 001	1/6
			20 L	0897 420 003	1

Hydraulic Oils

Product	Designation	Application	Approvals	Contents	Art. No.	P. Qty.	
HYDRAULIC OIL HLP 10	High-performance hydraulic oil which is compatible with all common sealing compounds as well as steel, non-ferrous and light metals. Offers optimum wear protection under heavy loads.	Especially well-suited for hydraulic systems with hydrostatic drives, hydraulic construction machines, excavators, elevators, industrial machines and machine tools, lifting platforms and presses.	DIN 51524 Part 2, ISO VG 10	60 L	0897 610 004	1/6	
HYDRAULIC OIL HLP 22				DIN 51524 Part 2, ISO VG 22	60 L	0897 622 004	1
HYDRAULIC OIL HLP 32			DIN 51524 Part 2, ISO VG 32		208 L	0897 622 005	1
				DIN 51524 Part 2, ISO VG 32	60 L	0897 632 004	1
HYDRAULIC OIL HLP 46			DIN 51524 Part 2, ISO VG 46		208 L	0897 632 005	1
				DIN 51524 Part 2, ISO VG 46	20 L	0897 646 003	1
					60 L	0897 646 004	1
HYDRAULIC OIL HLP 68			DIN 51524 Part 2, ISO VG 68	208 L	0897 646 005	1	
				DIN 51524 Part 2, ISO VG 68	20 L	0897 668 003	1
					60 L	0897 668 004	1
				208 L	0897 668 005	1	

Designation	Area of use	Performance class/Approval	Contents	Art. No.	P. Qty.
HYDRAULIC OIL SERVO AUTO High-performance central hydraulic oil for most demanding requirements. Outstanding wear and corrosion protection. Excellently suited for use in cold countries.	FULLY SYNTHETIC Suitable as central hydraulic oil in power steering, level adjustment, hydraulic brake servos and hydropneumatic suspensions. For use in passenger cars and commercial vehicles.	MAN M3289 Würth also recommends this product for vehicles which comply with the following specifications: MB 345.0, Ford WSS-M2C 204-A, ZF-TE-ML 02K, PENTOSIN CHF 11S. Or as an alternative for products with the following original spare parts No.: VW TL 52146 (G002 000/ G004 000), BMW 81 22 9 407 758, Opel 1940 766	1 L	0897 650 001	1/6