



Adhesive Trim Tape

High-strength double-sided adhesive tape with polyethylene carrier and acrylate adhesive.

▶ Very strong adhesion.

Your advantages:

- The tape provides outstanding adhesion immediately after installation of the trim. A high level of final adhesive strength is achieved after a curing time of 24 hours.
- Very strong adhesion also on rough and slightly uneven surfaces.

▶ Foam carrier.

Your advantage:

The tape has a vibration-damping effect and compensates for the expansion properties of two different materials.

▶ High temperature, UV and weather resistance.

Your advantages:

- The tape can be used indoors as well as outdoors.
- Does not lose adhesion at higher temperatures.

Width mm	Length m	Thickness mm	Art. No.	Pack Qty.
4	10	0.8	0894 910 4	1
12			0894 910	
19			0894 910 0	
24			0894 910 1	

Areas of application

- Trim and functional metal strips, logos, emblems, screens and holding brackets in the automobile industry.
- Attachment of name plates on machines.
- For attachment of spoilers in connection with mechanical elements.

Specifications

Adhesive base	acrylate adhesive
Carrier	Polyethylene (anthracite)
Adhesive strength	19 N / 25 mm
Elongation at rupture	> 300%
Application temperature	+5°C to +40°C (applies to surface and adhesive tape)
Temperature stability	-40°C to +95°C
Shelf life (at approx. +20°C and 50% humidity)	12 months
UV resistance	yes
Moisture resistance	yes

Instructions for use

- The surfaces to be joined must be dry and free from dust, grease and silicon.
- In order to assure perfect adhesion, sufficient pressure must be applied to the tape during installation.
- Optimal final adhesive strength is reached after 24 hours.
- In case of sensitive surface finishes (e.g. PP, PE, rubber) and porous surfaces (e.g. wood or stone), carry out a preliminary application test.
- In case of plastic materials to be joined containing plasticizer additives, these additives may change the adhesive layer and impair the strength of the adhesive (perform preliminary test).

These notes are intended to provide our advice to the best of our knowledge, based on tests and experience. However, we cannot assume any liability for processing results in individual cases due to the wide variety of applications as well as storage and processing conditions beyond our control. This also applies in case our technical and com-

mercial customer service is consulted free of charge and without obligation. We recommend carrying out individual tests. We guarantee the constant quality of our products. We reserve the right to make technical modifications and advanced developments.