



# Double-Sided Adhesive Tape

Adhesive tape with special paper carrier and acrylate adhesive.

- ▶ Very good adhesion.  
**Your advantage:**  
Due to its outstanding adhesive property, the tape is suitable for bonding a broad range of materials, e.g. wood, metal, plastic, glass, stone etc.
- ▶ Can be pulled off by hand.  
**Your advantage:**  
Fast, easy application of the tape.
- ▶ UV and moisture-resistant.  
**Your advantage:**  
The adhesive tape can be used both indoors and outdoors
- ▶ Resistant to ageing.  
**Your advantage:**  
When used properly, tape adhesion for many years is possible.

Width in mm	Length in m	Thickn. in mm	Art. No.	P. Qty.
12	25	0.13	<b>0894 500 4</b>	3

## Applications

For bonding wood, metals, plastics, paper, felt and cardboard in various areas, e.g.:

- Bonding sash bars in window construction sector.
- Bonding facade claddings.
- Fastening in lorry and caravan construction.
- Doublings in wood sector.
- Fastening cable holders and cable ducts.

## Technical data

Adhesive basis	Acrylate adhesive
Carrier	Special paper (transparent)
Adhesive strength	22 N / 25 mm
Elongation at tear	10%
Application temperature	+15°C to +30°C (applies to the surface and the adhesive tape)
Thermal stability	-30°C to +120°C
Shelf life (at approx. +20°C and 50% humidity)	12 months
UV resistance	given
Moisture resistance	given

## Notes on application

- The surfaces to be glued must be dry, and dust, grease and silicone-free.
- To ensure proper adhesion, the tape must be sufficiently pressed onto the material to be glued.
- Optimum final strength is achieved after 24 hours.
- With sensitive surfaces (e.g. PP, PE, rubber) and attachment surfaces (e.g. wood, stone), please carry out preliminary tests.
- In cases where plastics containing softener additives are to be adhered, the softener can modify the adhesive coating. This impairs the strength of the adhesive.

With this information we want to advise you to the best of our knowledge based on our tests and experience. However, we can assume no liability for the application results in individual cases due to the large number of applications and to the fact that storage and application conditions are beyond our influence. This also applies to

the use of the non-binding technical and commercial Customer Service we provide. We always recommend that you conduct your own tests. We guarantee the consistent quality of our products. We reserve the right to make technical changes and carry out further development.