

# Cable Ties with Metal and Plastic Tongue

- **Temperature stability:** –40°C to +85°C.
- **Material: Polyamide 6.6.**
- **Halogen and silicone free.**
- **For quick, problem-free and reliable bundling of cables, cable harnesses, hoses, etc.**

- Easy insertion of the cable tie into the eye due to the raised tip.
- Absolutely secure lock.
- Long service life.
- Particularly tough in cold weather, does not become brittle or porous at low temperatures.
- Resistant to oils, grease, fuels and many other organic materials. Caution in case of strongly mineral acids and/or oxidizing chemicals, especially at high temperatures.

- **Neutral:** for indoor use.
- **Black:** UV and weather stabilized. Due to carbon additive the effect of UV radiation on the material is slowed down.

## Areas of Application

- Switch cabinets
- Installation
- Automotive
- Automobile workshops
- Industrial workshops
- Elevator construction

## Cable Ties with Plastic Tongue

### Design:

- Plastic tongue.
- No sharp edges.
- High retaining strength.



Width mm	Length mm	Bundling Ø mm	Art. No. neutral	Art. No. black	Pack Qty.
2.5	100	1.6– 20	<b>0502 11</b>	<b>0502 111*</b>	100/1000
3.6	140	1.6– 30	<b>0502 12</b>	<b>0502 121*</b>	100/1000
3.5	200	1.6– 40	<b>0502 13</b>	<b>0502 131</b>	100/1000
3.6	280	1.6– 75	<b>0502 135</b>	<b>0502 135 1</b>	100/ 500
4.8	178	1.6– 40	<b>0502 14</b>	<b>0502 141*</b>	100/1000
4.8	280	1.6– 75	<b>0502 15</b>	<b>0502 151*</b>	100
4.8	360	1.6–100	<b>0502 16</b>	<b>0502 161*</b>	100
7.8	180	1.6– 40	<b>0502 17</b>	<b>0502 171</b>	100
7.8	360	1.6–100	<b>0502 18</b>	<b>0502 181</b>	100
7.8	540	25–150	<b>0502 19</b>	<b>0502 190 1</b>	100
7.8	750	40–220	<b>0502 181 31</b>	<b>0502 181 3</b>	100
12.5	720	48–220	<b>0502 201</b>	<b>0502 201 1</b>	50
12.5	1000	48–300	<b>0502 202</b>	<b>0502 202 2</b>	50

\* also available in Pack Qty. 300