

# PNEUMATIC NAIL GUN



Especially lightweight and handy nail gun for nails with a diameter of 1.2 mm, and a length of 15-54 mm. The machine is used on door moldings, wall elements, profile moldings, bandings, ornaments, decorative profiles, decorative moldings, door panels and baseboards.

## DSK 1555

Art. No. 0703 547 0

- Powerful, oil-free drive therefore maintenance-free.
- Empty magazine recognition.
- Toolless depth adjustment for protecting work surfaces.
- Dual-function switch for changing from single triggering to contact triggering.
- Toolless access for easy troubleshooting.
- Adjustable air ejection.
- Belt hook.
- Rubber nose piece for use on sensitive surfaces.
- Supplied in a case.
- 3-year warranty.

| Delivery scope              |              |         |
|-----------------------------|--------------|---------|
| Designation                 | Art. No.     | P. Qty. |
| DSK 1555 Pneumatic Nail Gun | 0703 547 0   | 1       |
| Empty Carrying Case         | 0955 703 547 | 1       |
| Safety Goggles              | -            | 1       |
| Offset Screwdrivers         | -            | 1       |
| Allen head 3 and 4 mm       | -            | 1       |
| Operating Instructions      | -            | 1       |

| Technical data          |                         |
|-------------------------|-------------------------|
| Nail dia.               | 1.2 mm                  |
| Nail length             | 15-54 mm                |
| Magazine capacity       | 105 nails               |
| Working pressure        | 4.8-8.3 bar             |
| Max. operating pressure | 8.3 bar                 |
| Air consumption         | approx. 1.13 l / impact |
| Minimum hose dia.       | 6 mm                    |
| Compressed-air supply   | 1/4"                    |
| Weight                  | 1.09 kg                 |
| Dimensions (L x W x H)  | 241 x 67 x 245 mm       |

| Suitable accessories                  |              |         |
|---------------------------------------|--------------|---------|
| Version                               | Art. No.     | P. Qty. |
| Plug-in nipple (brass) 1/4"           | 0699 211 4   | 1       |
| Plug-in nipple (steel) 1/4"           | 0699 211 41  | 1       |
| Quick-action coupling (brass) 6 mm    | 0699 126     | 1       |
| Quick-action coupling (steel) 6 mm    | 0699 126 1   | 3       |
| Quick-action coupling (safety) 6 mm   | 0699 152 6   | 1       |
| Small mist oiler 1/4"                 | 0699 070 314 | 1       |
| Compressed air service oil, 1 liter   | 0893 050 5   | 1       |
| Compressed air hose, inside dia. 6 mm | 0699 906 1   | 10 m    |

## Suitable compressed-head nails, Type WX and WY

- Version: Galvanized steel, blue passivated (A2K).

| Version                     | Dia. in mm | Length in mm | Art. No.    | P. Qty. |
|-----------------------------|------------|--------------|-------------|---------|
| Galvanized steel, Type WX   | 1.2        | 16           | 0480 12 16  | 5000    |
|                             | 1.2        | 19           | 0480 12 19  | 5000    |
|                             | 1.2        | 25           | 0480 12 25  | 5000    |
|                             | 1.2        | 30           | 0480 12 30  | 5000    |
|                             | 1.2        | 35           | 0480 12 35  | 5000    |
|                             | 1.2        | 38           | 0480 12 38  | 5000    |
|                             | 1.2        | 40           | 0480 12 40  | 5000    |
|                             | 1.2        | 45           | 0480 12 45  | 5000    |
|                             | 1.2        | 50           | 0480 12 50  | 5000    |
|                             | 1.2        | 54           | 0480 12 54  | 5000    |
| dark brown, Type WX, galv.  | -          | 35           | 0480 12 351 | 5000    |
| white, Type WX, galv.       | -          | 35           | 0480 12 353 | 5000    |
| light brown, Type WX, galv. | -          | 35           | 0480 12 354 | 5000    |
| small head, type WX, galv.  | 1.0        | 16           | 0480 13 16  | 5000    |
|                             | 1.0        | 19           | 0480 13 19  | 5000    |
|                             | 1.0        | 25           | 0480 13 25  | 5000    |
|                             | 1.0        | 32           | 0480 13 32  | 5000    |
|                             | 1.0        | 38           | 0480 13 38  | 5000    |

These versions can also be used in machines of the competition (see ccomparison list).

□ = bare ■ = galv. blue pass. ■ = galv. yellow pass. ■ = stainl. steel

## Suitable compressor K 290

Art. No. 0701 229

### Consumption example:

40 nails/min. x 1.13 l/nail gives an air consumption of 45 l/min. The K 290 compressor supplies 152 l/min., which means that there is sufficient reserve. Adjust operating pressure on pressure reducer!

