

PNEUMATIC STAPLER AND NAIL GUN



Scope of delivery		
Description	Art. No.	P./Qty.
Pneumatic Stapler and Nail Gun DKN 3065	0703 556 0	1
Protective goggles	-	1
Service oil	-	1
Offset screwdrivers Allen head 4 mm	-	1
Operating manual	-	1

Technical data	
Staple width and length	10.7 mm / 30-67 mm
Staple width and length	11.1 mm / 32-50 mm Δ
Staple width and length	11.2-11.7 mm / 32-67 mm
T nail dia. / length	2.2 mm / 32-64 mm
Headless tacks	2.5-2.7 mm / 44-64 mm
Magazine capacity	150 staples / 100 T nails
Working pressure	5-8 bar
Operating pressure	max. 8.0 bar
Air consumption	1.609 l
Minimum hose width	9 mm
Air connection	1/4"
Weight	2.9 kg

Δ staples not included in the range!

Matching Staples and Nails

- Type: Galvanized steel, blue passivated (A2K).

Type	Width in mm	Length in mm	Art. No.	P./Qty.
Staples Type WN, galv., resin-coated	10.7	30	0480 107 30	10,000
		35	0480 107 35	10,000
		40	0480 107 40	10,000
		45	0480 107 45	10,000
Staples Type W 155, galv., resin-coated	10.7	40	0480 107 140*	10,000
		50	0480 107 150*	10,000
		65	0480 107 165*	5,000
T-nails, smooth, bright	dia. 2.2	38	0481 22 38	10,000
		44	0481 22 44	10,000
		50	0481 22 50	10,000
		55	0481 22 55	10,000
		62	0481 22 62	10,000

* For gypsum plasterboard conforming to DIN 18182.

These types can also be used in competitors' machines (see comparison list).

□ = bare ■ = galv. blue pass. ■ = galv. yellow pass. ■ = stainless steel

Powerful combination unit for installing different fastening elements: Type WN staples, Type W155 staples and T-nails.

DKN 3065 Combination Art. No. 0703 556 0

Applications include pre-fabricated house construction, interior finishing, gypsum plasterboard, substructures, indoor house construction, joiner's work, woodworking, roofing and carpenter's shops.

- Dual-function switch for changing from single triggering to contact triggering
- Toolless depth adjustment
- Adjustable air ejection
- Toolless access for easy troubleshooting
- Magnesium housing, therefore light in weight for comfortable working
- 3-year warranty

Suitable Accessories		
Type	Art. No.	P./Qty.
Plug-in nipple (brass) 1/4"	0699 211 4	1
Plug-in nipple (steel) 1/4"	0699 100 614	1
Quick-action coupling (brass) 9 mm	0699 129	1
Quick-action coupling (steel) 9 mm	0699 100 108	3
Safety coupling 9 mm	0699 153 516	1
Small mist oiler 1/4"	0699 070 314	1
Pneumatic service oil 1 liter	0893 050 5	1
Pneumatic hose, 9 mm, 10 meters	0699 909 1	1



Suitable K 410 compressor Art. No. 0701 241

Consumption example:

40 nails/min. x 1.6 l/nails results in air consumption of 64 l/min. The compressor K 410 delivers 180 l/min. so that there is also sufficient reserve. Adjust the operating pressure on the pressure reducer!

- Type: Galvanized steel, blue passivated (A2K).

Type	Width in mm	Length in mm	Art. No.	P./Qty.
Staples Type Q, galv., resin-coated	11.3	40	0480 112 45	2,500
		50	0480 112 50	2,500
		56	0480 112 57	2,500
		63	0480 112 63	2,500
Staples Type QZ, galv., resin-coated	11.3	50	0480 112 150	2,500
		63	0480 112 163	2,500



Nylon Carrying Case with Carrying Strap Art. No. 0955 703 500