

PNEUMATIC IMPACT WRENCH



Reliable, compact impact wrench in a rugged, glass-fiber reinforced plastic housing, with high power and convenient equipment features.

Recommended maximum bolt size: M16.

DSS 1/2" X
Art. No. 0703 313 0

Excellent power-to-weight ratio for a 1/2" pneumatic tool.

Up to 816 Nm max. releasing torque with a weight of just 1.95 kg.

High-quality double impact mechanism and cylinder with 6-disk motor.

For reliable, high performance values and a long service life.

4-stage power setting with convenient clockwise-counterclockwise control.

Always optimum, user-friendly adjustment to respective application.

Ergonomic handle with professional trigger.

Excellent handling and optimum control.

Three-year warranty

on manufacturing or material defects.

Technical Data		
Model		DSS 1/2" X
Square drive		1/2"
Working torque*	Nm	68-600
Max. releasing torque	Nm	816
Avg. Operating pressure	bar	6.3
Weight	kg	1.95
Avg. air consumption	l/min.	125
Connection thread		1/4"
Minimum hose dia.	mm	8
Sound pressure level	dB (A)	90.8
Art. No.		0703 313 0
P. Qty.		1

* The operating torque is the torque usually achieved under average working conditions. It depends on the highly varying ambient conditions (air pressure, hose diameter, soiling, etc.).

Available in the fleet management system
ORSY®fleet.

Accessories		
Designation	Art. No.	P. Qty.
Plug-in nipple with R 1/4" male thread, made of nickel-plated steel	0699 100 614	3
Small mist oiler with 1/4" female thread	0699 070 314	1
Special oil for pneumatic tools (1l)	0893 050 5	1
Grease tube and grease syringe maintenance set	0709 213 052	1
Individual grease tube	0709 213 053	1
1/2"-power socket wrench sets	0714 13 ...	1

When the impact wrench is used regularly (e.g. for tire service), a little oil should be refilled daily and approx. two strokes of gear grease should be refilled monthly via the grease nipple.

