

PNEUMATIC NAIL GUN



Powerful, light pneumatic nail gun for half-head strip nails with 30-34° angle, in the diameters 2.9 - 3.3 mm, length 50 - 90 mm. Areas of use include pre-fabricated house construction, interior finishing, carpentry, rivet nailing, boxes, crates and roof laths.

**DSN 5090 34°
Art. No. 0703 543 0**

- Adjustable reloading magazine for various nail sizes
- Empty magazine recognition for a longer unit service life
- Toolless depth adjustment protects the working surface
- Dual-function switch for changing from single triggering to contact triggering
- Specially shaped trigger bites into the material and prevents the unit from slipping
- Air filter installed in the handle to protect against dust and dirt
- Adjustable air ejection
- Belt hook
- Magnesium housing, therefore light in weight for comfortable working
- Including nylon carrying case

Scope of delivery		
Designation	Art. No.	P./Qty.
Pneumatic nail gun DSN 5090 34°	0703 543 0	1
Nylon carrying case with carrying strap	0955 703 500	
Protective goggles	-	
Service oil	-	
Offset screwdriver, Allen head 5 mm	-	
Operating instructions	-	

Technical data	
Type/Model	DSN 5090 34°
Nail dia.	2.9-3.3 mm
Nail length	50-90 mm
Magazine capacity	88-98 nails
Operating pressure	4.8-8.3 bar
Max. operating pressure	8.3 bar
Air consumption	approx. 3.69 l / impact
Minimum hose dia.	9 mm
Compressed air supply	1/4"
Weight	3.76 kg
Dimensions (L x W x H)	476 x 114 x 362 mm

Suitable accessories		
Type	Art. No.	P./Qty.
Plug-in nipple (brass) 1/4"	0699 211 4	1
Plug-in nipple (steel) 1/4"	0699 211 41	
Quick-action coupling (brass) 9 mm	0699 129	
Quick-action coupling (steel) 9 mm	0699 129 1	3
Quick-action coupling (safety) 9 mm	0699 152 9	1
Small mist oiler 1/4"	0699 070 314	
Compressed air service oil, 1 liter	0893 050 5	10 m
Compressed air hose, inside dia. 9 mm	0699 909 1	

Suitable 34° round-head strip nails conforming to DIN 1052

- Design: Galvanized steel, yellow passivated (A2C).

Type	Dia. in mm	Length in mm	Art. No.	P./Qty.
smooth, bare, resin-coated	2.9	63	0482 329 63	6000
	2.9	75	0482 329 75	5400
	3.1	82	0482 331 82	4000
		90	0482 331 90	4200
	bare, grooved, resin-coated	2.9	75	0482 629 75
3.1		82	0482 631 82	4000
		90	0482 631 90	4200
galvanized, grooved, resin-coated	2.9	50	0482 729 50	5000
		63	0482 729 63	
		75	0482 729 75	
	3.1	90	0482 731 90	
galvanized steel, smooth, resin-coated	2.9	63	0482 429 63	6000
		75	0482 429 75	5400
	3.1	82	0482 431 82	4000
		90	0482 431 90	4200

These types can also be used in competitors' machines (see comparison list).



**Suitable K 400 compressor
Art. No. 0701 240**

Consumption example:

40 nails/min. x 3.69 l/nails results in air consumption of 147.6 l/min. The compressor K 400 delivers 180 l/min. so that there is also sufficient reserve. Adjust the operating pressure on the pressure reducer!

□ = bare ■ = galv. blue pass. ■ = galv. yellow pass. ■ = stainless steel