

SERIES 4000 PNEUMATIC FITTINGS



S 4000 Quick-Action Coupling



PU hose



S 4000 Plug-In Nipple

Fig.	Hose dia. in mm		Flow	Art. No.	P.Qty.
	Inside	Outdoors			
1	11.0	16.0	3,900	0699 410 111	3
2				0699 942 11.	1
3				0699 410 411	3
1	13.0	18.0		0699 410 118	3
2				0699 942 13.	1
3				0699 410 418	3

Features convenience connection for PU compressed-air hoses

High flow rate of up to 3,900 l/min and maximum operating pressure of 16 bar

Enables optimum output utilization of compressed-air consumers

Ergonomically designed locking bush

Ensures a secure grip and prevents slipping off

Tempered steel nipples and locking bushes

For max. load-bearing capacity and a long service life

Low coupling force enables one-handed operation

Only minimal force required for simple, fast, safe coupling and decoupling

Airtight connections

Low energy consumption and high level of efficiency

Exposed surfaces are chrome-plated, nickel-plated or galvanized

High corrosion resistance and protection, even under demanding conditions

Fittings comply with Eurostandard 10.4

Compatibility with other pneumatic fittings

SERIES 4000 PNEUMATIC FITTINGS



S 4000 AG Quick-Action Coupling



S 4000 AG Plug-In Nipple

Fig.	Connection (AG)	Flow in l/min.	Art. No.	P.Qty.
1	G 3/8"	3,900	0699 410 338	3
2			0699 410 638	
1	G 1/2"		0699 410 312	
2			0699 410 612	

With male thread

High flow rate of up to 3,900 l/min and maximum operating pressure of 16 bar

Enables optimum output utilization of compressed-air consumers

Ergonomically designed locking bush

Ensures a secure grip and prevents slipping off

Tempered steel nipples and locking bushes

For max. load-bearing capacity and a long service life

Low coupling force enables one-handed operation

Only minimal force required for simple, fast, safe coupling and decoupling

Airtight connections

Low energy consumption and high level of efficiency

Exposed surfaces are chrome-plated, nickel-plated or galvanized

High corrosion resistance and protection, even under demanding conditions

Fittings comply with Eurostandard 10.4

Compatibility with other pneumatic fittings