



# Paint-Spray Protection Mask

**CE 96.0194**

**Disposable mask with double filter FFA 1 according to EN 405**

- Gas-filtering half mask for use against organic gases and vapours up to 30 times their limit values.
- Safety on account of a comfortable sealing fit.
- Comfortable fit because of head bands.
- Good distribution of weight.
- Low breathing resistance.
- Tightly fitting filters resulting in good freedom of movement.
- Suitable for persons wearing glasses.
- On account of high charcoal content the disposable paint-spray mask can be used until the charcoal is used completely. Depending on the amount of contamination in the ambient air the mask can be used for several days. Please ensure that the mask is put back into the sealable bag when it is not in use (break, end of shift etc.). This can decisively extend the service life of the mask.
- The mask is completely burnable.

**Art. No. 0899 160**

Pack Qty.: 1

## Application Areas

Mainly for paint-spraying and when handling solvents (e.g. diluting agents such as butyraldehyde, Z-thoxyl ethyl acetate, or xylol; combined solvents such as turpentine oil, or CKW such as Tri).

## Please Note

Our examples for the application do not claim to be complete or correct. Constant research and test about pollutants and their effects on the human body are frequently subject to new assessment or new assignment with respect to AGW-value and therefore to the respective filter class.