

SH-4



- 4-point interior attachment.
- Straight helmet shell.

SH-6



- 6-point interior attachment.
- Downward extended helmet shell serves as neck protection.

SH-6 E



Safety Helmets

according to EN 397

- Optimum protection: The special net structure reinforces the shell at all critical points.
- Light weight for pleasing wearing comfort and maximum acceptance.
- Circumferential rain groove for directed water run-off.
- Ventilation holes for "good climate" under the helmet.
- 30-mm insert pockets for hearing protection.
- Long, circumferential sweatband made of especially absorbent fleece material.
- Attachment points for chin strap.
- Quick release closure for optimum adjustment to head size.
- Size: 52 – 62 cm.
- Additional qualification: approved as cold-weather helmet down to -30°C .

Designation	Interior attachments	Color	Art. No.	P. Qty.
SH-4	4 points	yellow	0899 200 75	1
SH-4	4 points	white	0899 200 76	
SH-6	6 points	yellow	0899 200 70	
SH-6	6 points	white	0899 200 71	

Electrician's Safety Helmet

according to EN 397

- Tested and approved as electrician's safety helmet up to 1,000 V AC.
- Closed helmet shell without ventilation openings.
- Signal color: fluorescent yellow.

Designation	Interior attachments	Color	Art. No.	P. Qty.
Electrician's Helmet	6 points	fluorescent yellow	0899 200 77	1