

ELECTRONIC HOT-AIR BLOWER



Handy, light unit with stepless temperature and air quantity adjustment. Additional LCD display with memory function.

HLG 2300 LCD
Art. No. 0702 203 0

Handy, light unit with stepless temperature adjustment.

HLG 2000
Art. No. 0702 202 0

Rugged ceramic heater.

Long service life,
low sensitivity to jolts.

Light and ergonomical.

Low fatigue even when working for longer periods.

3-year warranty.

During this period all manufacturing or material defects will be repaired free of charge.

**Only HLG 2300-LCD:
LCD display.**

Enables storage of frequently used settings. In addition, simple temperature and air quantity control is also possible.

Delivery Scope		
Designation	HLG 2000	HLG 2300-LCD
HLG 2000 Hot-Air Blower	1	-
HLG 2300-LCD Hot-Air Blower	-	1
Reducing nozzle, 9 mm dia.	1	1

Technical Data		
Designation	HLG 2000	HLG 2300-LCD
Voltage	230 V/ 50 Hz	
Protection class	IP / II	
Output	2,000 W	2,300 W
Temperature	50 - 600 °C	50 - 650 °C
Air flow	150, 300, 500 l/min.	150 - 500 l/min.
Cable length	4 m	
Weight	0.87 kg	0.95 kg



The temperature of the air stream can be controlled with the adjusting wheel.



The LCD display enables exact adjustment of the temperature and air quantity. In addition, four presettings are stored:

Level	Temperature °C*	Level	Temperature °C*
1	50	6	400
2	100	7	480
3	200	8	540
4	300	9	600
5	350	-	-

* Guide values

Program	Temperature °C	Air quantity l/min.	Use
1	250	350	Deforming plastic pipes
2	350	400	Heat-sealing plastic
3	450	500	Removing paint
4	550	400	Soft soldering

The values for the presettings can be changed as desired.