

CORE DRILL

Technical information for DS 130-P and DS 130-T



Unit elements

- 1 Additional handle (360° rotation)
- 2 Water regulation
- 3 Speed-selection switch for speed regulation
- 4 Bubble levels
- 5 Coated aluminum handle
- 6 LED motor load indicator
- 7 Water-flow indicator



The machine spindle has a combined tool mount with a common 1/2" inside thread and 1 1/4" outside thread.

Accessories

Image	Designation	Art. No.	P. Qty.
4	Second Handle Piece for DS 130-T	5709 112 010	1
5	Dry Drilling Set with dust extraction for DS 130-P/DS 130-T	5709 112 111	1
6	Industrial Wet and Dry Vacuum ISS 55-S Automatic	0701 156 0	1
7	Carriage for DS 130-P/DS 130-T	5709 111 112	1
8	DS COMPACT and DS COMFORT Drilling Stands for DS 130-P/DS 130-T	5709 14. 0	1
9	Diamond Wet Drilling Bits for DS core drills	545.	1
10	Water pressure tank for drilling work without a water connection at the construction site. Pressure gauge for tank pressure (max. 6 bar). Fill volume: 10 L, hose length: 2.5 m. Safety valve against overpressure and for relieving residual pressure. Large filling funnel	0651 150 205	1



Fig. 3



Fig. 4

Second Handle Piece for DS 130-T Dry drilling set with dust extraction

- Ideal for vertical drilling
- Enables working in back-saving body positions
- Enables dust-free drilling
- The dry drilling set connected in front prevents the penetration of drilling dust into the machine interior



Fig. 5



Fig. 6



Fig. 7

Carriage for DS 130-P/DS 130-T

For machine mounting in conjunction with drilling stands DS COMPACT and DS COMFORT



Fig. 8



Fig. 9



Fig. 10