DRILLING STANDS

Delivery scope					
Fig.	**Designation**	**DS COMPACT Art. No. 5709 141 0**	**DS COMFORT Art. No. 5709 142 0**	**DS COMFORT XL Art. No. 5709 143 0**	**P. Qty.**
1	DS COMPACT Drilling Stands	**5709 141 X**	-	-	1
2	DS COMFORT Drilling Stands	-	**5709 142 X**	-	1
3	DS COMFORT XL Drilling Stands			**5709 143 X**	1
4	Mounting Set M12 for the anchoring of the DS drilling stands in conjunction with W-ED Drive-In Anchor Art. No. 0904 010 126 and Spreader Tool Art. No. 0904 020 12 (please order both separately)	**5709 151 100**			1

Technical data			
Type (compatible with)	**DS COMPACT**	**DS COMFORT**	**DS COMFORT XL**
DS 130-P/DS 130-T	•	•	•
DS 164	•	•	•
DS 300	-	•	•
Column height	760 mm	920 mm	1,420 mm
Weight	10.3 kg	13.9 kg	17.0 kg

Compact and convenient drilling stands for DS 130-P/DS 130-T, DS 164 and DS 300 Diamond Core Drills.

DS COMPACT
Art. No. 5709 141 0

DS COMFORT
Art. No. 5709 142 0

DS COMFORT XL
Art. No. 5709 143 0

Aluminum column with carry handle and two solid rubber wheels on a stainless-steel axle for easier tipping of the drilling stand (DS COMFORT only).
Easy and comfortable to transport.

Engraved drilling depth and angle indicator and drilling center indicator made of stainless steel.
All indicators are resistant to humidity and dirt.

Column features dovetail guide.
Stable hold and precise guidance of the drilling carriage.

Knurled set screws with additional hexagon head.
Operated manually or with drill spindle/ tool.

Drill spindle with quick-change connection; mountable on either side of carriage; features integrated wrench for the knurled set screws.
Equally suitable for right- and left-handed people. Drill spindle or tool is always at hand.

Available in the fleet management system ORSY®fleet.

KR - 06/13 - 15181 - ©