

## LONGLIFE CUTOFF WHEELS

- Synthetic resin-bonded, fibrous material-reinforced high-performance cutoff wheels
- For free-hand cutting with electric or pneumatic angle grinders
- Extremely low susceptibility to breakage
- Minimal dimension and imbalance tolerances
- Max. circumferential speed 80 m/s
- Comply with the most demanding safety requirements of European standard **EN 12413** and the **OSA** (Organization for Safety of Grinding Tools)
- Extremely long service life
- Optimum cutting capacity in solid and profile materials
- Very high lateral stability

### Blue for steel

#### Applications

Cutting solid materials, thick-walled pipes, profiles, metal sheets etc.

Dia. x thickn. in mm	Hole in mm	Version	Max. rpm	Art. No.	P. Qty.
115 x 2.5	22.23		13,300	<b>0670 101 152</b>	25
125 x 2.5	22.23		12,200	<b>0670 101 252</b>	25
180 x 2,5	22.23		8,500	<b>0670 101 802</b>	25
230 x 2.5	22.23		6,600	<b>0670 102 302</b>	25
300 x 3.5	20.00		5,100	<b>0670 103 023</b>	10
350 x 4.0*	20.00		5,400	<b>0670 103 524</b>	10

\*Max. working speed: **100 m/s** (For use on gasoline and electric cutting machines)



### Yellow for aluminum

#### Applications

Cutting sprues, solid materials, pipes, profiles, sheet metal etc.

Dia. x thickn. in mm	Hole in mm	Version	Max. rpm	Art. No.	P. Qty.
115 x 2,5	22.23		13,300	<b>0670 121 152</b>	25
125 x 2.5	22.23		12,200	<b>0670 121 252</b>	25
180 x 2.5	22.23		8,500	<b>0670 121 802</b>	25
230 x 2.5	22.23		6,600	<b>0670 122 302</b>	25



#### Application examples

