

SANDING BELTS FOR TUBE BELT SANDER



Abrasives: Ceramic grain
 Color: Green
 Bonding: Phenol resin with high percentage of active filler
 Backing: Y-polyester (P40-80), X-polyester (P120)
 Connection: Green film (P40), blue film (P60-120)
 Granularity: P40 - P120

ZEBRA® Ceramic Grain Fabric Sanding Belts

Applications:

Sanding of pipes, pipe elbows and closed pipe structures, sanding welding seams, removing tempering color, removing rust and scale.

Design: Ceramic grain

Special micro-fragmentation

Your advantages: Considerably more sharp grinding edges, resulting in an extremely high material removal without high grinding pressure, finer and more uniform surface quality, up to 4x longer service life compared to zirconium-corundum.

Sanding-active additives

Your advantages: Very cool grinding, no material discoloration.

Materials to be machined:

Stainless steel, rust, acid and heat-resistant steel (high-alloyed), e.g. Inconel®, steel and non-ferrous materials.

* Brand name of Special Metals Corporation

Dimensions in mm	Granularity 40 Art No.	Granularity 60 Art No.	Granularity 80 Art No.	Granularity 120 Art No.	P. Qty.	Suitable for machine
20 x 760	0673 400 004	0673 400 006	0673 400 008	0673 400 012	10	FLEX LRP 1503 VRA
20 x 820	0673 401 004	0673 401 006	0673 401 008	0673 401 012	10	FEIN RS 12-70
30 x 533	0673 402 004	0673 402 006	0673 402 008	0673 402 012	10	RÜGGERBERG UBS 5/70 Si-R SUHNER UTC 7-R
30 x 610	0673 403 004	0673 403 006	0673 403 008	0673 403 012	10	RÜGGERBERG UBS 11/90 Si-R SUHNER UTG 9-R
40 x 618	0673 404 004	0673 404 006	0673 404 008	0673 404 012	10	FLEX LBR 1506 VRA
40 x 675	0673 405 004	0673 405 006	0673 405 008	0673 405 012	10	CIBO FiniTube
40 x 760	0673 406 004	0673 406 006	0673 406 008	0673 406 012	10	FLEX LRP 1503 VRA
40 x 820	0673 407 004	0673 407 006	0673 407 008	0673 407 012	10	FEIN RS 12-70 POLY-ROMY Poly-Romy/1
35 x 650	0673 408 004	0673 408 006	0673 408 008	0673 408 012	10	Würth RBS 650
15 x 650	-	-	0673 409 008	0673 409 012	10	Würth RBS 650