

COARSE CLEANING ABRASIVE FLEECE, PURPLE



For cleaning weld seams, removing tempering colour, scale, rust, corrosion and coatings.

Reinforced fleece structure

- Extremely high edge strength.
- Optimum service life for all applications.
→ Saves costs thanks to minimal set-up and auxiliary process times.

Open, flexible fleece structure

- Does not clog; adjusts excellently to the workpiece.
→ Optimum contact with the surface
→ No change of the workpiece geometry.

Nylon fibre fleece

- Free of corrosive metals.
→ Metallically pure surfaces.



Nylon abrasive fleece disc, purple with replaceable clamping mandrel

- For use in BM13-XE drills, art. no. 0702 321 0, straight grinders GS 600-E, art. no. 0702 500 and flexible shafts.
- Only for use with suitable clamping mandrels and support flanges.

Caution: Flange diameter ≥ half of disc diameter!

Materials to be processed:

For universal use on virtually all materials.
Especially for stainless steel, steel, non-ferrous metals, coatings and plastics.

Clamping mandrels

for 1 or 2 nylon abrasive fleece discs.

Diameter x width mm	max. rpm	recom. rpm	Art. no.	PU/Qty.
100 x 13	6000	4500-5500	0585 330 100	10
150 x 13	4000	2700-3500	0585 330 150	5

Design	Overall length in mm	Art. no.	PU Qty.
6-mm shank, for disc 0585 330 100	52	0585 110 01	1
8-mm shank, for disc 0585 330 150	70	0585 115 01	1

Nylon abrasive fleece disc, purple with permanently integrated clamping mandrel

- For use in BM13-XE drills, art. no. 0702 311 0, straight grinders GS 600-E, art. no. 0702 500 and flexible shafts.

Materials to be processed:

For universal use on virtually all materials.
Especially for stainless steel, steel, non-ferrous metals, coatings and plastics.



Diameter x width mm	max. rpm	rec. rpm	Art. no.	PU/Qty.
100 x 13 x 6	8000	5500-7000	0585 331 100	5

Nylon abrasive fleece disc, purple with cloth plate

- For direct use on speed-controlled angle grinders, art. no. 0702 473 2.

Materials to be processed:

For universal use on virtually all materials.
Especially for stainless steel, steel, non-ferrous metals, coatings and plastics.

Application:

- Cleaning welding seams, metal surfaces and plastics.
- Removing tempering colour, scale, rust, corrosion, dirt and oxide layers, coatings, paints, old brushed-on coatings, synthetic resins, adhesives, jointing residues, cement and concrete residues.
- Light deburring work.
- Cleaning vehicle underbodies and various other work in car body construction.



Dia. mm	max. rpm	recom. rpm	Art. no.	PU/Qty.
115	11,000	5000-7000	0585 332 115	10

Additional products:



EWS 125-ES
Fixtec
Art. no. 0702 473 2



Drill driver
BM 13-XE
Art. no. 0702 321 0



Straight grinder
GS 600-E
Art. no. 0702 500