



ORSY 10 Nylon Abrasive Fleece Reel System

Art. No. 0585 805

Pack Qty. 1

Supplied with

Grain	Art. No.	Reel length m	Pack Qty.
P 180	0585 805 180	5	1
P 280	0585 805 280		
P 1000	0585 805 600		

Areas of application

Fine A, grain 180

- Pretreatment for painting galvanised steel.
- Roughening and cleaning of aluminium truck bodies (platform gates, box and tank bodies).
- Soiled areas containing oil must also be degreased.

Very Fine A, grain 280

- For cleaning, grease removal and roughening.
- Stripe matting (decorative finish) of nonferrous metals, stainless steel etc.
- Polishing copper, drawn skin and brazed joints.

Silicium carbide Ultra Fine S, grain 1000

- Polishing reaction primers and primer fillers as well as two-component filler primers.
- Touch up paintwork: roughening of surfaces adjacent to repair points for keying of mist edge and for perfect blending (in particular for two-coat metallic paintwork).
- Repair of defects in surface coat, e.g. orange peel effect etc.
- Roughening of interspaces when painting decorative stripes.
- Removal of overspray occurring during paintwork.
- Roughening of thermo plastics.
- Fine polishing of glass fibre reinforced plastic parts.

Large Dispenser, Empty

Art. No. 0956 109 0

Pack Qty. 1

Large Stars

Ø 75 / 250 mm

Art. No. 0956 109 02

Pack Qty. 1

Grain	Roll length m	Roll width			P. Qty.
		35 mm Art. No.	70 mm Art. No.	115 mm Art. No.	
P 100	5	0585 835 100	0585 870 100	0585 805 100	1
P 180		0585 835 180	0585 870 180	0585 805 180	
P 280		–	–	0585 805 280	
P 1000		0585 835 600	0585 870 600	0585 805 600	

Nylon Abrasive Fleece