

JOINT CUTTER



Delivery scope		
Designation	Art. No.	P. Qty.
FF 180-2 Joint Cutter	0702 911 X	1
Plastic Case	0955 702 911	1
Diamond Cutoff Wheel, 180 mm dia.	0666 100 180	1

Technical data	
Power consumption	1,200 W
Power output	750 W
Speed	7,000 rpm
Diamond Cutoff Wheel,	180 mm dia.
Weight	4.1 kg
Cable with plug	4 m
Cutting depth	0 - 50 mm
Noise level	97.5 dB (A)
Sound pressure level	86.5 dB (A)

Accessories		
Designation	Art. No.	P. Qty.
Saber Saw SBS1300-VES	0702 695 1	1
Multi-Cutter EMS 2.0	0702 698 1	1
ISS 35-S automatic Industrial Vacuum Cleaner	0701 138 0	1
ZEBRA® Diamond Cutoff Wheel, 180 mm	0666 100 180	1
Vacuum Adapter	0702 400 042	1
Encapsulated Ear Protection	0899 300 210	1
Safety Gloves	0899 400 ...	1



The large diamond cutoff wheel effortlessly separates tiles, plaster and metal anchors.



Old windows are separated from the reveal with a single cut and almost no dust. Fast, precise and requires very little expenditure of force.

Extremely rugged and powerful cutter for the removal of old windows. Thanks to its high-quality diamond cutoff wheel, this cutter effortlessly separates plaster, cement, tiles, masonry and metal anchors with a single, clean and powerful cut – causes next to no damage and almost no dust. Supplied in a case with a ZEBRA® Diamond Cutoff Wheel, 180 mm dia.

FF 180-2
Art. No. **0702 911 1**

Electronic overload protection.

Protects the motor, which guarantees a long service life under all usage conditions.

Windows are separated from reveals with a single cut.

No turn-out or ragged edges. Trouble-free insertion of the new window without repair work.

Precise depth stop.

The cut depth can be set precisely.

Especially low, closed and rugged vacuum housing.

Enables angling of the machine, so the cut can also be located directly above the window frame.

Elastic motor bearing.

Low-vibration motor makes working easier.

Easy to handle with minimal expenditure of force.

Reliable guidance thanks to sturdy additional handle and ergonomic and light design.

3-year warranty.

During this period, any manufacturing or material defects will be repaired free of charge.

Available in the fleet management system
ORSY®fleet.

ATTENTION: For optimum work results, always work with a vacuum cleaner. Use only special Diamond Cutoff Wheel Art. No. 0666 100 180!



The joint cutter can be guided diagonally while cutting so that the cut line is directly above the old window frame. Otherwise, the distance from the old window frame is 7 - 8 mm. Ideal for the frames of today's insulated glass windows.