

MULTI-TESTER PRO II LCD TWO-POLE VOLTAGE TESTER



AC voltage test



DC voltage test



Light function



For use in electrical installation and service work, measurements on hybrid and electric vehicles and on photovoltaic systems thanks to overvoltage category CAT IV 1000 V.

Testing equipment of the highest safety category (CAT IV 1000 V)

No presetting, intuitive operation

Automatic selection of measuring range

Voltages can also be displayed without a battery

When operated with batteries, a visual, audible and vibrating warning is given at and above 35V AC/DC

FI/RCD test using two buttons

Connectable load using a button allows the desired tripping of the residual current-operated circuit breaker so that the protective conductor can also be measured.

Screw-on 4 mm test tip adapter

- Improved hold in the safety socket and CEE socket
- Suitable for narrow test openings

Energy-saving

Automatic switch-off mechanism

Art. No.	0715 53 175
Display	visual, LCD display
Operating field	Light, Data-Hold and FI/RCD button
Measuring ranges	Automatic selection of measuring range
Voltage range	3 - 1,000 V AC TRMS 4 - 1,400 V DC with polarity indicator
Conductivity testing	0 - 50 Ohm with audible signal
Phase indicator	> 100 V AC
Switchable load	30 mA at 230 V AC
Diode test	Yes
Polarity	Yes (- in the LCD)
PELV indicator	Visual, audible and vibrating indicator
Resistance measurement	1 - 1,999 Ohm
Frequency measurement	0 - 1,000 Hz
Data-Hold	Yes (voltage and resistance)
Voltage supply	2 x 1.5 AAA included
Overvoltage category	CAT IV 1000 V
Dimensions (L x W x D)	300 x 75 x 20 mm
IEC protection rating	IP 65
Standard	EN 61243-3:2010
Weight	290 grams

Scope of delivery:

Includes two AAA alkaline batteries
HIGH POWER (Art. No. 0827 111)

Note:

Test without finger contact allows full protective clothing to be worn.

Additional items:

Alkaline Battery High Power
Art. No. 0827 111

Standby Bag
Art. No. 0715 53 308