

# MULTI-TESTER PRO II LCD TWO-POLE VOLTAGE TESTER



Voltage test



Voltage test with earthing contact socket



Voltage test with CEE socket

**For use in electrical installation and service work, measurements on hybrid and electric vehicles and on photovoltaic systems thanks to overvoltage category CAT IV 1000 V.**

**Testing equipment of the highest safety category (CAT IV 1000 V)**

**No presetting, intuitive operation**

Automatic selection of measuring range

**Voltages can also be displayed without a battery**

When operated with batteries, a visual, audible and vibrating warning is given at and above 35 V AC/DC

**FI/RCD test using two buttons**

Connectable load using a button allows the desired tripping of the residual current-operated circuit breaker so that the protective conductor can also be measured.

**Screw-on 4 mm test tip adapter**

- Improved hold in the safety socket and CEE socket
- Suitable for narrow test openings

**Energy-saving**

Automatic switch-off mechanism

Art. No.	0715 53 165
Display	Visual, LEDs
Operating field	Light, FI/RCD button
Measuring ranges	Automatic selection of measuring range
Voltage range	6 - 1,000 V AC 6 - 1,400 V DC with polarity indicator
Conductivity testing	0 - 50 kOhm (visual/audible)
Phase indicator	> 100 V AC
Switchable load	30 mA at 230 V AC
Diode test	Yes
Polarity	Yes (+, - LED)
PELV indicator	Visual, audible and vibrating indicator
Voltage supply	2 x 1.5 AAA included
Overvoltage category	CAT IV 1000 V
Dimensions (L x W x D)	300 x 75 x 20 mm
IEC protection rating	IP 65
Standard	EN 61243-3:2010
Weight	290 g

## Scope of delivery:

Includes two AAA alkaline batteries  
HIGH POWER (Art. No. 0827 111)

## Note:

Test without finger contact allows full protective clothing to be worn.

## Additional items:

**Alkaline Battery High Power**  
Art. No. 0827 111  
**Standby Bag**  
Art. No. 0715 53 308