

## Standard Welding Pistol with Trigger Button

Suitable for PinPuller® Spot when using:  
 Copper Electrode, Art. No. 0691 500 178  
 Corrugated Wire Electrode, Art. No. 0691 500 148  
 Carbon Electrode, Art. No. 0691 500 282  
 Control current connection with XLR plug



Welding current connection socket dia. in mm	Cable length in m	Clamping diameter for tools in mm	Art. No.	
13	2	10 and 16	<b>0691 500 291</b>	1

## Grounding Cable with Copper Shoe

Suitable for PinPuller® Spot  
 For ground connection on body parts



Welding current connection socket dia. in mm	Cable length in m	Art. No.	
13	1.6	<b>0691 500 292</b>	1

## Magnetic Ground

- Suitable for Grounding Cable Art. No. 0691 500 292, with clamping slit and clamping screw. Enables changing of mounting of magnetic ground on gripper within seconds.
- Rubber sleeve keeps steel chips away from magnet.



Total dia. in mm	Height in mm	Slit width in mm	Magnetic holding force in kg	Art. No.	
95	70	12	17	<b>0691 500 293</b>	1

## Dent Removal Slide Hammer

- Suitable for Welding Pistol Art. No. 0691 500 291 or for mounts with 10 and 16 mm dia.
- For quick dent removal on bodies, ideal in conjunction with the PinPuller® Spot.



Total length in mm	Total weight in kg	Clamping diameter in mm	Art. No.	
400	2	10 and 16	<b>0691 500 288</b>	1
Spare Lunette Eye			<b>0691 500 281</b>	20