

## DME 75 PNEUMATIC MINI ECCENTRIC GRINDER



**Art. No. 0703 236 0**

P. Qty. 1

### Ergonomic, rubber-coated handle

Comfortable and slip-resistant.

### Light, compact design

Fatigue-free working and excellently suited for tight spaces.

### With speed control

Optimum adjustment to the application.

### Sound-dampened air outlet at the end of the handle

No air outlet in the working area.

### Large-sized and comfortable adjustment valve

Optimized operating convenience.

### 3-year guarantee

on manufacturing and material defects.

Available in the fleet management system ORSY®fleet.

Delivery Scope			
Designation	Delivery Scope	Art. No.	P. Qty.
DME 75 Pneumatic MINI Eccentric Grinder	1	<b>0703 236 X</b>	1
Adhesive Plate dia. 75 mm (Velcro)	1	<b>0586 585 075</b>	1
Combination Open-Ended Wrench 14/19 mm	1	<b>0709 234 028</b>	1

Technical Data	
Type	DME 75
Clamping sleeve female thread	M6
Speed in r.p.m.	15,000
Stroke in mm	4
Weight in kg	0.7
Operating pressure (bar)	6.3
Av. air consumption in l/min.	113
Power in W	224
Connection thread	1/4"
Minimum hose dia. in mm	8

Accessories		
Designation	Art. No.	P. Qty.
Plug-in nipple with R 1/4" male thread made of nickel-plated steel	<b>0699 100 614</b>	3
Pneumatic couplings	<b>0699 1...</b>	
Pneumatic rotary joints 1/4"	<b>0699 2...</b>	
Pneumatic hoses	<b>0699 9...</b>	1
Small mist oiler	<b>0699 070 314</b>	
Special oil for pneumatic tools (1 l)	<b>0893 050 5</b>	
Pressure reducing valve 6 bar, 1/4" male and female thread, made of nickel-plated brass	<b>0699 003 60</b>	
Adhesive Plate dia. 50 mm (Velcro)	<b>0586 585 050</b>	
Headlight preparation set with DME 75	<b>0964 893 160</b>	

When used regularly, the machine should be lightly oiled via the compressed-air supply every day. The use of a mist oiler is recommended.