

LONG 7-PC. SCREW EXTRACTOR SET

Art. No. 0714 131 200



Problem solver for stripped Allen and Torx screw heads; compact range of the most common sizes. Can often be used for similar drives as well.

Features:

- Precisely manufactured conical spiral profile
- $\frac{3}{8}$ " square drive up to size 10 mm
- $\frac{1}{2}$ " square drive for 12 and 14 mm
- Spreading effect limited by collar
- Supplied in metal box with high-quality foam insert with clamping effect

Ideal for deep-set screws

Thanks to the longer design

Saves lots of time

There's no need for drilling out or welding on

Easy loosening of stripped Allen and Torx bolt heads

Thanks to conical spiral profile

Delivery scope			
Designation	Length	Art. No.	P. Qty.
$\frac{3}{8}$ " Long Internal Extractor, 3 mm	60 mm	0714 131 203	1
$\frac{3}{8}$ " Long Internal Extractor, 4 mm		0714 131 204	
$\frac{3}{8}$ " Long Internal Extractor, 6 mm		0714 131 206	
$\frac{3}{8}$ " Long Internal Extractor, 8 mm		0714 131 208	
$\frac{3}{8}$ " Long Internal Extractor, 10 mm		0714 131 210	
$\frac{1}{2}$ " Long Internal Extractor, 12 mm	78 mm	0714 131 212	
$\frac{1}{2}$ " Long Internal Extractor, 14 mm		0714 131 214	
Metal Box, size 1	220 x 110 x 35 mm	0955 715 1	
Foam Insert	215 x 105 x 30 mm	0955 131 200	

Notes on use:

Select the appropriate extractor and screw it into the screw with $\frac{3}{8}$ " or $\frac{1}{2}$ " ratchet. Thanks to its aggressive conical spiral shape, the extractor grips securely into the material of the screw, allowing it to be securely unscrewed.

Also ideal for unscrewing torn-off bolts and screws. Tap torn-off bolt or screw. Drill up to a half millimeter larger with dias. up to 6 mm. Drill up to one millimeter larger with dias. of 8 - 14 mm. Select the corresponding extractor, screw it into the drilled hole and then unscrew the screw or bolt.

Application:

