



# ASSY® BELTED SCREWS

## ASSY®

		ASSY®mat 50	ASSY®mat 50s	ASSY®mat 80	ASSY®mat 80 w/ adapter set	ASSY® 3.0		ASSY® 3.0		P. Qty.
Construction Approval						with approval				
Thread		M5	M5	M6	M5	Partial thread		Full thread		
Dia. in mm	Length in mm					Art. No. galvanized yellow	lg in mm	Art. No. galvanized yellow	lg in mm	
3.9	25	-	x	-	-	-		-		1000
	35	-	x	-	-	-		-		
	45	-	x	-	-	-		-		
4	25	x	-	-	x	<b>0163 740 025</b>	18	-		
	30	x	-	-	x	<b>0163 740 030</b>	18	-		
	35	x	-	-	x	<b>0163 740 035</b>	21	-		
	40	x	-	-	x	<b>0163 740 040</b>	24	-		
4.5	45	x	-	-	x	<b>0163 740 045</b>	29	<b>0163 940 045</b>	39	
	40	-	-	-	x	<b>0163 745 040</b>	26	-		
	50	-	-	x	-	<b>0163 745 050</b>	28	<b>0163 945 050</b>	43	
5	60	-	-	x	-	<b>0163 745 060</b>	33	<b>0163 945 060</b>	50	
	60	-	-	x	-	<b>0163 750 060</b>	37	-		
5	70	-	-	x	-	<b>0163 750 070</b>	42	<b>0163 950 070</b>	62	
	80	-	-	x	-	<b>0163 750 080</b>	42	<b>0163 950 080</b>	72	

		ASSY®mat 50	ASSY®mat 50s	ASSY®mat 80	ASSY®mat 80 w/adapter set	ECOFAST®	High-Speed Construction Screws		P. Qty.
Construction Approval						Without permit			
Thread		M5	M5	M6	M5	Partial thread	Partial thread (double)	Partial thread (coarse)	
Dia. in mm	Length in mm					Art. No. galvanized yellow	Art. No. phosphated	Art. No. phosphated	
3.9	25	-	x	-	-	-	<b>0179 239 25</b>	<b>0179 439 25</b>	1000
	35	-	x	-	-	-	<b>0179 239 35</b>	<b>0179 439 35</b>	
	45	-	x	-	-	-	<b>0179 239 45</b>	<b>0179 439 45</b>	
4	25	x	-	-	x	-	-	-	
	30	x	-	-	x	-	-	-	
	35	x	-	-	x	<b>0173 34 35</b>	-	-	
	40	x	-	-	x	<b>0173 34 40</b>	-	-	
4.5	45	x	-	-	x	<b>0173 34 45</b>	-	-	
	40	-	-	-	x	-	-	-	
	50	-	-	x	-	-	-	-	
5	60	-	-	x	-	<b>0173 345 60</b>	-	-	
	60	-	-	x	-	-	-	-	
5	70	-	-	x	-	-	-	-	
	80	-	-	x	-	-	-	-	

**ASSY® 3.0** 4.0-4.5 mm dia. **ASSY® 3.0** 5.0-12.0 mm dia.



With general construction permit

With general construction permit



ETA-11/0190

Drive	M5 thread Length 45 mm	M6 thread Length 45 mm	P. Qty.
PH2	<b>0614 176 679</b>	-	5
PZ2	<b>0614 176 677</b>	<b>0614 176 687</b>	
AW20	<b>0614 542 0</b>	<b>0614 622 0</b>	

**ASSY® 3.0** particle board screws are optimized for use in wooden materials. When used in plastic anchors, a reduction of the load-bearing capacity is possible. For this reason, we recommend only using screws without optimized thread tips (drilling tip, counter thread, ring thread, ground corrugated, self-clearing groove etc.), e.g. anchor screws, Pre. No. 0157, hex. wood screws DIN 571, Pre. No. 0192, Wüpfostat® screws, Pre No. 0186, 0198).