


QUICK-CHANGE MOUNT FOR BI-METAL CYLINDER SAWS



Problem-solver

Using the A4/A2 combination adapter, two diameters can be combined to drill open an existing hole.

A single mount for all diameters

Fast, convenient and safe

- Specialized adapters make it very easy and fast to change between different diameters.
- To change the saw, the mount does not need to be removed from the chuck or collet. This makes one-handed operation possible.

Very high precision and longevity

Very tight production tolerances and 3-surface shaft for considerably less vibration on the saw and optimum fitting in the chuck or collet → Longer service life of the cylinder saw and less wear on the bearing of the drive machine.

| Scope of delivery | | |
|---|---------------------|---------|
| Designation | Art. No. | P. Qty. |
| 3-Surface Shaft Mount, 14 - 152 mm dia. | 0632 900 000 | 1 |
| HSCO Center Drill, 110 mm long | - | |
| A4 Adapter, 14 - 30 mm dia. | - | |
| A2 Adapter, 32 - 152 mm dia. | - | |

| Accessories | | |
|--------------------------------|---------------------|---------|
| Designation | Art. No. | P. Qty. |
| HSCO Center Drill, 110 mm long | 0632 900 001 | 1 |
| A2 Adapter, 32 - 152 mm dia. | 0632 900 002 | 3 |
| A4/A2 Combination Adapter | 0632 900 003 | 1 |
| A4 Adapter, 14 - 30 mm dia. | 0632 900 004 | 2 |