



| Drill bit dia. in mm | Length in mm | For saws w/ dia. (mm) | Art. No. | P. Qty. |
|----------------------|--------------|-----------------------|-------------------|---------|
| 6 | 80 | 18–60 | 0630 120 1 | 1 |
| 8 | 80 | 64 | 0630 120 2 | |

HSS Center Drill

for HW hole saws (flat cut) and MBS HW hole saws



| Type | Center drill | For saws w/ dia. (mm) | Art. No. | P. Qty. |
|------------------------|--------------|-----------------------|-------------------|---------|
| Triang., 13 mm dia. | 630 120 1 | 32–60 | 0630 120 3 | 1 |
| | 630 120 2 | 64 | 0630 120 4 | |
| Mk-2 | | | 32–64 | |

Mounting Shaft

MBS for HW hole saws

- Complete with center drill and 2.5 mm Allen key for changing drill bit.
- Mounting shaft made of special hardened steel.



| Type | Center drill | For saws w/ dia. (mm) | Art. No. | P. Qty. |
|---------------------|---------------------------|-----------------------|-------------------|---------|
| Triang., 10 mm dia. | 0630 130 1 (6 x 60 mm) | 32–50 | 0630 130 3 | 1 |
| Triang., 13 mm dia. | | 51–90 | 0630 130 4 | |
| Mk-2 | 0630 120 2 (8 x 80 mm) | 32–90 | 0630 120 5 | |

Mounting Shaft

for HW hole saws (flat cut)

- Complete with center drill and 2.5 mm Allen key for changing drill bit.
- Mounting shaft made of special hardened steel.