

# Zebra Screwdriver with hexagon blade and spanner nut





## Slotted Screwdriver

Blade: Hexagon blade  
with spanner nut,  
nicromatt.

Drive: DIN 5264-A, ISO 2380  
Black Point.

\* without striking cap and spanner nut

 a mm    b mm	 A mm    B/C mm		 mm	 inch	Art. No.	
	A mm	B/C mm				
0.6 x 3.5	75	83/27	4/-	1/8 x 3 1/16"	<b>0613 421 035*</b>	1
0.8 x 4.0	90	96/31	5/8	5/32 x 3 5/8"	<b>0613 421 004*</b>	
1.0 x 5.5	100	96/31	5/8	7/32 x 4"	<b>0613 421 055</b>	
1.2 x 6.5	125	106/35	6/10	1/4 x 5"	<b>0613 421 065</b>	
1.6 x 8.0	150	114/38	8/13	5/16 x 6"	<b>0613 421 08</b>	
1.6 x 10.0	175	114/38	8/13	3/8 x 7"	<b>0613 421 10</b>	
2.0 x 12.0	200	120/40.5	10/16	1/2 x 8"	<b>0613 421 12</b>	



## Screwdriver Cross-recess (PH)

Blade: Hexagon blade  
with spanner nut,  
nicromatt.

Drive: DIN 5260-PH, ISO 8764-PH  
Black Point.

 PH	 A mm    B/C mm		 mm	 A inch	Art. No.	
	A mm	B/C mm				
PH1	80	96/31	5/8	3 1/8"	<b>0613 422 1</b>	1
PH2	100	106/35	6/10	4"	<b>0613 422 2</b>	
PH3	150	114/38	8/13	6"	<b>0613 422 3</b>	
PH4	200	120/40,5	10/16	8"	<b>0613 422 4</b>	