

SCREWDRIVER



1/4" tip

- Blade: round, bright chrome-plated
- Output: DIN 3126-A 6.3
- Fig. 1 - 1/4" Tip with continuous blade
- Fig. 2 - 1/4" Tip with flexible shaft
- Application: Mounting socket wrench inserts, square.

Fig.	Inch	A mm	B/C mm	A inch	Art. no.	PU/Qty.
1	1/4"	110	106/35	4 3/8inch	0613 430 310	1
2	1/4"	150	106/35	6"	0613 473 3	1



With 1/4" quick-change chuck

- Blade: Hexagon blade with spanner nut, brushed chromium-plated
- Head: bright-nickel-plated
- Output: DIN 3126-D 6.3
- Fig. 2 - with flexible shaft
- Application: Mounting bits, hexagon.

Fig.	Inch	A mm	B/C mm	mm	A inch	Art. no.	PU/Qty.
1	1/4"	110	106/35	6/10	4 3/8inch	0613 210 21	1
2	1/4"	177	106/35	-	6"	0613 280 21	1



With 1/4" bit holder

- Blade: Circular blade, with magnet
- Head: bright-nickel-plated
- Output: DIN 3126-D 6.3
- Application: Mounting bits, hexagon

Inch	A mm	B/C mm	A inch	Art. no.	PU/Qty.
1/4"	100	106/35	4"	0613 430 31	1