




VDE SCREWDRIVER



EN 60900, IEC 60900

- Routine check test in a water bath with test voltage 10 kV
- For working on live parts up to 1000 volts (AC) and up to 1500 volts (DC)
- Identification marking with the year of manufacture
- Cold impact test at -40 °C
- (Identification marking C)

 mm				Art. no.	PU/Qty.
	A mm	B/C mm	A inch		
0.30 x 1.5	40	100/20	1 5/16 inch	0613 486 015	1
0.30 x 1.8	60	100/20	2 3/8 inch	0613 486 018	1
0.40 x 2.0	60	100/20	2 3/8 inch	0613 486 020	1
0.40 x 2.5	75	100/20	3 inch	0613 486 025	1
0.50 x 3.0	75	100/20	3 inch	0613 486 030	1

VDE screwdriver, flat slotted

- Blade: Circular blade, insulated, bronzed
- Output: DIN 5264-A, ISO 2380,
- Standard: EN 60900, IEC 60900

 1000 V








VDE screwdriver, Phillips (PH)

- Blade: Circular blade, insulated, bronzed
- Output: ISO 8764-PH
- Standard: EN 60900, IEC 60900

 1000 V



				Art. no.	PU/Qty.
mm	A mm	B/C mm	A inch		
PH 00	40	100/20	1 5/16 inch	0613 487 00	1
PH 0	60	100/20	2 3/8 inch	0613 487 0	1

	Art. no.		Art. no.	PU/Qty.
mm		mm		
0.30 x 1.5	0613 486 015	PH 00	0613 487 00	1
0.30 x 1.8	0613 486 018	PH 0	0613 487 0	1
0.40 x 2.0	0613 486 020			1
0.40 x 2.5	0613 486 025			1
0.50 x 3.0	0613 486 030			1

Screwdriver set in plastic cassette VDE slotted and Phillips screwdrivers

Art. no. 0613 489 4

