

⚡ 1000 V



### VDE Screwdriver Cross recess (PZ)

Blade: gunmetal finish, insulated.

Tip: ISO 8764-PZ.

Standard: DIN 7445, IEC 900, EN 60900.

				Art. No.	
	A in mm	B/C in mm	A in inches		
PZ 0	80	83/27	3 1/8"	<b>0613 633 0</b>	1
PZ 1	80	96/31	3 1/8"	<b>0613 633 1</b>	
PZ 2	100	106/35	4"	<b>0613 633 2</b>	
PZ 3	150	114/38	6"	<b>0613 633 3</b>	



### VDE Socket Spanner for External Hexagon Screws

Blade: gunmetal finish, insulated.

Tip: DIN 475/2.

Standard: DIN 7445, IEC 900, EN 60900.

				Art. No.	
in mm	A in mm	B/C in mm	A in inches		
5.5	125	96/31	5"	<b>0613 636 055</b>	1
6.0	125	96/31	5"	<b>0613 636 06</b>	
7.0	125	106/35	5"	<b>0613 636 07</b>	
8.0	125	106/35	5"	<b>0613 636 08</b>	
9.0	125	106/35	5"	<b>0613 636 09</b>	
10.0	125	106/35	5"	<b>0613 636 10</b>	
11.0	125	114/38	5"	<b>0613 636 11</b>	
12.0	125	114/38	5"	<b>0613 636 12</b>	
13.0	125	114/38	5"	<b>0613 636 13</b>	



### Screwdriver Set

VDE Screwdriver  
for External Hexagon Screws

Art. No. 0613 936 66

	A	Art. No.		A	Art. No.	
in mm	in mm		in mm	in mm		
5.5	125	<b>0613 636 055</b>	8.0	125	<b>0613 636 08</b>	1
6.0	125	<b>0613 636 06</b>	10.0	125	<b>0613 636 10</b>	
7.0	125	<b>0613 636 07</b>	13.0	125	<b>0613 636 13</b>	