

Zebra VDE Screwdriver / EN 60900, IEC 900

1000 V



- Routine check test in a water bath with test voltage 10 kV.
- For work under voltages up to 1,000 volts (AC), up to 1,500 volts (DC).
- Identification marking with year of manufacture.
- Stricter low-temperature impact test.



VDE Screwdriver Flat

Blade: gunmetal finish, insulated.
Tip: DIN 5264-A, ISO 2380, conical blade.
Standard: DIN 7437, IEC 900, EN 60900.

a b in mm	A in mm	B/C in mm	b A in inches	Art. No.	
2.5	80	83/27	3/32 x 3 1/8"	0613 631 025	1
0.5 x 3.0	100	83/27	1/8 x 4"	0613 631 03	
0.6 x 3.5	100	83/27	1/8 x 4"	0613 631 035	
0.8 x 4.0	100	83/27	5/32 x 4"	0613 631 04	
1.0 x 5.5	125	96/31	7/32 x 5"	0613 631 055	
1.2 x 6.5	150	106/35	1/4 x 6"	0613 631 065	
1.2 x 8.0	175	114/38	5/16 x 7"	0613 631 08	
1.6 x 8.0	200	114/38	5/16 x 8"	0613 631 082	
1.6 x 10.0	200	114/38	3/8 x 8"	0613 631 10	



VDE Screwdriver Cross recess (PH)

Blade: gunmetal finish, insulated.
Tip: DIN 5260-PH, ISO 8764-PH.
Standard DIN 7438, IEC 900, EN 60900.

	A in mm	B/C in mm	A in inches	Art. No.	
	80	83/27	3 1/8"	0613 632 0	1
PH 1	80	96/31	3 1/8"	0613 632 1	
PH 2	100	106/35	4"	0613 632 2	
PH 3	150	114/38	6"	0613 632 3	
PH 4	200	114/38	8"	0613 632 4	